Intelligence Through the Lens of Interaction

Kiana Ehsani

A dissertation submitted in partial fulfillment of

the requirements for the degree of

Doctor of Philosophy

University of Washington

2021

Reading Committee:

Ali Farhadi, Chair

Roozbeh Mottaghi

Dieter Fox

Abhinav Gupta

Program Authorized to Offer Degree:

Computer Science and Engineering

©Copyright 2021

Kiana Ehsani

University of Washington

Abstract

Intelligence Through the Lens of Interaction

Kiana Ehsani

Chair of the Supervisory Committee:

Professor Ali Farhadi

Computer Science and Engineering

In this thesis, I will discuss the problem of acquiring visual intelligence from the interaction, focusing on two aspects of visual understanding: (1) visual perception and (2) embodied intelligence.

To address the first question, I designed experiments to learn visual representations by observing animals and humans interact with the visual world. Further, I investigated the idea of learning perception from hands-on interaction – acquiring generalizable physical understanding by predicting the forces applied in an observed video and trying to replicate the motion observed in simulation, with no additional supervision provided.

To address the second question, I discuss our findings on training intelligent embodied agents using interaction from two perspectives. I designed a training paradigm that enables learning-to-learn from interactions. This training regime helps us to continue to learn from our interactions even during inference time. Moreover, I introduce a visually rich object manipulation framework, ManipulaTHOR, which opens the gate for directly training embodied agents to interact intelligently in a physically realistic environment via low-level object manipulation and navigation.

To my parents,
for giving me wings and teaching me to fly.

Acknowledgement

First and foremost, I wish to express my sincere gratitude and thanks to my Ph.D. advisor, Professor Ali Farhadi, who has supported me throughout my endeavor. I am genuinely appreciative of his patience, motivation, enthusiasm, and immense knowledge. His guidance helped me throughout exciting research projects, extending my career after graduation, and making important career decisions. I could not have imagined having a better advisor and mentor.

I was fortunate to be co-advised by Professor Roozbeh Mottaghi. It is not often that one finds a mentor who always listens to the problems and roadblocks that a junior student faces during the research. His technical advice and mentorship were an essential component of my success and have taught me innumerable lessons and insights on the workings of academic research.

I would also like to thank my committee members, professor Dieter Fox, professor Abhinav Gupta, and professor Andrea Stocco for their contributions to the pleasant insightful discussion during the defense and their thoughtful comments and suggestions.

I would also like to thank all my fantastic co-authors who have contributed throughout different projects. I have learned a lot during my collaborations, and they have all had an undeniable impact on the researcher I have become today.

I would also like to acknowledge my family's support, especially my mother, my brother, and my father, for always believing that I can achieve whatever I set my mind on and encouraging me to follow what I cherish.

Finally, I would like to thank the most important and impactful staff at Paul G. Allen School of Computer Science and Engineering, Elise deGoede Dorough, the director of the graduate student

services, for her unconditional love and support for the students at the program. She is the linchpin of the school, and I genuinely believe I would have never been able to overcome the obstacles in graduate school without her help.

Contents

1 Introduction **21**

2 Learning Perception via Interaction **25**

2.1 Learning by Observing Interactions – From Dogs 25

2.1.1 Introduction 25

2.1.2 Related Work 27

2.1.3 Dataset 29

2.1.4 Acting like a dog 31

2.1.5 Planning like a dog 33

2.1.6 Learning from a dog. 34

2.1.7 Experiments 36

2.1.7.1 Implementation details 36

2.1.7.2 Evaluation metrics 39

2.1.7.3 Results 39

2.1.8 Conclusion 43

2.2 Learning by Observing Interactions – From Humans 43

2.2.1 Introduction 43

2.2.2 Related Work 45

2.2.3 Human Interaction Dataset 47

2.2.4 Interaction-based Representation Learning 48

2.2.5 Learning Features . . . 49
2.2.6 Adapting the Representation to New Tasks . . . 51
2.2.7 Experiments . . . 52
2.2.7.1 Self-Supervised Baseline . . . 52
2.2.7.2 Evaluation of the Learned Representation . . . 53
2.2.7.3 Ablative Analyses . . . 55
2.2.7.4 Visual Loss . . . 55
2.2.7.5 Movement Estimation . . . 55
2.2.7.6 Effects of the Body Parts . . . 56
2.2.8 Conclusion . . . 56
2.3 Learning by Performing Interactions . . . 57
2.3.1 Introduction . . . 57
2.3.2 Related Work . . . 59
2.3.3 Approach . . . 61
2.3.3.1 Interaction Dataset . . . 62
2.3.3.2 Supervisory Signal via Physical Simulation . . . 63
2.3.3.3 Putting it together: Joint Learning of Forces and Contact Points . 64
2.3.4 Experiments . . . 66
2.3.4.1 Qualitative Evaluation . . . 67
2.3.4.2 Quantitative Evaluation . . . 67
2.3.4.3 Few-shot Generalization to Novel Objects . . . 70
2.3.4.4 Additional Ablation Analysis . . . 72
2.3.5 Conclusion . . . 74

3 Learning to Interact via Interaction 75

3.1 Learning to Learn from Interactions . . . 75
3.1.1 Introduction . . . 75

3.1.2 Related Work . . . 77
3.1.3 Adaptive Navigation . . . 79
3.1.3.1 Task Definition . . . 79
3.1.3.2 Learning . . . 81
3.1.3.3 Learning to Learn . . . 81
3.1.3.4 Learning to Learn How to Learn . . . 84
3.1.3.5 Training and Testing . . . 86
3.1.4 Experiments . . . 88
3.1.4.1 Experiment setup . . . 88
3.1.4.2 Implementation details . . . 89
3.1.4.3 Evaluation metrics . . . 90
3.1.4.4 Baselines . . . 90
3.1.4.5 Results . . . 90
3.1.4.6 Ablation Study . . . 92
3.1.5 Conclusions . . . 94
3.2 Learning to interact . . . 94
3.2.1 Introduction . . . 94
3.2.2 Related Works . . . 97
3.2.3 ManipulaTHOR . . . 98
3.2.4 ARMPOINTNAV . . . 101
3.2.5 Model . . . 104
3.2.6 Experiments . . . 106
3.2.7 Conclusion . . . 110

4 Conclusion **113**

4.1 Future Research Direction . . . 114

List of Figures

1.1 **Outline of the Thesis.** Intelligence Through the Lens of Interaction. 22

2.1 We address three problems: (1) *Acting like a dog*: where the goal is to predict the future movements of the dog given a sequence of previously seen images. (2) *Planning like a dog*: where the goal is to find a sequence of actions that move the dog between the locations of the given pair of images. (3) *Learning from a dog*: where we use the learned representation for a third task (e.g., walkable surface estimation). 26

2.2 **Model architecture for acting.** The model is an encoder-decoder style neural network. The encoder receives a stream of image pairs, and the decoder outputs future actions for each joint. There is a fully connected layer (FC) between the encoder and decoder parts to better capture the change in the domain (change from images to actions). In the decoder, the output probability of actions at each timestep is passed to the next timestep. We share the weights between the two ResNet towers. 32

2.3 **Model architecture for planning.** The model is a combination of CNNs and an LSTM. The inputs to the model are two images I_1 and I_N, which are $N-1$ time steps apart in the video sequence. The LSTM receives the features from the CNNs and outputs a sequence of actions (joint movements) that move the dog from I_1 to I_N. 34

2.4 **Model architecture for walkable surface estimation.** We augment the last four layers of ResNet with Deconvolution and Convolution layers to infer walkable surfaces. 35

2.5 **Qualitative Results: Learning to Act.** Our model sees 5 frames of a video where a man begins throwing a ball past the dog. In the video the ball bounces past the dog and the dog turns to the right to chase the ball. Using just the first 5 frames our model correctly predicts how the dog turns to the right as the ball flies past. 40

2.6 We propose to use human's interactions with their visual surrounding as a training signal for representation learning. We record first person observations as well as the movements and gaze of people living their daily routines and use these cues to learn a visual embedding. We use the learned representation on a variety of diverse tasks and show consistent improvements compared to state-of-the-art self-supervised vision-only techniques. 45

2.7 **Dataset examples.** Two sequences from our dataset are shown on the left. The first row shows the sequence of the images and the second row shows the movements of the body parts according to the IMU readings. We visualize the gaze using the red circle. This is just for visualization purposes and does not exist in the image. On the right, we show the data collection setup. 48

2.8 **Model Overview.** We learn a muscly-supervisedrepresentation by jointly optimizing visual, movement and center of focus (gaze) objectives. The portion outlined with a rectangle is the backbone that is used to evaluate the representation for target tasks. All parts of the network are initialized randomly and trained from scratch. . . 49

2.9 We study the problem of physical understanding of human-object interactions by inferring object motion, points of contacts and forces from RGB videos. We use physics simulation to see how these interactions change the dynamics of the object and try to imitate the motion observed in the video. 59

2.10 **Dataset.** Showing two sample frames (drill and hammer) from our dataset. We collect annotation for semantic keypoints of the objects (Column 2) and human contact points. This data helps us to calculate object 6DOF pose (Column 3) and contact points on object mesh (Column 4). 62

2.11 **Training schema.** Given a video as input, the model predicts the forces and their corresponding contact points. We then apply these forces on the object mesh in physics simulation and jointly optimize for keypoint projection loss $\mathcal{L}_{keypoint}$ and contact point prediction loss $\mathcal{L}_{cp}$ with the aim to imitate the motion observed in the video. 64

2.12 **Model overview.** Given a video of a person moving an object, along with the initial pose of the object, our network predicts the human contact points and the forces applied at those for each time step. The implied effects of these forces can then be recovered by applying them in a physics simulation. Using the gradients through this simulated interaction, our model learns how to optimize for its two objectives: minimizing the error in projection of the object to camera frame, and predicting the accurate contact points. 65

2.13 **Qualitative Results.** We show the results for the model which optimizes for both $\mathcal{L}_{keypoint}$ and $\mathcal{L}_{cp}$. Due to space limitations only Frames for $t = 0, 4$ are shown. For more videos and contact point visualizations refer to supplementary material. . . . 68

2.14 **Improvements in contact point prediction after joint optimization.** We qualitatively show some examples for which the model makes better contact point predictions when it is trained using both $\mathcal{L}_{keypoint}$ and $\mathcal{L}_{cp}$. Fingers are color-coded (Thumb: orange, Index: Red, Middle: Blue, Ring: Green, Pinky: Purple). 69

2.15 **Few shot experiment.** Showing the keypoint projection error for the model that is trained on planes and fine-tuned on few examples for held out objects (Lower is better). The results are shown for 1, 5, or 10 examples, as well as the model trained on the whole training set. The red bar shows errors for training on 10 examples without plane pre-training. 71

2.16 **Robustness to initial pose.** The changes in the keypoint projection error with respect to the magnitude of the noise added to the initial state. We also calculated the error bars for 5 runs with different random seeds. The labels on the bottom of the chart show the magnitude of the noise in rotation in degrees and the one on the top shows the magnitude of noise in translation in meters. 73

3.1 Traditional navigation approaches freeze the model during inference (top row); this may result in difficulties generalizing to unseen environments. In this paper, we propose a meta-reinforcement learning approach for navigation, where the agent learns to adapt in a self-supervised manner (bottom row). In this example, the agent learns to adapt itself when it collides with an object once and acts correctly afterwards. In contrast, a standard solution (top row) makes multiple mistakes of the same kind when performing the task. 76

3.2 **Model overview.** Our network optimizes two objective functions, 1) self-supervised interaction loss $\mathcal{L}_{\text{int}}^{\phi}$ and 2) navigation loss $\mathcal{L}_{\text{nav}}$. The inputs to the network at each time t are the egocentric image from the current location and word embedding of the target object class. The network outputs a policy $\pi_{\theta}(s_t)$. During training, the interaction and navigation-gradients are back-propagated through the network, and the parameters of the self-supervised loss are updated at the end of each episode using navigation-gradients. At test time the parameters of the interaction loss remain fixed while the rest of the network is updated using interaction-gradients. Note that the green color in the figure represents the intermediate and final outputs. 80

3.3 **Qualitative examples.** We compare our method with the non-adaptive baseline. We illustrate the trajectory of the agent (white corresponds to the beginning of the trajectory and dark blue shows the end). Black arrows represent rotation. We also show the egocentric view of the agent at a few time steps. Our method may learn from its mistakes (e.g., getting stuck behind an object). 87

3.4 **Failed actions.** Our approach learns to adapt and not to take unsuccessful actions as the navigation proceeds. 92

3.5 **Number of Gradients Ablation.** Our success rate increases as more interaction-gradients are taken during training/testing. 93

3.6 We address the problem of *visual object manipulation*, where the goal is to move an object between two locations in a scene. Operating in visually rich and complex environments, generalizing to unseen environments and objects, avoiding collisions with objects and structures in the scene, and visual planning to reach the destination are among the major challenges of this task. Here, we illustrate a sequence of actions taken a by a virtual robot within the AI2-THOR environment for picking up a vase from the shelf and stack it on a plate on the countertop. 96

3.7 **Arm Design and Kinematic Constraints.** The arm consists of four joints (a). The max reach of the arm is defined by a hemisphere centered around the end of the first joint, whose radius is equal to 0.6335m (b,c). The height of the arm can be adjusted along the body of the agent (d). All joint rotations are solved by inverse kinematics, so any position the wrist can move to within the hemisphere's extents will have the joints rotate to accommodate the position of the wrist joint (e,f). 100

3.8 **Scene and object splits in APND.** In order to benchmark the performance on ARMPOINTNAV, in addition to providing a large pool of datapoints for training, we provide a small subset of tasks per data split. We randomly subsampled 60 tasks per object per scene for evaluation purposes. 101

3.9 **Dataset Samples.** The initial location of the object can pose a variety of challenges. In (a) the tomato is occluded by the bowl, therefore the agent needs to remove the bowl to reach the tomato. In (b) the lettuce is on the shelf, which requires the agent to move the arm carefully such that it does not collide with the shelf or the vase. In (c) The goal object is inside another object and in (d) the goal object is inside a receptacle, therefore it requires interacting with another entity (opening microwave's door) before reaching for the object. The latter case is outside the scope of this paper. 102

3.10 **Statistics of the dataset.** This plot presents the distribution of the initial distance of the object from the target location in meters. We mark the step size for the agent and the arm movements, and the average width of the rooms for reference. 103

3.11 **Architecture**. Our network uses the Depth (c=1), RGB (c=3) or RGBD (c=4) observations and the agent's arm relative location to the object to estimate the movements needed to pickup the target object and take it to the goal state while avoiding the unwanted collisions. 105

3.12 **Qualitative Results.** Our qualitative results illustrate our network's ability to generalize to picking up objects in novel environments and navigating the agent with the object in hand to the desired location. For example, row (c) shows a scenario from a third-perspective in which the agent needs to navigate in the kitchen while avoiding the collision with other objects (toaster, tomato and sink in this case). 106

3.13 **Comparison of SRwD rates based on the initial distance to goal.** The plot shows that our network's generalizability to novel scenes is superior to generalization to unseen objects. 108

List of Tables

2.1 Inferring the action between two consecutive frames. 38

2.2 **Acting Results.** We observe a video sequence of 5 frames and predict the next 5 actions. 39

2.3 **Planning Results.** Planning between the start and end frame. We consider start and end images that are 5 steps apart. 41

2.4 Continuous evaluation and all-joint evaluation. Lower is better in the first column. Higher is better in the second column. 41

2.5 **Walkable surface estimation.** We compare the result of the network that is trained on ImageNet with the network that is trained for our *acting* task. The evaluation metric is IOU. 42

2.6 **Target task results.** We compare the performance of our learned representation from movement and gaze cues with a recent self-supervised baseline MoCo [76] (which is trained on our data). Note that the MoCo baseline is trained using only visual data ('vis'). We evaluate the performance on a variety of different target tasks. 52

2.7 **Ablation of the visual loss.** The result of using an autoencoder for the visual loss. We re-train the models for the five target tasks. $\mathcal{L}_{att}$, $\mathcal{L}_{move}$ and $\mathcal{L}_{nce}$ are the ones used in Eq. 2.4. 54

2.8 **Body part movement prediction.** We investigate the correlation of the movement and attention by using the human gaze as an additional input to predict the body part movements. 56

2.9 **Ablation of body parts.** We show how the performance on the target tasks changes when we ignore a body part during representation learning. 57

2.10 **Contact point prediction and key point projection error on test set, independent vs. joint optimization** In each set, the first row shows the results of the model optimizing for contact point and keypoint projection error separately, and the second row represents the joint optimization results. End to end training improves the results for both contact point prediction and keypoint projection. In the table, $\mathcal{L}_{kp}$ denotes $\mathcal{L}_{keypoint}$ and input to the network is the RGB image. 70

2.11 **Predicting the forces using ground truth contact points** We first train a model to predict the forces on the ground-truth contact points. The first four rows show the quantitative results for training separate model per object using the $\mathcal{L}_{keypoint}$ objective and the last row shows the result for training one shared model for all 8 objects. 71

2.12 **Pseudo-ground truth force regression.** We trained a model to predict the pseudo-ground truth forces for toy airplane from video, initial pose and contact points as input, by directly optimizing for the force prediction ($\mathcal{L}_{force}$). Although the training error is similar to the model trained on keypoint projection loss, it fails to generalize to unseen images and trajectories. 72

2.13 **Predicting initial state.** The result for the model trained on toy plane object set, predicting the initial pose as well as the forces on ground truth contact points. To see how the error in object initial pose estimation is affecting the performance, we input the ground-truth object pose to the model as input during inference to compare. This model is trained with $\mathcal{L}_{keypoint}$ objective. 73

3.1 **Quantitative results.** We compare variations of our method with random, nearest neighbor and non-adaptive baselines. We consider two evaluation metrics, Success Rate and SPL. We provide results for all targets 'All' and a subset of targets whose optimal trajectory length is greater than 5. We report the average over 5 training runs with standard deviations shown in sub-scripted parentheses. 91

3.2 **Ablation results.** We compare our approach with the non-adaptive baseline augmented with memory and our hand-crafted loss. We also provide the result when we use ground truth object information (bottom two rows). 93

3.3 **Quantitative results.** The performance of our network on different data splits. Our experiments show that our trained agent can generalize to novel scenes and objects. 108

3.4 **Ablation Studies.** We study ablations of our network using different combinations of sensors as well as architecture design. Input sensors that are used by these networks are a subset of GPS (G), Depth (D) and RGB (R) sensors. 110

Chapter 1

Introduction

Deep learning has made an impressive impact on the computer vision community. These extensive efforts have been made towards building intelligent models that can perceive the visual world through the pre-recorded images. Intelligence is usually defined through a set of proxy tasks. During the past decade, the focus has been on tackling the image perception problem in the form of image understanding, such as image classification, object detection, segmentation, depth estimation, and more.

A popular learning pipeline for solving these proxy tasks is to learn passively from an unchanged set of images or videos, predicting a fixed set of semantic or non-semantic labels. The standard approach is to collect a dataset of images with their corresponding labels annotating the labels for each specific task. Once the task is defined, the data is annotated, and the network architecture is designed, the model will be trained. Data, model, and labels will remain unchanged after the training is over and during the inference time.

There has been great progress using these pipelines of supervised learning in computer vision. We can classify images [185; 85], detect objects, and localize them in an image[114; 224], and segment and map the pixels of the image to their corresponding entities[77; 156]. The community has come a long way to make these models faster, more accurate, and more efficient.

Despite the undeniable progress and impact of the works in this area, these approaches can




Figure 1.1: **Outline of the Thesis.** Intelligence Through the Lens of Interaction.

introduce multiple dilemmas. The first problem is “How can we define the labels for intelligence?". These labels can be defined in various ways, such as annotating the locations of objects in a scene or estimating the depth of an observed image. However, defining the label for a task becomes exceptionally complex when dealing with a higher-level concept, such as acting like an intelligent human. Furthermore, the more vague the definition of the task is, the harder it becomes to provide labeled data to solve the problem. The second problem arises when the data we are working with changes. For example, we might train an agent to learn how to manipulate skillets, but it later needs to work with a novel object such as a bowl. “Do we have to reprocess the full pipeline of data collection, annotation, and training a model for each novel object we observe?". The third problem is that our environments are constantly changing. There is no wall between training or inference. We learn as we are performing a task. We gain knowledge about novel environments by interacting with them. “Why should our models remain unchanged during inference time?".

In this thesis, I would like to define intelligence in a more interactive approach. First, I would discuss how to learn perception using interactions with the visual world (Setion 2). In Section 2.1 and 2.2, I describe how to learn a visual representation by observing the intelligent agents (humans

and dogs) interact with the environment. I investigate the additional cues that can help with the learning process. More specifically, I evaluate the effectiveness of adding movements and attention of these agents toward learning a rich visual representation without additional semantic labels. Furthermore, in Section 2.3, I will explain how to learn about the forces applied to an object by observing an interaction and trying to replicate the motion in a physics simulation. Using the interaction's feedback, we acquire a rich physical understanding that enables us to generalize to unseen objects.

Although visual perception can benefit from interaction with the world, there is still a gap between passive visual perception and having the ability to take actions. Interacting with the world can change the data that is received. In Section 3, I discuss how to use interaction to learn how to interact. More specifically, in Section 3.1, I propose building models that use interaction to become more robust to change. I explain a pipeline that allows continuing the learning process after the training is done and as the task is being performed. Further, In section 3.2, I introduce ManipulaTHOR, a framework we built that enables interacting with the visually rich physically realistic environments.

Publication

Portion of the thesis has been appeared in the following publications:

- **"ManipulaTHOR: A Framework for Visual Object Manipulation"**
  K Ehsani, W Han, A Herrasti, E VanderBilt, L Weihs, E Kolve, A Kembhavi, R Mottaghi (CVPR'21, Oral)

- **"What Can You Learn From Your Muscles? Learning Visual Representation from Human Interactions"**
  K. Ehsani, D. Gordon, T. Nguyen, R. Mottaghi, A. Farhadi (ICLR'21)

- **"Use the Force, Luke! Learning to Predict Physical Forces by Simulating Effects"**
  K. Ehsani, S. Tulsiani, S. Gupta, A. Farhadi, A. Gupta (CVPR20, Oral)

◇ **“Learning to Learn How to Learn: Self-Adaptive Visual Navigation Using Meta-Learning"**

M. Wortsman, K Ehsani, M. Rastegari, A. Farhadi, R. Mottaghi (CVPR’19, Oral)

◇ **“Who Let The Dogs Out? Modeling Dog Behavior From Visual Data"**

K.Ehsani, H.Bagherinezhad, J. Redmon, R. Mottaghi, A. Farhadi (CVPR’18)

Chapter 2

Learning Perception via Interaction

2.1 Learning by Observing Interactions – From Dogs

2.1.1 Introduction

Computer vision research typically focuses on a few well defined tasks including image classification, object recognition, object detection, image segmentation, etc. These tasks have organically emerged and evolved over time as proxies for the actual problem of visual intelligence. Visual intelligence spans a wide range of problems and is hard to formally define or evaluate. As a result, the proxy tasks have served the community as the main point of focus and indicators of progress.

We value the undeniable impact of these proxy tasks in computer vision research and advocate the continuation of research on these fundamental problems. There is, however, a gap between the ideal outcome of these proxy tasks and the expected functionality of visually intelligent systems. In this paper, we take a direct approach to the problem of visual intelligence. Inspired by recent work that explores the role of action and interaction in visual understanding [226; 7; 150], we define the problem of visual intelligence as *understanding visual data to the extent that an agent can take actions and perform tasks in the visual world.* Under this definition, we propose to learn to act like a visually intelligent agent in the visual world.




Figure 2.1: We address three problems: (1) *Acting like a dog*: where the goal is to predict the future movements of the dog given a sequence of previously seen images. (2) *Planning like a dog*: where the goal is to find a sequence of actions that move the dog between the locations of the given pair of images. (3) *Learning from a dog*: where we use the learned representation for a third task (e.g., walkable surface estimation).

Learning to act like visually intelligent agents, in general, is an extremely challenging and a hard-to-define problem. Actions correspond to a wide range of movements with complicated semantics. In this paper, we take a small step towards the problem of learning to directly act like intelligent agents by considering actions in their most basic and semantic-free form: simple movements.

We choose to model a dog as the visual agent. Dogs have a much simpler action space than, say, a human, making the task more tractable. However, they clearly demonstrate visual intelligence, recognizing food, obstacles, other humans and animals, and reacting to those inputs. Yet their goals

and motivations are often unknown a priori. They simply exist as sovereign entities in our world. Thus we are modelling a black box where we only know the inputs and outputs of the system.

In this paper, we study the problem of learning to act and plan like a dog from visual input. We compile the Dataset of Ego-Centric Actions in a Dog Environment (DECADE), which includes ego-centric videos of a dog with her corresponding movements. To record movements we mount Inertial Measurement Units (IMU) on the joints and the body of the dog. We record the absolute position and can calculate the relative angle of the dog's main limbs and body.

Using DECADE, we explore three main problems in this paper (Figure 2.1): (1) learning to act like a dog; (2) learning to plan like a dog; and (3) using dogs movements as supervisory signal for representation learning.

In *learning to act like a dog*, we study the problem of predicting the dog's future moves, in terms of all the joint movements, by observing what the dog has observed up to the current time. In *learning to plan like a dog*, we address the problem of estimating a sequence of movements that take the state of the dog's world from what is observed at a given time to a desired observed state. In *using dogs as supervision*, we explore the potentials of using the dogs movements for representation learning.

Our evaluations show interesting and promising results. Our models can predict how the dog moves in various scenarios (act like a dog) and how she decides to move from one state to another (plan like a dog). In addition, we show that the representation our model learns on dog behavior generalizes to other tasks. In particular, we see accuracy improvements using our dog model as pretraining for walkable surface estimation and scene recognition.

2.1.2 Related Work

To the best of our knowledge there is little to no work that directly models dog behavior. We mention past work that is most relevant.

Visual prediction. [218; 149] predict the motion of objects in a static image using a large collection

of videos. [145] infer the goals of people and their intended actions. [158] infer future activities from a stream of video. [63] improve tracking by considering multiple hypotheses for future plans of people. [83] recognize partial events, which enables early detection of events. [99] perform activity forecasting by integrating semantic scene understanding with optimal control theory. [104] use object affordances to predict the future activities of people. [205] localize functional objects by predicting people's intent. [182] propose an unsupervised approach to predict possible motions and appearance of objects in the future. [106] propose a hierarchical approach to predict a set of actions that happen in the future. [154] propose a method to generate the future frames of a video. [103] predict the future paths of pedestrians from a vehicle camera. [167] predict future trajectories of a person in an ego-centric setting. [126] predict the future trajectories of objects according to Newtonian physics. [181] predict visual representations for future images. [220] forecast future frames by learning a policy to reproduce natural video sequences. Our work is different from these works since our goal is to predict the behavior of a dog and the movement of the joints from an ego-centric camera that captures the viewpoint of the dog.

Sequence to sequence models. Sequence to sequence learning [173] has been used for different applications in computer vision such as representation learning [169], video captioning [179; 212], human pose estimation [184], motion prediction [118], or body pose labeling and forecasting [55; 184]. Our model fits into this paradigm since we map the frames in a video to joint movements of the dog.

Ego-centric vision. Our work is along the lines of ego-centric vision (e.g., [50; 152; 107; 109]) since we study the dog's behavior from the perspective of the dog. However, dogs have less complex actions compared to humans, which makes the problem more manageable. Prior work explores future prediction in the context of ego-centric vision. [225] infer the temporal ordering of two snippets of ego-centric videos and predict what will happen next. [139] predict plausible future trajectories of ego-motion in ego-centric stereo images. [94] estimates the 3D joint position of unseen body joints using ego-centric videos. [157] use online reinforcement learning to forecast the

future goals of the person wearing the camera. In contrast, our work focuses on predicting future joint movements given a stream of video.

Ego-motion estimation. Our planning approach shares similarities with ego-motion learning. [223] propose an unsupervised approach for camera motion estimation. [187] propose a method based on combination of CNNs and RNNs to perform ego-motion estimation for cars. [120] learn a network to estimate relative pose of two cameras. [178] also train a CNN to learn depth map and motion of the camera in two consecutive images. In contrast to these approaches that estimate translation and rotation of the camera, we predict a sequence of joint movements. Note that the joint movements are constrained by the structure of the dog body so the predictions are constrained.

Action inference & Planning. Our dog planning model infers the action sequence for the dog given a pair of images showing before and after action execution. [7] also learn the mapping between actions of a robot and changes in the visual state for the task of pushing objects. [140] optimize for actions that capture the state changes in an exploration setting.

Inverse Reinforcement Learning. Several works (e.g., [2; 12; 157]) have used Inverse Reinforcement Learning (IRL) to infer the agent's reward function from the observed behavior. IRL is not directly applicable to our problem since our action space is large and we do not have multiple training examples for each goal.

Self-supervision. Various research explores representation learning by different self-supervisory signals such as ego-motion [5; 92], spatial location [41], tracking in video [189], colorization [221], physical robot interaction [150], inpainting [144], sound [138], etc. As a side product, we show we learn a useful representation using embeddings of joint movements and visual signals.

2.1.3 Dataset

We introduce DECADE, a dataset of ego-centric dog video and joint movements. The dataset includes 380 video clips from a camera mounted on the dog's head. It also includes corresponding information about body position and movement. Overall we have 24500 frames. We use 21000 of

them for training, 1500 for validation, and 2000 for testing. Train, validation, and test splits consist of disjoint video clips.

We use a GoPro camera on the dog's head to capture the ego-centric videos. We sub-sample frames at the rate of 5 fps. The camera applies video stabilization to the captured stream. We use inertial measurement units (IMUs) to measure body position and movement. Four IMUs measure the position of the dog's limbs, one measures the tail, and one measures the body position. The IMUs enable us to capture the movements in terms of angular displacements.

For each frame, we have the absolute angular displacement of the six IMUs. Each angular displacement is represented as a 4 dimensional quaternion vector. More details about angular calculations in this domain and the method for quantizing the data is explained in detail in Section 2.1.7. The absolute angular displacements of the IMUs depend on what direction the dog is facing. For that reason, we compute the difference between angular displacements of the joints, also in the quaternion space. The difference of the angular displacements between two consecutive frames (that is $0.2s$ in time) represents the action of the dog in that timestep.

An Arduino on the dog's back connects to the IMUs and records the positional information. It also collects audio data via a microphone mounted on the dog's back. We synchronize the GoPro with the IMU measurements using audio information. This allows us to synchronize the video stream with the IMU readings with microsecond precision. We collect the data in various outdoor and indoor scenes: living room, stairs, balcony, street, and dog park are examples of these scenes. The data is recorded in more than 50 different locations. We recorded the behavior of the dog while involved in certain activities such as walking, following, fetching, interaction with other dogs, and tracking objects. No annotations are provided for the video frames, we use the raw data for our experiments.

2.1.4 Acting like a dog

We predict how the dog acts in the visual world in response to various situations. Specifically, we model the future actions of the dog given a sequence of previously seen images. The input is a sequence of image frames $(I_1, I_2, \ldots, I_t)$, and the output is the future actions (movements) of each joint j at each timestep $t < t' \leq N$: $(a^j_{t+1}, a^j_{t+2}, \ldots, a^j_{t+N})$. Timesteps are spaced evenly by $0.2s$ in time. The action a^j_t is the movement of the joint j, that along with the movements of other joints, takes us from image frame I_t to I_{t+1}. For instance, a^2_3 represents the movement of the second joint that takes place between image frames I_3 and I_4. Each action is the change in the orientation of the joints in the 3D space.

We formulate the problem as classification, i.e. we quantize joint angular movements and label each joint movement as a ground-truth action class. To obtain action classes, we cluster changes in IMU readings (joint angular movements) by K-means, and we use quaternion angular distances to represent angular distances between quaternions. Each cluster centroid represents a possible movement of that joint.

Our movement prediction model is based on an encoder-decoder architecture, where the goal is to find a mapping between input images and future actions. For instance, if the dog sees her owner with a bag of treats, there is a high probability that the dog will sit and wait for a treat, or if the dog sees her owner throwing a ball, the dog will likely track the ball and run toward it.

Figure 2.2 shows our model. The encoder part of the model consists of a CNN and an LSTM. At each timestep, the CNN receives a pair of consecutive images as input and provides an embedding, which is used as the input to the LSTM. That is, the LSTM cell receives the features from frames t and $t + 1$ as the input in a timestep, and receives frames $t + 1$ and $t + 2$ in the next timestep. Our experimental results show that observing the two frames in each timestep of LSTM improves the performance of the model. The CNN consists of two towers of ResNet-18 [78], one for each frame, whose weights are shared.

The decoder's goal is to predict the future joint movements of the dog given the embedding of




Figure 2.2: **Model architecture for acting.** The model is an encoder-decoder style neural network. The encoder receives a stream of image pairs, and the decoder outputs future actions for each joint. There is a fully connected layer (FC) between the encoder and decoder parts to better capture the change in the domain (change from images to actions). In the decoder, the output probability of actions at each timestep is passed to the next timestep. We share the weights between the two ResNet towers.

the input frames. The decoder receives its initial hidden state and cell from the encoder. At each timestep, the decoder outputs the action class for each of the joints. The input to the decoder at the first timestep is all zeros, at all other timesteps, we feed in the prediction of the last timestep, embedded by a linear transformer. Since we train the model with fixed output length, no stop token is required and we always stop at a fixed number of steps. Note that there are a total of six joints; hence our model outputs six classes of actions at each timestep.

Each image is given to the ResNet tower individually and the features for the two images are concatenated. The combined features are embedded into a smaller space by a linear transformation. The embedded features are fed into the encoder LSTM. We use a ResNet pre-trained on ImageNet [37] and we fine-tune it under a Siamese setting to estimate the joints movements between two consecutive frames. We use the fine-tuned ResNet in our encoder-decoder model.

We use an average of weighted class entropy losses, one for each joint, to train our encoder-

decoder. Our loss function can be formulated as follows:

$$L(o, g) = \frac{1}{NK} \sum_{t=1}^{N} \sum_{i=1}^{K} \frac{1}{f_{g_i}^i} \log o(t)_{g(t)_i}^i, \tag{2.1}$$

where $g(t)_i$ is the ground-truth class for i-th joint at timestep t, $o(t)_{g_i}^i$ is the predicted probability score for g_i-th class of i-th joint at timestep t, $f_{g_i}^i$ is the number of data points whose i-th joint is labeled with g_i, K is the number of joints, and N is the number of timesteps. The $\frac{1}{f_{g_i}^i}$ factor helps the ground-truth labels that are underrepresented in the training data.

2.1.5 Planning like a dog

Another goal is to model how dogs plan actions to accomplish a task. To achieve this, we design a task as follows: Given a pair of non-consecutive image frames, plan a sequence of joint movements that the dog would take to get from the first frame (starting state) to the second frame (ending state). Note that a traditional motion estimator would not work here. Motion estimators infer a translation and rotation for the camera that can take us from an image to another; in contrast, here we expect the model to plan for the actuator, with its set of feasible actions, to traverse from one state to another.

More formally, the task can be defined as follows. Given a pair of images (I_1, I_N), output an action sequence of length $N - 1$ for each joint, that results in the movement of the dog from the starting point, where I_1 is observed, to the end point, where I_N is observed.

Each action that the dog takes changes the states of the world, and therefore planning for the next steps. Thus, we design a recurrent neural network, containing an LSTM that observes the actions taken by the model in previous timesteps for the next timestamp action prediction. Figure 2.3 shows the overview of our model. We feed-forward image frames I_1 and I_N to individual ResNet-18 towers, concatenate the features from the last layer and feed it to the LSTM. At each timestep, the LSTM cell outputs planned actions for all six joints. We pass the planned actions for a timestep as the input of the next timestep. This enables the network to plan the next movements conditioned on




Figure 2.3: **Model architecture for planning.** The model is a combination of CNNs and an LSTM. The inputs to the model are two images I_1 and I_N, which are $N-1$ time steps apart in the video sequence. The LSTM receives the features from the CNNs and outputs a sequence of actions (joint movements) that move the dog from I_1 to I_N.

the previous actions. As opposed to making hard decisions about the previously taken actions, we pass the action probabilities as the input to the LSTM in the next timestep. A low probability action at the current timestep might result in a high probability trajectory further along in the sequence. Using action probabilities prevents early pruning to keep all possibilities for the future actions.

We train this recurrent neural network using a weighted cross entropy loss over all time steps and joints as described in Equation 2.1. Similar to the *acting* problem, we use a discretized action space, which is obtained using the procedure described in Section 2.1.7.

2.1.6 Learning from a dog.

While learning to predict the movements of the dog's joints from the images that the dog observes we obtain an image representation that encodes different types of information. To learn a representation, we train a ResNet-18 model to estimate the current dog movements (the change in the IMUs from time $t-1$ to t) by looking at the images that the dog observes in time $t-1$ and t. We then test




Figure 2.4: **Model architecture for walkable surface estimation.** We augment the last four layers of ResNet with Deconvolution and Convolution layers to infer walkable surfaces.

this representation, and compare with a ResNet-18 model trained on ImageNet, in a different task using separate data. For our experiments we choose the task of walkable surface estimation [128] and scene categorization using SUN397 dataset [203]. Figure 2.4 depicts our model for estimating the walkable surfaces from an image. To showcase the effects of our representation, we replace the ResNet-18 part of the model shown in blue with a ResNet trained on ImageNet and compare it with a ResNet trained on DECADE.

2.1.7 Experiments

We evaluate our models on (1) how well they can predict the future movements of the dog (acting), (2) how accurately they can plan like a dog, and (3) how well the representation learned from dog data generalizes to other tasks.

2.1.7.1 Implementation details

We use inertial measurement units (IMUs) to obtain the angular displacements of the dog's joints. The IMUs that we use in this project process the angular displacements internally and provide the absolute orientation in quaternion form at average rate of 20 readings per second. To synchronize all IMUs together, we connect all the IMUs to the same embedded system (Raspberry pi 3.0). We use a GoPro on the dog's head to capture ego-centric video, and we sub-sample the images at a rate of 5 frames per second. To sync the GoPro and Raspberry pi, we use audio that has been recorded on both instruments.

The rate of the joint movement readings and video frames are different. We perform interpolation and averaging to compute the absolute angular orientation for each frame. For each frame of the video, we compute the average of IMU readings, in quaternion space, corresponding to a window of 0.1 second centered at the current frame.

To factor out the effects of global orientation change we use the relative orientations rather than the absolute ones. We compute the difference of absolute angular orientations corresponding to consecutive frames after calculating the average of quaternions for each frame. The reason for using quaternions, instead of Euler angles, is that subtracting two quaternions is more well-defined and is easily obtained by:

$$q_2 - q_1 = q_1^{-1} q_2$$

We use K-means clustering to quantize the action space (space of relative joint movements).

The distance function that we use for K-means clustering is defined by:

$$\text{dist}(q_1, q_2) = 2\text{arccos}(\langle q_1, q_2 \rangle)$$

The reason for formulating the problem as classification rather than regression is that our experimental evaluations showed that CNNs obtain better results for classification (as opposed to regression to continuous values). The same observation has been made by [183; 188; 130], where they also formulate a continuous value estimation problem as classification.

We treat each joint separately during training. It is more natural to consider all joints together for classification to respect the kinematic constraints, however it should be noted that: (1) It is hard to collect enough training data for all possible joint combinations (3910 different joint configurations appear in our training data); (2) By combining the losses for all joints, the model encodes an implicit model of kinematic possibilities; (3) Our experiments showed that per-joint clustering is better than all-joint clustering.

To visualize the dog movements we use a 3D model of a dog from [229]. Their model is a 3D articulated model that can represent animals, such as dogs. For visualization, we apply the movement estimates from the model to the dog model.

Learning to Act. The input to the acting network, explained in Section 2.1.4, are pairs of frames of size 224×224 and the output is a sequence of movements predicted for future actions of the dog. The input images are fed into two ResNet-18 towers with shared weights. The outputs of the ResNets (the layer before the classification layer), which are of size 512, are concatenated into a vector of size 1024. The image vector is then used as the input to the encoder LSTM. The encoder LSTM has a hidden size of 512, and we set the initial hidden and cell states to all zeros.

The hidden and cell state of the last LSTM cell of the encoder are used as the initialization of the hidden and cell state of the LSTM for the decoder part. There is a fully connected layer before the input to the decoder LSTM to capture the domain change between the encoder and the decoder

Model	Test Accuracy
Nearest Neighbor	13.14
CNN - regression	12.73
Our Model – Single Tower	18.65
Our Model	**20.69**

Table 2.1: Inferring the action between two consecutive frames.

(encoder is in the image domain, while the decoder in the joint movement domain).

The output of each decoder LSTM cell is then fed into 6 fully connected layers, where each one estimates the action class for each joint. We consider 8 classes of actions for each joint. We visualized our training data for different number of clusters and observed that 8 clusters provide a reasonable separation of clusters, does not result in false clusters, and clusters correspond to natural movements of the limbs.

We pre-train the ResNets by fine-tuning them for the task of estimating the joint actions, where we use a pair of consecutive frames as input and we have 6 different classification layers corresponding to different joints.

Learning to Plan. For the planning network, the input is obtained by concatenation of the ResNet-18 features for the source and destination input images (a vector of size 2048). A fully connected layer receives this vector as input and converts it to a 512 dimensional vector, which is then used as the first time step input for the LSTM. The LSTM output is 48 dimensional (6 joints $\times$ 8 action class). The output is followed by a 48×512 fully connected layer. The output of the fully connected layer is used as the input of the LSTM at the next timestep.

Learning from a dog. To obtain the representation, we train a ResNet-18 model to estimate the dog movements from time $t-1$ to time t by looking at the images at time $t-1$ and t. We use a simple Siamese network with two ResNet-18 towers whose weights are shared. We concatenate the features of both frames into a 1024-dimensional vector and use a fully connected layer to predict the final 48 labels (6 IMUs each having 8 class of values). Table 2.1 shows our results on how well this network can predict the current (not future) movements of the dog. The evaluation metric is the

Model	Test Accuracy	Perplexity
Nearest Neighbor	12.64	N/A
CNN	19.84	0.2171
Our Model–1 tower	18.04	0.2023
Our Model–1 frame/timestep	19.28	0.242
Our Model	**21.62**	**0.2514**

Table 2.2: **Acting Results.** We observe a video sequence of 5 frames and predict the next 5 actions. class accuracy described below. We use this base network to obtain our image representation. We also use this network for initializing our acting and planning networks.

2.1.7.2 Evaluation metrics

We use different evaluation metrics to compare our method with the baselines.

Class Accuracy: This is the standard metric for classification tasks. We report the average per class accuracy rather than the overall accuracy for two reasons: 1) The dataset is not uniformly distributed among the clusters and we do not want to favor larger clusters over smaller ones, and 2) Unlike the overall unbalanced accuracy, the mean class accuracy of a model that always predicts the mode class is not higher than chance.

Perplexity: Perplexity measures the likelihood of the ground-truth label. Perplexity is commonly used for sequence modeling. We report perplexity for all of the baselines and models that are probabilistic and predict a sequence. If our model assigns probability p to a sequence of length n, the perplexity measure is calculated as $p^{\frac{1}{n}}$.

2.1.7.3 Results

Learning to act like a dog. Table 2.2 summarizes our experimental results for predicting the future movements of the dog using the images the dog observes. We compare our method with two baselines in terms of both test set accuracy and perplexity. The Nearest Neighbors baseline uses the features obtained from a ResNet18 network trained on ImageNet. The CNN baseline concatenates all the images into an input tensor for a ResNet18 model that classifies the future actions. We also




Figure 2.5: **Qualitative Results: Learning to Act.** Our model sees 5 frames of a video where a man begins throwing a ball past the dog. In the video the ball bounces past the dog and the dog turns to the right to chase the ball. Using just the first 5 frames our model correctly predicts how the dog turns to the right as the ball flies past.

report two ablations of our model. The 1 tower ablation uses the model depicted in Figure 2.2 but only uses one ResNet-18 tower with both frames concatenated (6 channels) as the input. We also compare our model with an ablation that only uses one image at each timestep instead of looking at two. Our results show that our model outperforms the baselines. Our ablations also show the importance of different components in our model. Figure 2.5 shows an example where a man is throwing a ball past the dog. Our model correctly predicts the future dog movements (the bottom row) by only observing the images the dog observed in the previous time steps (the first row). The second row shows the set of images the dog actually observed. These images were not shown to the algorithm and are depicted here to better render the situation.

Learning to plan like a dog. Table 2.3 shows our experimental results for the task of planning. The nearest neighbor baseline concatenates the image features obtained from a ResNet-18 trained

Model	Test Accuracy	Perplexity
Nearest Neighbor	14.09	N/A
CNN	14.61	0.1419
Our Model	**19.77**	**0.2362**

Table 2.3: **Planning Results.** Planning between the start and end frame. We consider start and end images that are 5 steps apart.

Model	Angular metric	All joints
Random	131.70	4e-4
CNN-acting	63.42	8.67
Our model-acting	**59.61**	**9.49**
CNN-planning	76.18	0.14
Our model-planning	**63.14**	**3.66**

Table 2.4: Continuous evaluation and all-joint evaluation. Lower is better in the first column. Higher is better in the second column.

on ImageNet and searches for a plan of the required size that corresponds to the closest feature. The CNN baseline concatenates the input source and destination images into an input tensor that feeds into a ResNet-18 that predicts a plan for the required size. Our results show that our model outperforms these baselines in the challenging task of planning like a dog both in terms of accuracy and perplexity.

To better understand the behavior of the model, for both acting and planning, we show the performance in terms of a continuous angular metric and also for all joints in Table 2.4. The angular metric compares the mean of the predicted cluster with the actual continuous joint movements in groundtruth ($\arccos(2(q_{pred} \cdot q_{gt})^2 - 1)$), where q_{pred} and q_{gt} are the predicted and groundtruth quaternion angles, respectively. The all-joint metric calculates the percentage of correct predictions, where we consider a prediction correct if all joints are predicted (classified) correctly.

Learning from a dog. We test our hypothesis about the information encoded in our representation learned from mimicking dogs behaviour by comparing our representation with a similar one trained for image classification on ImageNet on a third task. We chose the task of walkable surface estimation and scene classification.

1) Walkable surface estimation. The goal for this task is to label pixels that correspond to

Model	Pre-training task	IOU
ResNet-18	ImageNet Classification	42.88
ResNet-18	Acting like a dog	**45.60**

Table 2.5: **Walkable surface estimation.** We compare the result of the network that is trained on ImageNet with the network that is trained for our *acting* task. The evaluation metric is IOU.

walkable regions in an image (e.g., floor, rug, and carpet regions). We use the dataset provided by [128]. In our dataset, we have some sequences of dog walking in indoor and outdoor scenes. There are various types of obstacles (e.g., furniture, people, or walls) in the scenes that the dog avoids. We conjecture that the learned representation for our network should provide strong cues for estimating walkable surfaces.

The definition of walkable surfaces for humans and dogs is not the same. As an example, the area under the tables are labeled as non-walkable for humans and walkable for dogs. However, since our dog is large-size dog, the definition of walkability is roughly the same for humans and the dog.

We trained ResNet-18 on ImageNet and then finetuned it on the walkable surface dataset as our baseline. We performed the same procedure for using our features (trained for the *acting* task). For finetuning both models, we just update the weights for the last convolutional layer (green block in Figure 2.4).

Table 2.5 shows the results. Our features provide a significant improvement, 3%, over the ImageNet features. We use IOU as the evaluation metric. This indicates that our features have some information orthogonal to the ImageNet features.

2) Scene classification. We perform an additional scene recognition experiment using SUN 397 dataset [203]. We used the same 5-instance training protocol used by [5]. The representation learned by us obtains the accuracy of 4.48 (as a point of reference [92] achieves 1.58 and [5] achieves 0.5-6.4 from their representations, and the chance is 0.251). This is interesting since our dataset does not include many of the scene types (gas station, store, etc).

2.1.8 Conclusion

We study the task of directly modeling a visually intelligent agent. Our model learns from egocentric video and movement information to act and plan like a dog would in the same situation. We see some success both in our quantitative and qualitative results. Our experiments show that our models can make predictions about future movements of a dog and can plan movements similar to the dog.

This is a first step towards end-to-end modelling of intelligent agents. This approach does not need manually labeled data or detailed semantic information about the task or goals of the agent. We can use this model on a wide variety of agents and scenarios and learn useful information despite the lack of semantic labels.

For this work, we limit ourselves to only considering visual data. However, intelligent agents use a variety of input modalities when interacting with the world including sound, touch, smell, etc. We are interested in expanding our models to encompass more input modalities in a combined, end-to-end model. We also limit our work to modelling a single, specific dog. It would be interesting to collect data from multiple dogs and evaluate generalization across dogs. We hope this work paves the way towards better understanding of visual intelligence and of the other intelligent beings that inhabit our world.

2.2 Learning by Observing Interactions – From Humans

2.2.1 Introduction

Encoding visual information from pixel space to a lower-dimensional vector is the core element of most modern deep learning-based solutions to computer vision. A rich set of algorithms and architectures have been developed to enable learning these encodings. A common practice in computer vision is to explicitly train the networks to map visual inputs to a curated label space.

For example, a neural network is pre-trained using a large-scale annotated classification dataset [39; 105] and the entire network or part of it is fine-tuned to a new target task [65; 219].

In recent years, weakly supervised and self-supervised representation learning approaches (e.g., [116; 76; 28]) have been proposed to mitigate the need for supervision. The most successful ones are contrastive learning-based approaches such as [30; 29] and they have shown remarkable results on target tasks such as image classification and object detection. Despite their success, there are two primary caveats: (1) These self-supervised methods are still trained on ImageNet or similar datasets, which are fairly cleaned up and/or include a pre-specified set of object categories. (2) This method of training is a *passive* approach in that it does not encode interactions. On the contrary, for humans, a vast majority of our visual understanding is shaped by our interactions and our observations of others interacting with their environments. We are not limited to learning from visual cues alone, and there are various other supervisory signals such as body movements and attention cues available to us. It is shown that by learning how to move the joints to walk and crawl, infants can significantly enhance their perception and cognition [3]. Moreover, by observing another person interact with the environment humans obtain a visual and physical perception of the world [13].

The question we investigate in this paper is, “can we learn a rich generalizable visual representation by encoding human interactions into our visual features?". In this work, we consider the movement of human body parts and the center of attention (gaze) as an indicator of their interactions with the environment and propose an approach for incorporating interaction information into the muscly-supervisedrepresentation learning process.

To study what we can learn from interaction, we attach sensors to humans’ limbs and see how they react to visual events in their daily lives. More specifically, we record the movements of the body parts by Inertial Movement Units (IMUs) and also the gaze to monitor the center of attention. We introduce a new dataset of more than 4,500 minutes of interaction by 35 participants engaging in everyday scenarios with their corresponding body part movements and center of attention. There are no constraints on the actions, and no manual annotations or labels are provided.

Our experiments show that the representation we learn by predicting gaze and body movements in addition to the visual cues outperforms the visual-only baseline on a diverse set of target tasks (Figure 2.6): semantic (scene classification), temporal (action recognition), geometric (depth estimation), physics (dynamics prediction) and affordance-based (walkable surface estimation). This shows that movement and gaze information can help to learn a more informative representation compared to a visual-only model.




Figure 2.6: We propose to use human's interactions with their visual surrounding as a training signal for representation learning. We record first person observations as well as the movements and gaze of people living their daily routines and use these cues to learn a visual embedding. We use the learned representation on a variety of diverse tasks and show consistent improvements compared to state-of-the-art self-supervised vision-only techniques.

2.2.2 Related Work

Visual representations can be learned using many different techniques from full supervision to no supervision at all. We outline the most common paradigms of representation learning, namely supervised, self-supervised, and interaction-based representation learning.

Supervised Representation Learning. Supervised representation learning in computer vision is typically performed by pre-training neural networks on large-scale datasets with full supervision (e.g., ImageNet [39]) or weak supervision (e.g., Instagram-1B [116]). These models are fine-tuned for a variety of tasks including object detection [61; 155], semantic segmentation [163; 27], and

visual question answering [4; 88]. However, collecting a manually annotated large-scale dataset such as ImageNet requires extensive resources in terms of cost and time. In contrast, in this paper, we only use human interaction data, which does not require any manual annotation.

Self-supervised Representation Learning. There has been a wide range of research on self-supervised learning of visual representations in which properties of the images themselves act as supervision. The objectives for these methods cover a variety of tasks such as solving jigsaw puzzles [135], colorizing grayscale images [222], learning to count [136], predicting context [42], inpainting [143], adversarial training [43] and predicting image rotations [60]. This type of representation learning is not limited to learning from single frames. [6] and [93] both use egomotion, [190] cyclically track patches in videos, [142] use low-level non-semantic motion-based cues, and [180] predict the representation of future frames.

Inspired by contrastive learning [73], recent methods have used "instance discrimination" in which the network uniquely identifies each image. A network is trained to produce a non-linear mapping that projects multiple variations of an image closer to each other than to all other images. Using Noise Contrastive Estimation [71], networks are trained to differentiate between similar images under complex noise models (such as non-overlapping crops and heavy color jittering) and dissimilar images. [137] and [80] introduce and investigate the Contrastive Predictive Coding (CPC) method, which encodes the shared information between different crops of an image to predict the features from masked regions of the image. [198; 124] use a memory bank, which enables contrasting features of the current image against a large set of negative samples, increasing the likelihood of finding a nearby negative. The MoCo technique [76; 30] encodes the positive samples with a momentum encoder to avoid the rapid changes in the original feature extractor. They achieve comparable results with supervised learning representations. [28; 29] show that by using a trainable non-linear transformation between the representation and contrastive latent space and larger batch sizes, they can omit memory banks entirely, allowing for full backpropagation through both positive and negative samples, and achieve better results. [11; 176] maximize the mutual information

between different extracted features of the same image from multiple views. [228] enforce the extracted features of similar images to move towards the same part of the embedding space. [64], [213], and [40] apply contrastive method to videos and leverage spatio-temporal cues to learn visual representations. Similar to these approaches, we do not rely on any manual annotation, but in contrast to them, we utilize human interactions along with their visual observation for representation learning.

Interaction-Based Representation Learning. The third class of learning representations relies on cues obtained by interacting with a dynamic environment. [151] learn a representation from interactions of a robotic arm (e.g., grasping and pushing) with different objects. [25] and [191] both tackle the representation learning problem by training an agent to play a game in an interactive environment. [46] learn a representation by modeling the non-semantic movements of a dog. Our work falls in this category since we use human interactions for learning the representation. We differ from these approaches in that we use low-level observations of human interaction such as body part movements and gaze to show significant improvement over a state-of-the-art baseline across multiple low-level and high-level target tasks.

2.2.3 Human Interaction Dataset

We introduce a new dataset of human interactions for our representation learning framework. In this section, we describe the data collection. Our goal is to capture how humans react to the visual world by recording their movements and focus of attention. Previous datasets of human actions and gaze include only gaze information [51; 207], part movements from a third-person view [90; 75], or only action or hand labels in an ego-centric setting [35; 166]. In contrast, our new dataset includes ego-centric observations along with the corresponding gaze and body movement information during their daily activities ranging from walking and cycling to driving and shopping.

To collect the dataset, we record egocentric videos from a GoPro camera attached to the subjects' forehead. We simultaneously capture body movements, as well as the gaze. We use Tobii Pro2




Figure 2.7: **Dataset examples.** Two sequences from our dataset are shown on the left. The first row shows the sequence of the images and the second row shows the movements of the body parts according to the IMU readings. We visualize the gaze using the red circle. This is just for visualization purposes and does not exist in the image. On the right, we show the data collection setup.

eye-tracking to track the center of the gaze in the camera frame. We record the body part movements using BNO055 Inertial Measurement Units (IMUs) in 10 different locations (torso, neck, 2 triceps, 2 forearms, 2 thighs, and 2 legs). Figure 2.7 shows the data collection setup along with two clips of the captured sequences. In total, we collected 4,260 minutes of videos with their corresponding body part movement and gaze from 35 people. Unlike the common large-scale datasets used for representation learning such as ImageNet, there is no restriction on the categories observed in the images, and no manual annotation is provided. Although the supervision from movement and gaze does not come for free and still requires the participants wearing the sensors, no manual or semantic annotation is needed for acquiring this dataset.

2.2.4 Interaction-based Representation Learning

Visual representation learning is typically performed using visual cues from single images or videos [76; 64]. Our goal in this paper is to incorporate human interactions into our representations to move beyond a purely visually-trained feature representation. Below, we describe our approach for integrating movement and gaze information in the representation learning pipeline. Intuitively,




Figure 2.8: **Model Overview.** We learn a muscly-supervisedrepresentation by jointly optimizing visual, movement and center of focus (gaze) objectives. The portion outlined with a rectangle is the backbone that is used to evaluate the representation for target tasks. All parts of the network are initialized randomly and trained from scratch.

body part movements should encode the temporal changes in the image based on the underlying cause of those changes (e.g., moving legs results in walking which makes distant objects move closer). Additionally, gaze grounds the visual features with the location in the image where the person pays the most attention. This should correlate well with semantic concepts such as objects, or affordances such as walkable surfaces.

2.2.5 Learning Features

Our goal is to learn visual representations by simultaneous learning of a visual encoding for each frame and predicting body part movements and gaze attention from the sequence of observations. Formally, given an ego-centric video as a sequence of images $V = (I_t, \ldots, I_{t+k})$, the goal is to 1) estimate the gaze $G = (G_t, \ldots, G_{t+k})$, where G_t is the person's center of focus in 2D camera coordinates, and 2) predict the body part movements $P = (P_t, \ldots, P_{t+k})$, where P_t is a binary vector of length equal to the number of body parts, indicating whether a part is moved at time t.

We optimize three objectives: (1) gaze prediction, (2) body part movement prediction, and (3) auxiliary visual prediction. The visual features obtained from a CNN backbone are combined with a sequence-to-sequence model in order to predict gaze and movement. Note that the weights of

the backbone are randomly initialized, i.e. we train the model from scratch. Figure 2.8 shows an overview of the architecture. The objectives are jointly optimized. In the following, we explain each of them in more detail.

Gaze: We predict the person's focus of attention by modeling their gaze in the camera reference frame. We use the Huber loss to train the center of attention $\mathcal{L}_{attention}(\hat{G}, G)$,

$$\mathcal{L}_{attention}(\hat{G}, G) = \begin{cases} \frac{1}{2}\left\|\hat{G} - G\right\|_2^2 & |\hat{G} - G| < \delta \\ |\hat{G} - G| - \frac{1}{2} & \text{otherwise} \end{cases} \tag{2.2}$$

Movement: We find the task of predicting body part movement direction and magnitude to be highly ambiguous. For example, when walking, the visual information may not show the legs, so we cannot know how high the legs were lifted. Instead, for each body part, we predict whether it is moving at all which is less ambiguous and reduces the problem to a binary classification task. Rather than predicting the movements for lower and upper parts of the joint separately (leg and thigh, forearm and tricep), we combine the movements into 6 categories of torso, neck, right arm, left arm, right leg, and left leg. To estimate this movement, we use binary cross-entropy loss and denote it as $\mathcal{L}_{movement}(\hat{P}, P)$.

Auxiliary Visual Prediction: We also use a visual objective, $\mathcal{L}_{visual}(\hat{I}_t, I_t)$. For this objective, similar to [76], we use instance discrimination. Any alternative visual encoding objective can be used instead. In section 2.2.7.4, we provide results for another type of visual encoding as well.

Instance discrimination's objective is to force the visual features of different augmentations of the same image to be as close as possible in the latent space [198; 28; 228] while pushing apart all other image embeddings. By learning to extract what makes each image unique, the network focuses on semantically meaningful features of the image. This enables the feature extractor to embed a more invariant representation of the image, which is especially important when transferring to different tasks and domains. To contrast the positive samples (the augmentations of the image), with a large set of negative samples, we maintain a memory bank of embedded features from different

images in the data. The final objective can be formalized as $\mathcal{L}_{visual}$ (which is also known as the InfoNCE [137] loss),

$$\mathcal{L}_{visual}(\hat{I}_t, I_t) = -\log \frac{\exp(f(I_t) \cdot f(\hat{I}_t)/\tau)}{\sum_{i=0}^{N} \exp(f(I_t) \cdot M_i/\tau)}, \tag{2.3}$$

where $I_t, \hat{I}_t$ are two different random augmentations of the *first* image of the sequence V, f is the image feature extractor (ResNet backbone), $M = (M_0, \ldots, M_N)$ is the bank of negative samples and τ is a parameter that controls the concentration level of the distribution [82]. We also use a momentum-updated encoder as in [76]. We apply the visual loss only to the first image of the sequence, as images within a sequence tend to be visually similar to each other.

The overall objective is a weighted sum of the described loss functions.

$$\mathcal{L}_{interaction} = \alpha\mathcal{L}_{attention}(\hat{G}, G) + \beta\mathcal{L}_{movement}(\hat{P}, P) + \gamma\mathcal{L}_{visual}(\hat{I}_t, I_t) \tag{2.4}$$

2.2.6 Adapting the Representation to New Tasks

After training the model using $\mathcal{L}_{interaction}$ objective, we use the trained weights of our feature extraction network (i.e., only the ResNet part) as the initialization for our target tasks. Our goal in this paper is to evaluate the visual representation on its own rather than using it as initialization for end-to-end training. Hence, during training for the target tasks, the weights of the feature extraction backbone are frozen. We have a diverse set of target tasks, where each requires a specific network architecture (for example, depth estimation requires up-convolutional layers, while action recognition requires a temporal architecture). Below, we describe the result of the transfer to the target tasks.

Datasets		SUN397 [204]	Epic Kitchen [35]	VIND [127]	NYUv2 [134]	
Method	Training Objective	(a) Scene (Top-1 ↑)	(b) Action (Top-1 ↑)	(c) Dynamics (Top-1 ↑)	(d) Walkable (IOU ↑)	(e) Depth (RMSElog ↓)
MoCo [76]	vis	15.80	24.45	13.18	58.97	0.148
Ours	vis/attn	21.27	26.80	13.71	**59.65**	0.145
Ours	vis/move	21.08	26.71	13.22	58.42	**0.144**
Ours	vis/move/attn	**22.82**	**27.95**	**14.44**	58.38	0.146

Table 2.6: **Target task results.** We compare the performance of our learned representation from movement and gaze cues with a recent self-supervised baseline MoCo [76] (which is trained on our data). Note that the MoCo baseline is trained using only visual data ('vis'). We evaluate the performance on a variety of different target tasks.

2.2.7 Experiments

To evaluate our representation learning approach, we consider five different types of target tasks. The tasks are chosen such that they cover a wide range of domains: semantic (scene classification), temporal (action recognition), geometric (depth estimation), physical (dynamics prediction), and affordance (walkable surface estimation). We show that our learned representation, which encodes body part movement and gaze and does not rely on any manual annotation, outperforms a strong self-supervised baseline which relies on purely visual cues. Furthermore, we provide ablations of our model by using an alternative visual loss and using a subset of body parts for representation learning.

2.2.7.1 Self-Supervised Baseline

We compare our method with the recently introduced self-supervised representation learning technique, Momentum Contrast network (MoCo) [76], which is a state-of-the-art representation learning approach and achieves strong performance on a variety of target tasks such as image classification and object detection. The original work was trained on images from the ImageNet dataset. To ensure the comparison between our method and the baseline is fair, we train MoCo on the images from our dataset. Note that this baseline relies on visual cues only. Our goal is to show whether we can learn better representations when we use movement and gaze information in

addition to the visual information.

2.2.7.2 Evaluation of the Learned Representation

We evaluate the learned representation on five different target tasks. The weights for feature extraction backbone are frozen, and only the task-specific layers are trained. We show that the representation trained using the movement and attention (gaze) supervision in addition to the visual cues outperforms MoCo [76] baseline (trained on our data) across the board. For each target task, we report the results in four settings, each using a different combination of visual, movement, and gaze (attention) cues for representation learning.

Scene Classification. For the task of scene classification, a network receives a single image as input and predicts the scene category of the image. We use SUN397 [204] dataset for this task, as it provides a large-scale dataset of 130k images of 397 different scene categories (e.g., park, restaurant, kitchen). The results are shown in Table 2.6-column (a). The representation that encodes both movement and attention cues performs the best on the semantic task of scene classification. We achieve nearly a 7% improvement compared to fine-tuning the MoCo [76] baseline.

Action Recognition. The task is to predict the category of action from ego-centric videos. We use the EPIC-KITCHENS dataset [35] for this task, which is a large-scale dataset of 11M images from different action categories that are performed in various kitchens.

As shown in Table 2.6-column (b), our method outperforms the strong baseline representation learning method by 3.5%. This again shows that incorporating additional cues such as part movements and gaze in the representation learning is beneficial for downstream tasks. It seems that both movement and attention cues are helpful for action recognition. This is aligned with our intuition that predicting the gaze of a person and how they move their body parts may be beneficial to recognizing the actions they perform.

Future Prediction of Dynamics. The goal of this task is to predict the future dynamics of an object in an image. We use the VIND [127] dataset for this task. It includes 150K images with

Training Objective	Scene Classification Top-1 ↑	Action Recognition Top-1 ↑	Dynamics Prediction Top-1 ↑	Walkable Estimation IoU ↑	Depth Estimation RMSElog ↓
$\mathcal{L}_{ae}$	11.59	23.84	9.62	43.64	0.175
$\mathcal{L}_{ae} + \mathcal{L}_{att} + \mathcal{L}_{move}$	15.08	25.69	10.78	47.20	0.169
$\mathcal{L}_{nce} + \mathcal{L}_{att} + \mathcal{L}_{move}$	**22.82**	**27.95**	**14.44**	**58.38**	**0.146**

Table 2.7: **Ablation of the visual loss.** The result of using an autoencoder for the visual loss. We re-train the models for the five target tasks. $\mathcal{L}_{att}$, $\mathcal{L}_{move}$ and $\mathcal{L}_{nce}$ are the ones used in Eq. 2.4.

corresponding object bounding boxes. The dataset categorizes physical dynamics into Newtonian scenarios such as sliding, projectile motion, and bouncing. The goal is to predict these Newtonian scenarios and the camera viewpoint for a query object that is specified by a bounding box and physical motion labels. There are 66 classes in total. The input to the network is a single RGB image and the bounding box for the query object. Table 2.6-column (c) includes the results for this task. We outperform the baseline by 1.3%. The representation that is learned by using both attention and movement provides the best performance for this task, which involves predicting the future trajectory of objects.

Walkable Surface Estimation. The goal of this task is to segment the pixels in an image that a person can walk on. We use the data from [129], which provides annotation for 1449 images of the NYU DepthV2 [134] dataset. The results are shown in Table 2.6-column (d). The variation of our method that uses only the gaze information achieves the highest accuracy. This might be due to the fact that, during walking, human attention is focused on the places that they can walk on. Therefore, the gaze provides sufficient information to perform this task.

Depth Estimation. For depth estimation, the task is to regress the values of the depth for a single monocular RGB image. We use NYU DepthV2 [134] dataset for this task, which provides 1449 densely labeled pairs of RGB and depth images. The results are shown in Table 2.6-column (e). Our learned representation outperforms the baseline for this task as well. Movement cues seem more aligned with the task of depth estimation, and the representation embedding with this information performs better. Note that the metrics for depth and walkable surface estimation are global metrics

i.e. they are computed for the entire image. Therefore, typically a small improvement in those metrics has a significant effect on the qualitative results.

2.2.7.3 Ablative Analyses

We ablate our results by replacing the InfoNCE visual loss with an autoencoder loss. Additionally, we show how gaze information affects the prediction of the body part movements. Finally, we evaluate which movements serve as an important supervision by masking out subsets of the body parts and retraining the representation.

2.2.7.4 Visual Loss

As discussed in Section 2.2.5, we use the InfoNCE loss [137] while learning the representation. In order to investigate the impact of using this objective, we learn the representation using an autoencoder loss for our visual objective and evaluate the learned representation on all five target tasks after re-training using the new backbone. The autoencoder loss, $\mathcal{L}_{ae}$ is defined as $\mathcal{L}_{ae}(d(f(I_t)), I_t) = \|d(f(I_t)) - I_t\|_2$, where f is the feature extractor backbone and d is a decoder network of five up-convolution layers, which receives the $512 \times 7 \times 7$ feature as input and reconstructs a $3 \times 56 \times 56$ image.

Table 2.7 shows that gaze and movement information still provide a strong signal compared to the visual-only case. However, the results are worse than the case that we use the InfoNCE loss for learning the representation.

2.2.7.5 Movement Estimation

To better understand the effect of gaze, we predict body part movements with and without gaze information. This experiment is not part of the representation learning experiments. It is just to evaluate whether using gaze provides any additional cue for prediction of the movements.

In this experiment, we predict which subset of the six groups of body parts (neck, torso, left

Prediction	Avg. Accuracy
Visual → Part Movement	79.19
Visual + Gaze → Part Movement	**81.01**

Table 2.8: **Body part movement prediction.** We investigate the correlation of the movement and attention by using the human gaze as an additional input to predict the body part movements.

arm, right arm, left leg, right leg) have moved. The overall architecture for this experiment is the same as our representation learning model, except for the inputs to the LSTM modules, which is instead the concatenated image features from ResNet and the embedded input gaze. The input gaze embedding is a two-layer network encoding the gaze into a feature vector of size 512.

Table 2.8 shows the results for this experiment. The network achieves an improvement in predicting the body parts movements by having the additional information of the person's center of attention, which can intuitively serve as a proper indicator of their "intentions".

2.2.7.6 Effects of the Body Parts

To evaluate how each body part affects the learned representation, we perform an experiment where we ignore a subset of body parts, re-train the representation learning (from scratch) and evaluate the features on target tasks. Table 2.9 summarizes the results. The performance on the target tasks (except depth estimation) drops when we ignore a body part during representation learning. For depth estimation, removing *torso* results in a slightly lower error, which might indicate that the torso movement is not as helpful for estimating the depth.

2.2.8 Conclusion

Representations that encode movements and actions become a necessity as we move deeper towards embodied visual understanding. In this paper, we investigate the idea of using human interactions to learn visual representations. To enable this research, we introduce a new dataset of human interactions which includes hours of synchronized streams of image frames, body part movements,

Masked Parts	Scene Classification Top-1 ↑	Action Recognition Top-1 ↑	Dynamics Prediction Top-1 ↑	Walkable Estimation IoU ↑	Depth Estimation RMSElog ↓
w/o Torso	21.56	25.42	13.47	57.50	**0.143**
w/o Neck	21.50	26.25	13.54	56.76	0.148
w/o Arms	20.72	24.97	13.79	58.08	0.148
w/o Legs	21.38	25.65	12.62	57.16	0.147
w/ all	**22.82**	**27.95**	**14.44**	**58.38**	0.146

Table 2.9: **Ablation of body parts.** We show how the performance on the target tasks changes when we ignore a body part during representation learning.

and gaze information across different subjects and activities. We show that representations trained to predict body movements and gaze encode additional information compared to their purely visual counterparts. More specifically, we show our representation outperforms a state-of-the-art self-supervised representation learning baseline for a variety of target tasks. Our main point in this paper is to show there are signals other than visual information that can be used for improving visual representation. However, we require additional sensors to capture data from other modalities and we acknowledge that scalability of our dataset requires additional data collection.

2.3 Learning by Performing Interactions

2.3.1 Introduction

What does it mean to understand a video of human-object interaction such as the one shown in Figure 2.9? One popular answer would be to recognize the nouns (objects) and verbs (actions) – e.g., in this case lifting a pot. But such an understanding is quite limited in nature. For example, simply recognizing 'lifting' does not tell one anything about how the pot was grasped, or how high it was lifted. To address these shortcomings, there has been a recent push towards a deeper geometric understanding of videos. From estimating contact points on the object [19] to estimating

human and object poses [113], these approaches tend to estimate the visible geometric structure. While the high-level semantic labeling ('lifting') or the geometric inferences (human and object pose estimation), both provide an answer to *what* happened in the video, it lacks the true physical substance for actionable understanding. For example, just knowing how the pot is moved is not sufficient for the robot to imitate – it needs to also understand *how* the act was accomplished.

In order to obtain a more actionable understanding, we argue that one must account for the physical nature of the task. The answer then, to the question of how the act was done, is rather straightforward from a physical perspective – the object was in contact with the human hand on two sides, and a combination of inward and upward forces applied at these contact points allowed it to be lifted up against gravity. This understanding of physical *forces* is not only directly useful for an active agent but also completely represents the interaction from the object's perspective as only external forces cause its motion. In this work, we take a step towards developing such an understanding and present a system that can infer the contact points and forces applied to a known object from an interaction video.

While the goal of being able to infer these forces is desirable, it is unfortunately tedious (if not impossible) to acquire direct supervision for this task. The existing force sensors [115] are not precise enough to provide accurate direction or magnitude measurement, and not compact enough to keep the interaction natural. So, how do we get the supervision? We note that if we can infer physical forces applied to an object, we can also recover a full geometric understanding by simulating the effect of the forces on that object. We build on this insight and present an approach to learn prediction of physical forces, that instead of directly supervising the predicted forces, enforces that their effects match the observations through the interaction video.

To train our system, we collect a dataset of videos recorded from multiple participants grabbing and moving objects. Then we use Mechanical Turk to annotate the keypoints of the objects and contact points on each frame and use this limited information in camera frame to infer the object's 6DOF pose in world coordinates and the person's contact points on object mesh. We observe that

our approach of learning to predict forces via supervising their effects allows us to learn meaningful estimates and that these can explain the observed interaction in terms of reproducing the observed motion.

Our experiments show that our model learns to infer human contact points on object mesh, and estimate the corresponding forces. We observe that applying these forces on the predicted contact points at each time step in physics simulation we can repeat the behavior depicted in the video. We also show that contact point and force prediction are highly correlated and jointly optimizing improves the performance on both tasks. Finally, we provide interesting evidence that the representation we learn encodes rich geometric and physical understanding that enables us to generalize to interacting with novel objects using only few shot examples.




Figure 2.9: We study the problem of physical understanding of human-object interactions by inferring object motion, points of contacts and forces from RGB videos. We use physics simulation to see how these interactions change the dynamics of the object and try to imitate the motion observed in the video.

2.3.2 Related Work

Pose estimation. In order to understand physical motions, a network needs to implicitly reason about the object pose. There is a long line of work in this area, with two different approaches: category-based [68; 159; 168] and instance-based [44; 96; 177; 202]. Our work is more aligned with the latter, and we use the YCB object set [21] which provides richly textured objects. While some of our model design decisions is inspired by these works, *e.g.* iterative pose estimation [112],

our final goal, to infer about physics of the observed motions, is different.

Contact point prediction. Predicting the contact point and hand pose estimation for object manipulation has been studied in the domain of detecting plausible tool grasping [8], human action recognition [57], hand tracking [74], and common grasp pattern recognition [87]. Brahmbhatt *et al.* [19] collected a dataset of detailed contact maps using a thermal camera, and introduced a model to predict diverse contact patterns from object shape. While our model also reasons about the contact points,it is only one of the components towards better understanding the physical actions. Moreover, we show that we benefit from force prediction to improve the contact point estimations.

Human Object interaction. Typical approaches for understanding human object interaction use high level semantic labels [62; 70; 214]. Recently there have been some works in understanding the physical aspects of the interaction. Pham *et al.* [148] have used data from force and motion sensors to reason about human object interactions. They also use off-the-shelf tracking, pose estimation, and analytical calculations to infer forces [147]. Hwang *et al.* [89] studied the forces applied to deformable objects and the changes it makes on object shape. Li *et al.* [113] reasoned about human body pose and forces on the joints when the person is interacting with rigid stick-like hand tools. While these methods show encouraging results for this direction, our work concentrates on interaction scenarios with complex object meshes and more diverse contact point patterns.

Predicting physical motions. Recently, learning the physics dynamic has been widely studied by classifying the dynamics of objects in static images [127], applying external forces in synthetic environments [131], predicting post-bounces of a ball [153], simulating billiard games [54], and using generative models to produce plausible human-object interactions [186]. These works are more broadly related to understanding the physical environment, however, their goal to predict how scenes evolve in the future is different from ours. We try to tackle the problem of physically reasoning about the motions observed in the videos.

Recovering physical properties. In recent years there have been efforts in building differentiable physics simulation [36; 86]. Wu *et al.* [195] use physics engines to estimate physical properties

of objects from visual inputs. However, in contrast to these approaches aimed at retrieving the properties of the physical world, we assume these are known and examine the problem of interacting with it. Our real-to-sim method is more aligned with the path taken by [24]; that being said, our goal is not bringing the simulation's and real world's distributions closer. We rather focus on replicating the observed trajectory in simulation.

2.3.3 Approach

Given a video depicting a human interacting with an object, our goal is to infer the physical forces applied over the course of the interaction. This is an extremely challenging task in the most general form. For example, the object geometry may vary wildly and even alter over the interaction (*e.g.* picking a cloth), or forms of contact may be challenging (*e.g.* from elbowing a door to playing a guitar). We therefore restrict the setup to make the task tractable, and assume that the interaction is with a known rigid object (given 3D model), and only involves a single hand (five fingers apply the force). Given such an interaction video, our goal is then to infer the forces applied to it at each time-step along with the corresponding contact points.

Formally, given a sequence of images $\{I_t\}$ depicting an interaction with a known object, and additional annotation for (approximate) initial object pose, we predict the person's contact points in object coordinates frame $C_t = (c_t^0, \ldots, c_t^4)$ (each representing one finger), and the forces applied to each contact point $(f_t^0, \ldots, f_t^4)$. As alluded to earlier, it is not possible to acquire supervision in the form of the ground-truth forces over a set of training interactions. Our key insight is that we can enable learning despite this, by instead acquiring indirect supervisory signal via enforcing that the simulated effect of predicted forces matches the observed motions across the video. We first describe in Section 2.3.3.1 a dataset we collect to allow learning using this procedure. We then describe in Section 2.3.3.2 how we can extract supervisory signal from this data, and finally present our overall learning procedure in Section 2.3.3.3.




Figure 2.10: **Dataset.** Showing two sample frames (drill and hammer) from our dataset. We collect annotation for semantic keypoints of the objects (Column 2) and human contact points. This data helps us to calculate object 6DOF pose (Column 3) and contact points on object mesh (Column 4).

2.3.3.1 Interaction Dataset

We collect a dataset of object manipulation videos, representing a diverse set of objects, motions, and grasping variations. We leverage the objects from the YCB set [21], as these have the underlying geometry available, and record a set of videos showing participants manipulating 8 objects. To enable learning using these videos, we collect additional annotations in the form of semantic keypoints and pixel locations of contact points to (indirectly) allow recovering the motion of the objects as well as the 3D contact points for each interaction.

We describe the data collection procedure in more detail in the supplementary, but in summary, we obtain: a) annotations for 2D locations for visible keypoints in each frame, b) 6D pose of the object w.r.t. the camera in each frame, though these are noisy due to partial visibility, co-planar keypoints, *etc.*, and c) 3D contact points on the object mesh over each interaction video. There are 174 distinct interaction videos in our dataset (111 train, 31 Test, 32 Validation), 13K frames in total. The 8 objects used are: pitcher, bleach bottle, skillet, drill, hammer, toy airplane, tomato soup can and mustard bottle. We show some examples from the dataset in Figure 2.10. We will publicly release the dataset and believe that it will also encourage future research on understanding physical interactions.

2.3.3.2 Supervisory Signal via Physical Simulation

Given per-timestep predicted forces f_t and corresponding contact points C_t, we show that these can get supervisory signal by simulating their effects, and comparing the simulated motion against the observed one.

Discrepancy between Simulated and Observed Motions. A rigid body's 'state' can be succinctly captured by its 6D pose, linear velocity, and angular velocity. Given a current state s_t and the specification of the applied forces, one can compute using a physics simulator $\mathcal{P}$, the resulting state $s_{t+1} \equiv \mathcal{P}(s_t, f_t, C_t)$. Therefore, given the initial state, and predicted forces and contact points, we can simulate the entire trajectory under these forces and obtain a resulting state at each timestep.

One possible way to measure the discrepancy between this resulting simulated motion and the observed one is to penalize the difference between the corresponding 6D poses. However, our annotated 'ground-truth' 6D poses are often not accurate (due to partial visibility *etc.*.), and this measure of error is not robust. Instead, we note that we can directly use the annotated 2D keypoint locations to measure the error, by penalizing the re-projection error between the projected keypoints under the simulated pose and the annotated locations of the observed ones. We define a loss function that penalizes this error:

$$\mathcal{L}_{keypoint}(l_t^{kp}, s_t) := \|l_t^{kp} - \pi(R_t, T_t)\|^2 \tag{2.5}$$

Here, l_t^{kp} is the annotated 2D location for keypoints, π is the projection operator which transforms 3D keypoints on the model to the camera frame under the (simulated) rotation and the translation at $s_t = (R_t, T_t)$.

Differentiable Physics Simulation. To allow learning using the objective above, we require a differentiable physics simulator $\mathcal{P}$. While typical general-purpose simulators are unfortunately not differentiable, we note that the number of input variables (state s_t, forces f_t, and contact points C_t) in our scenario is low-dimensional. We can therefore use finite difference method to calculate the




Figure 2.11: **Training schema.** Given a video as input, the model predicts the forces and their corresponding contact points. We then apply these forces on the object mesh in physics simulation and jointly optimize for keypoint projection loss $\mathcal{L}_{keypoint}$ and contact point prediction loss $\mathcal{L}_{cp}$ with the aim to imitate the motion observed in the video.

gradients of the outputs of the simulation with respect to its inputs.

In order to calculate the derivative of output with respect to input, we need to calculate the partial derivatives $\frac{\partial S_{t+1}}{S_t}$, $\frac{\partial S_{t+1}}{f_t}$ and $\frac{\partial S_{t+1}}{C}$. We use the approximation

$$\frac{df}{dx} \cong \frac{f(x+h) - f(x-h)}{2h} \tag{2.6}$$

where h is a small constant. As $s_t \in \mathbb{R}^{13}$, $f_t \in \mathbb{R}^{k\times 3}$, and $C_t \in \mathbb{R}^{k\times 3}$ ($k = 5$ is the number of contact points), we can compute the gradients w.r.t the input using $(13 + 3k + 3k) + 1$ calls to the simulator $\mathcal{P}$ (the last call is for calculating $f(x)$). We use the PyBullet simulator [33] for our work, and find that each (differentiable) call takes only 0.12 seconds.

2.3.3.3 Putting it together: Joint Learning of Forces and Contact Points

Given a video and the initial state of the object, we encode the sequence into a visual embedding, and use this embedding to predict the contact points and their corresponding forces. We then apply these forces in the physics simulation to infer the updated state of the object, and use it in addition to the sequence embedding to iteratively predict the subsequent forces to be applied. This can help




Figure 2.12: **Model overview.** Given a video of a person moving an object, along with the initial pose of the object, our network predicts the human contact points and the forces applied at those for each time step. The implied effects of these forces can then be recovered by applying them in a physics simulation. Using the gradients through this simulated interaction, our model learns how to optimize for its two objectives: minimizing the error in projection of the object to camera frame, and predicting the accurate contact points.

the network to adapt to the possible mistakes it might have made, and change the forces in the next steps accordingly (Figure 2.12).

To train our model we have two objectives: (1) to minimize the keypoint re-projection error, that help with reducing the discrepancy between the object trajectory in simulation and the one seen in the video (Equation 2.5), and (2) to minimize the error in contact point prediction in compare to the ground-truth (Figure 2.11). The objective we use for optimizing the contact point estimation is defined as,

$$\mathcal{L}_{cp}(C_t, \hat{C}_t) := \sum_{i=0,\ldots,k} \|c_i - \hat{c}_i\|^2, \tag{2.7}$$

where k is the number of contact points, and C_t and $\hat{C}_t$ are the ground truth and predicted contact points at time t.

We note that the contact point decoder gets supervisory signals both from contact point loss and the keypoint loss. We believe this constrains contact point prediction to generate physically plausible motions as seen in videos. In experiments, we show this joint loss leads to improvement even in contact point prediction.

Training details. The backbone for obtaining primary image features is ResNet18 [78] pre-trained on ImageNet [37]. We take the features (which are of size 512x7x7) before the average pooling.

For all the experiments we use batch size 64, Adam optimizer with learning rate of 0.001, videos of length 10 frames, with frequency of 30 fps, $h_f, h_s = 0.01$ and $h_c = 0.05$ for approximating gradients (refer to Equation 2.6) for force, state and contact point respectively.

We calculate the direction of the gravity in world coordinates and use it in physics simulation to ensure realistic behavior. To train our model we first train each branch in isolation using $\mathcal{L}_{cp}$ for contact point prediction and $\mathcal{L}_{keypoint}$ for force prediction modules, then we jointly optimize for both objectives and train end to end.

2.3.4 Experiments

The area of physical understanding of human-object interaction is largely unexplored, and there are no established benchmark datasets or evaluation metrics. In this work, we use our novel dataset to provide empirical evaluations, and in particular to show that: a) our results are qualitatively meaningful; and (b) individual components and loss terms are quantitatively meaningful (ablations). We will also demonstrate that a physical understanding of human-object interactions leads to improvement even in individual components such as contact point estimation and estimating object poses; and (c) finally we will demonstrate the generalization power by showing that our network learns a rich representation that can use few examples to generalize to manipulating novel objects.

Evaluation Metric: The goal of our work is to obtain physical understanding of human-object interactions. But getting ground truth forces is hard, which makes it impossible to quantitatively measure the performance by just force values. So instead of measuring forces, we evaluate if our predicted forces lead to similar motions as depicted in the videos. Therefore, for evaluating our performance, we use the CP and KP error (Equations 2.5 and 2.7) as evaluation metrics. The former measures the $L1$ distance between the predictions and ground truth for contact point (in object coordinates), and the latter measures error in keypoint projection (in image frame). Original image size is 1920×1080 and the keypoint projection error is reported in pixels in the original image dimension. Rotation and translation error are the angular difference (quaternion distance) in rotation

and $L2$ distance (meters) in translation respectively.

2.3.4.1 Qualitative Evaluation

We first show qualitative results of our full model: joint contact point and force prediction. The qualitative results for force prediction and contact point predictions are shown in Figure 2.13 and Figure 2.14 respectively. As the figure shows, our forces are quite meaningful. For example, in case of plane at $t = 0$ (See Figure 2.13(a)), initially the yellow and blue arrow is pushing to left and purple arrow is on the other side is pushing to right. This creates a twist motion and as seen at $t = 4$ rotates the plane. Also, in case of skillet (Figure 2.13(b)), there is a big change in the orientation of the object from $t = 0$ to $t = 4$, therefore a bigger magnitude of force is required. However, after getting the initial momentum the forces decrease to the minimum needed for maintaining the current state. Refer to project page* [1] for more visualizations.

Next we show few examples of contact point prediction. If contact points are predicted in isolation, small differences can lead to fundamentally different grasps. By enforcing physical meaning to these grasps (via forces), our approach ensures more meaningful predictions. An example is the top of Figure 2.13, where isolated prediction leads to grasp on the rim of the pitcher; but joint prediction leads to prediction of grasp on the handle.

2.3.4.2 Quantitative Evaluation

To quantitatively evaluate our approach, we measure performance by evaluating if application of forces as predicted lead to effects as depicted in the videos. Table 2.10 shows the performance in terms of CP metric and KP error. We report both the joint optimization (depicted as $\mathcal{L}_{keypoint} + \mathcal{L}_{cp}$) and the case where contact point prediction and force prediction modules are learned in an isolated manner ($\mathcal{L}_{keypoint}/\mathcal{L}_{cp}$). We observe that the joint model is significantly better (low error), both in contact point prediction and keypoint prediction.

[1]* `https://ehsanik.github.io/forcecvpr2020`




Figure 2.13: **Qualitative Results.** We show the results for the model which optimizes for both $\mathcal{L}_{keypoint}$ and $\mathcal{L}_{cp}$. Due to space limitations only Frames for $t = 0, 4$ are shown. For more videos and contact point visualizations refer to supplementary material.



Figure 2.14: **Improvements in contact point prediction after joint optimization.** We qualitatively show some examples for which the model makes better contact point predictions when it is trained using both $\mathcal{L}_{keypoint}$ and $\mathcal{L}_{cp}$. Fingers are color-coded (Thumb: orange, Index: Red, Middle: Blue, Ring: Green, Pinky: Purple).

Next, we measure what happens if the contact point prediction was perfectly matched with the annotated ground truth. So, instead of predicting them, we use ground truth contact points. Given a video, initial pose, and human contact points, we predict the forces applied to each point of contact to replicate the motion. Table 2.11 shows the results for unseen videos. Note that the training and test sets of contact points are disjoint, so model needs to be able to generalize to applying forces to the object under novel contact point configurations.

Comparing results in Table 2.10 and Table 2.11 shows that the jointly optimized model ($\mathcal{L}_{keypoint} + \mathcal{L}_{cp}$), (even though it is using the predicted contact points which may have errors), predicts forces that result in better KP metric in compare to the model that uses ground-truth contact points (and is only trained on $\mathcal{L}_{keypoint}$). This shows that jointly reasoning about where to apply the force and what force to apply can help with a better physical understanding.

Training one model for different objects. We try two training setup for each experiment: (1) training a separate model per object, and (2) sharing weights for one model across all objects (referred to as "All objects"). The common trend of performance improvement for both metrics

Object	Objective	CP Error	Keypoint Error (in px)	Rotation Error	Translation Error
Plane	$\mathcal{L}_{kp}/\mathcal{L}_{cp}$	8.79e-2	109.73	0.220	**0.152**
	$\mathcal{L}_{kp} + \mathcal{L}_{cp}$	**7.97e-2**	**99.89**	**0.152**	0.182
Skillet	$\mathcal{L}_{kp}/\mathcal{L}_{cp}$	2.37e-2	70.02	0.085	0.094
	$\mathcal{L}_{kp} + \mathcal{L}_{cp}$	**2.18e-2**	**65.25**	**0.076**	**0.063**
Pitcher	$\mathcal{L}_{kp}/\mathcal{L}_{cp}$	7.3e-2	131.62	0.126	0.212
	$\mathcal{L}_{kp} + \mathcal{L}_{cp}$	**5.61e-2**	**113.40**	**0.131**	**0.129**
Drill	$\mathcal{L}_{kp}/\mathcal{L}_{cp}$	7.08e-2	85.86	0.192	0.312
	$\mathcal{L}_{kp} + \mathcal{L}_{cp}$	**6.47e-2**	**71.00**	**0.163**	**0.250**
All objects	$\mathcal{L}_{kp}/\mathcal{L}_{cp}$	6.83e-2	104.57	0.218	0.250
	$\mathcal{L}_{kp} + \mathcal{L}_{cp}$	**6.71e-2**	**99.38**	**0.183**	**0.212**

Table 2.10: **Contact point prediction and key point projection error on test set, independent vs. joint optimization** In each set, the first row shows the results of the model optimizing for contact point and keypoint projection error separately, and the second row represents the joint optimization results. End to end training improves the results for both contact point prediction and keypoint projection. In the table, $\mathcal{L}_{kp}$ denotes $\mathcal{L}_{keypoint}$ and input to the network is the RGB image.

after joint optimization is observed when training one model for all objects as well.

2.3.4.3 Few-shot Generalization to Novel Objects

In order to evaluate the representation we learn from this training schema, we train a model for manipulating plane and use that to predict forces on unseen objects using few shot examples. Figure 2.15 shows that the representation we learned from predicting forces on one object can generalize to estimating forces for held-out objects using only few examples. Increasing the number of training samples yields better results on the test set. The 10 few shot experiment without pre-training (red) has a significantly lower accuracy than the one with our pre-training (light green) and is comparable with our 1-shot experiment (dark green).

Object	Input	Objective	Keypoint Error (in px)	Rotation Error	Translation Error
Plane	Img + CP_{gt}	$\mathcal{L}_{kp}$	104.33	0.134	0.199
Skillet	Img + CP_{gt}	$\mathcal{L}_{kp}$	67.47	0.075	0.089
Pitcher	Img + CP_{gt}	$\mathcal{L}_{kp}$	124.70	0.130	0.176
Drill	Img + CP_{gt}	$\mathcal{L}_{kp}$	91.25	0.236	0.352
All objects	Img + CP_{gt}	$\mathcal{L}_{kp}$	102.40	0.237	0.273

Table 2.11: **Predicting the forces using ground truth contact points** We first train a model to predict the forces on the ground-truth contact points. The first four rows show the quantitative results for training separate model per object using the $\mathcal{L}_{keypoint}$ objective and the last row shows the result for training one shared model for all 8 objects.




Figure 2.15: **Few shot experiment.** Showing the keypoint projection error for the model that is trained on planes and fine-tuned on few examples for held out objects (Lower is better). The results are shown for 1, 5, or 10 examples, as well as the model trained on the whole training set. The red bar shows errors for training on 10 examples without plane pre-training.

Set	Objective	KP (px)	Rotation	Translation
Train	$\mathcal{L}_{keypoint}$	55.96	0.129	0.063
Test	$\mathcal{L}_{keypoint}$	105.60	0.138	0.198
Train	$\mathcal{L}_{force}$	59.86	0.120	0.065
Test	$\mathcal{L}_{force}$	185.33	0.156	0.307

Table 2.12: **Pseudo-ground truth force regression.** We trained a model to predict the pseudo-ground truth forces for toy airplane from video, initial pose and contact points as input, by directly optimizing for the force prediction ($\mathcal{L}_{force}$). Although the training error is similar to the model trained on keypoint projection loss, it fails to generalize to unseen images and trajectories.

2.3.4.4 Additional Ablation Analysis

Regressing the force without simulation gradients. One alternative approach to solving the force inference problem is to predict the forces without the gradients from simulation. However, this requires having ground-truth labels for forces, which is almost impossible to obtain. So, we try to optimize for a set of pseudo-ground truth forces.

The goal of this experiment is to investigate how keeping the physics simulation in the training loop can help with understanding physics of the environment and generalizing to unseen trajectories.

To obtain pseudo-labels, we optimize a set of valid forces per training example which minimizes the error in keypoint projection. Then we train a model that given the sequence of images and ground truth contact points regresses these forces. The objective is defined as follows:

$$\mathcal{L}_{force}(f_{gt}, \hat{f}) = \|f_{gt} - \hat{f}\|^2$$

Table 2.12 shows that even though the error for training is relatively low, it still fails to generalize to unseen trajectories and gets a high test error. The intuition is that the gradients the network gets from interaction helps with learning a more generalizable representation.

Predicting initial state. We want to evaluate the necessity of giving the initial state as the input to the network. Thus, we try to predict the initial pose instead of using the ground truth. We do so by

Input	KP (px)	Rotation	Translation
Image	135.80	0.160	0.496
Image+S_0^{gt}	128.55	0.174	0.329

Table 2.13: **Predicting initial state.** The result for the model trained on toy plane object set, predicting the initial pose as well as the forces on ground truth contact points. To see how the error in object initial pose estimation is affecting the performance, we input the ground-truth object pose to the model as input during inference to compare. This model is trained with $\mathcal{L}_{keypoint}$ objective.




Figure 2.16: **Robustness to initial pose.** The changes in the keypoint projection error with respect to the magnitude of the noise added to the initial state. We also calculated the error bars for 5 runs with different random seeds. The labels on the bottom of the chart show the magnitude of the noise in rotation in degrees and the one on the top shows the magnitude of noise in translation in meters.

training a model that given a video as input and contact points in object coordinates (independent of object state), predicts the initial state of the object as well as the forces that are applied on each contact point (Table 2.13).

Adding noise to initial state during inference. We also want to investigate the effects of adding noise to initial state on performance. This experiment evaluates the robustness of the performance of the model to the initial state estimation. We used the trained model on toy airplane from Table 2.11, and added noise to the input initial state during inference time. Figure 2.16 shows the changes in KP metric with respect to tweaks in the rotation and translation of the initial state.

2.3.5 Conclusion

We have proposed a model that given a video depicting human-object interaction, predicts the contact points and the corresponding forces such that it replicates the observed motion. We demonstrate that jointly optimizing for both contact point prediction and keypoint projection error improves the results on both tasks in comparison to training models in isolation. We also show that our model learns a meaningful physical representation that can generalize to novel objects using few examples. Since our approach needs textured non-symmetric objects we were able to show these results on 8 objects from the YCB set [21], but we conjecture that if the keypoint labels in camera frame can be estimated, this method can generalize further than this object set. We believe our work takes step towards integrating action and perception in one common framework – bringing it closer to real-world robotics. A feasible future work would be to investigate how our model's prediction can speed up the robotic imitation learning procedure.

Chapter 3

Learning to Interact via Interaction

3.1 Learning to Learn from Interactions

3.1.1 Introduction

Learning is an inherently continuous phenomenon. We learn further about tasks that we have already learned and can learn to adapt to new environments by interacting in these environments. There is no hard boundary between the training and the testing phases while we are learning and performing tasks: we learn as we perform. This stands in stark contrast with many modern deep learning techniques, where the network is frozen during inference.

What we learn and how we learn it varies during different stages of learning. To learn a new task we often rely on explicit external supervision. After learning a task, we further learn as we adapt to new settings. This adaptation does not necessarily need explicit supervision; we often do this via interaction with the environment.

In this paper, we study the problem of learning to learn and adapt at both training and test time in the context of visual navigation; one of the most crucial skills for any visually intelligent agent. The goal of visual navigation is to move towards certain objects or regions of an environment. A key challenge in navigation is generalizing to a scene that has not been observed during training,




Figure 3.1: Traditional navigation approaches freeze the model during inference (top row); this may result in difficulties generalizing to unseen environments. In this paper, we propose a meta-reinforcement learning approach for navigation, where the agent learns to adapt in a self-supervised manner (bottom row). In this example, the agent learns to adapt itself when it collides with an object once and acts correctly afterwards. In contrast, a standard solution (top row) makes multiple mistakes of the same kind when performing the task.

as the structure of the scene and appearance of objects are unfamiliar. In this paper we propose a self-adaptive visual navigation (SAVN) model which learns to adapt during inference without any explicit supervision using an interaction loss (Figure 3.1).

Formally, our solution is a meta-reinforcement learning approach to visual navigation, where an agent learns to adapt through a self-supervised interaction loss. Our approach is inspired by gradient based meta-learning algorithms that learn quickly using a small amount of data [53]. In our approach, however, we learn quickly using a small amount of self-supervised interaction. In visual navigation, adaptation is possible without access to any reward function or positive example. As the agent trains, it learns a self-supervised loss that encourages effective navigation. During training, we encourage the gradients induced by the self-supervised loss to be similar to those we obtain from the supervised navigation loss. The agent is therefore able to adapt during inference when explicit supervision is not available.

In summary, during both training and testing, the agent modifies its network while performing navigation. This approach differs from traditional reinforcement learning where the network is frozen after training, and contrasts with supervised meta-learning as we learn to adapt to new environments during inference without access to rewards.

We perform our experiments using the AI2-THOR [100] framework. The agent aims to navigate to an instance of a given object category (e.g., *microwave*) using only visual observations. We show that SAVN outperforms the non-adaptive baseline in terms of both success rate (40.8 vs 33.0) and SPL (16.2 vs 14.7). Moreover, we demonstrate that learning a self-supervised loss provides improvement over hand-crafted self-supervised losses. Additionally, we show that our approach outperforms memory-augmented non-adaptive baselines.

3.1.2 Related Work

Deep Models for Navigation. Traditional navigation methods typically perform planning on a given map of the environment or build a map as the exploration proceeds [119; 174; 97; 102; 34; 16].

Recently, learning-based navigation methods (e.g., [226; 69; 121]) have become popular as they *implicitly* perform localization, mapping, exploration and semantic recognition end-to-end.

Zhu et al. [226] address target-driven navigation given a picture of the target. A joint mapper and planner has been introduced by [69]. [121] use auxiliary tasks such as loop closure to speed up RL training for navigation. We differ in our approach as we adapt dynamically to a novel scene. [160] propose the use of topological maps for the task of navigation. They explore the test environment for a long period to populate the memory. In our work, we learn to navigate without an exploration phase. [95] propose a self-supervised deep RL model for navigation. However, no semantic information is considered. [132] learn navigation policies based on object detectors and semantic segmentation modules. We do not rely on heavily supervised detectors and learn from a limited number of examples. [210; 197] incorporate semantic knowledge to better generalize to unseen scenarios. Both of these approaches dynamically update their manually defined knowledge graphs. However, our model learns which parameters should be updated during navigation and how they should be updated. Learning-based navigation has been explored in the context of other applications such as autonomous driving (e.g., [26]), map-based city navigation (e.g., [20]) and game play (e.g., [196]). Navigation using language instructions has been explored by various works [10; 23; 81; 215; 123]. Our goal is different since we focus on using meta-learning to more effectively navigate new scenes using only the class label for the target.

Meta-learning. Meta-learning, or learning to learn, has been a topic of continued interest in machine learning research [175; 162]. More recently, various meta-learning techniques have pushed the state of the art in low-shot problems across domains [53; 122; 45].

Finn et al. [53] introduce Model Agnostic Meta-Learning (MAML) which uses SGD updates to adapt quickly to new tasks. This gradient based meta-learning approach may also be interpreted as learning a good parameter initialization such that the network performs well after only a few gradient updates. [111] and [216] augment the MAML algorithm so that it uses supervision in one domain to adapt to another. Our work differs as we do not use supervision or labeled examples to

adapt.

Xu et al. [206] use meta-learning to significantly speed up training by encouraging exploration of the state space outside of what the actor's policy dictates. Additionally, [66] use meta-learning to augment the agent's policy with structured noise. At inference time, the agent is able to better adapt from a few episodes due to the variability of these episodes. Our work instead emphasizes self-supervised adaptation while executing a single visual navigation task. Neither of these works consider this domain.

Clavera et al. [32] consider the problem of learning to adapt to unexpected perturbations using meta-learning. Our approach is similar as we also consider the problem of learning to adapt. However, we consider the problem of visual navigation and adapt via a self-supervised loss.

Both [84] and [216] learn an objective function. However, [84] use evolutionary strategies instead of meta-learning. Our approach for learning a loss is inspired by and similar to [216]. However, we adapt in the same domain without explicit supervision while they adapt across domains using a video demonstration.

Self-supervision. Different types of self-supervision have been explored in the literature [5; 92; 41; 189; 221; 150; 144; 138]. Some works aim to maximize the prediction error in the representation of future states [141; 171]. In this work, we *learn* a self-supervised objective which encourages effective navigation.

3.1.3 Adaptive Navigation

In this section, we begin by formally presenting the task and our base model without adaptation. We then explain how to incorporate adaptation and perform training and testing in this setting.

3.1.3.1 Task Definition

Given a target object class, e.g. *microwave*, our goal is to navigate to an instance of an object from this class using only visual observations.




Figure 3.2: **Model overview.** Our network optimizes two objective functions, 1) self-supervised interaction loss $\mathcal{L}^{\phi}_{\text{int}}$ and 2) navigation loss $\mathcal{L}_{\text{nav}}$. The inputs to the network at each time t are the egocentric image from the current location and word embedding of the target object class. The network outputs a policy $\pi_\theta(s_t)$. During training, the interaction and navigation-gradients are back-propagated through the network, and the parameters of the self-supervised loss are updated at the end of each episode using navigation-gradients. At test time the parameters of the interaction loss remain fixed while the rest of the network is updated using interaction-gradients. Note that the green color in the figure represents the intermediate and final outputs.

Formally, we consider a set of scenes $\mathcal{S} = \{S_1, ..., S_n\}$ and target object classes $\mathcal{O} = \{o_1, ..., o_m\}$. A task $\tau \in \mathcal{T}$ consists of a scene S, target object class $o \in \mathcal{O}$, and initial position p. We therefore denote each task τ by the tuple $\tau = (S, o, p)$. We consider disjoint sets of scenes for the training tasks $\mathcal{T}_{\text{train}}$ and testing tasks $\mathcal{T}_{\text{test}}$. We refer to the trial of a navigation task as an episode.

The agent is required to navigate using only the egocentric RGB images and the target object class (the target object class is given as a Glove embedding [146]). At each time t the agent takes an action a from the action set $\mathcal{A}$ until the termination action is issued by the agent. We consider an episode to be successful if, within certain number of steps, the agent issues a termination action when an object from the given target class is sufficiently close and visible. If a termination action is issued at any other time, then the episode concludes and the agent has failed.

3.1.3.2 Learning

Before we discuss our self-adaptive approach we begin with an overview of our base model and discuss deep reinforcement learning for navigation in a traditional sense.

We let s_t, the egocentric RGB image, denote the agent's state at time t. Given s_t and the target object class, the network (parameterized by θ) returns a distribution over the actions which we denote $\pi_\theta(s_t)$ and a scalar $v_\theta(s_t)$. The distribution $\pi_\theta(s_t)$ is referred to as the agent's *policy* while $v_\theta(s_t)$ is the *value* of the state. Finally, we let $\pi_\theta^{(a)}(s_t)$ denote the probability that the agent chooses action a.

We use a traditional supervised actor-critic navigation loss as in [226; 121] which we denote $\mathcal{L}_{\text{nav}}$. By minimizing $\mathcal{L}_{\text{nav}}$, we maximize a reward function that penalizes the agent for taking a step while incentivizing the agent to reach the target. The loss is a function of the agent's policies, values, actions, and rewards throughout an episode.

The network architecture is illustrated in Figure 3.2. We use a ResNet18 [79] pretrained on ImageNet [38] to extract a feature map for a given image. We then obtain a joint feature-map consisting of both image and target information and perform a pointwise convolution. The output is then flattened and given as input to a Long Short-Term Memory network (LSTM). For the remainder of this work we refer to the LSTM hidden state and agent's internal state representation interchangeably. After applying an additional linear layer we obtain the policy and value. In Figure 3.2 we do not show the ReLU activations we use throughout, or reference the value $v_\theta(s_t)$.

3.1.3.3 Learning to Learn

In visual navigation there is ample opportunity for the agent to learn and adapt by interacting with the environment. For example, the agent may learn how to handle obstacles it is initially unable to circumvent. We therefore propose a method in which the agent learns how to adapt from interaction. The foundation of our method lies in recent works which present gradient based algorithms for learning to learn (meta-learning).

Background on Gradient Based Meta-Learning. We rely on the meta-learning approach detailed by the MAML algorithm [53]. The MAML algorithm optimizes for fast adaptation to new tasks. If the distribution of training and testing tasks are sufficiently similar then a network trained with MAML should quickly adapt to novel test tasks.

MAML assumes that during training we have access to a large set of tasks $\mathcal{T}_{\text{train}}$ where each task $\tau \in \mathcal{T}_{\text{train}}$ has a small meta-training dataset $\mathcal{D}_\tau^{\text{tr}}$ and meta-validation set $\mathcal{D}_\tau^{\text{val}}$. For example, in the problem of k-shot image classification, τ is a set of image classes and $\mathcal{D}_\tau^{\text{tr}}$ contains k examples of each class. The goal is then to correctly assign one of the class labels to each image in $\mathcal{D}_\tau^{\text{val}}$. A testing task $\tau \in \mathcal{T}_{\text{test}}$ then consists of unseen classes.

The training objective of MAML is given by

$$\min_{\theta} \sum_{\tau \in \mathcal{T}_{\text{train}}} \mathcal{L}\left(\theta - \alpha \nabla_\theta \mathcal{L}\left(\theta, \mathcal{D}_\tau^{\text{tr}}\right), \mathcal{D}_\tau^{\text{val}}\right), \tag{3.1}$$

where the loss $\mathcal{L}$ is written as a function of a dataset and the network parameters θ. Additionally, α is the step size hyper-parameter, and ∇ denotes the differential operator (gradient). The idea is to learn parameters θ such that they provide a good initialization for fast adaptation to test tasks. Formally, Equation 3.1 optimizes for performance on $\mathcal{D}_\tau^{\text{val}}$ after *adapting* to the task with a gradient step on $\mathcal{D}_\tau^{\text{tr}}$. Instead of using the network parameters θ for inference on $\mathcal{D}_\tau^{\text{val}}$, we use the *adapted* parameters $\theta - \alpha \nabla_\theta \mathcal{L}\left(\theta, \mathcal{D}_\tau^{\text{tr}}\right)$. In practice, multiple SGD updates may be used to compute the adapted parameters.

Training Objective for Navigation. Our goal is for an agent to be continually learning as it interacts with an environment. As in MAML, we use SGD updates for this adaptation. These SGD updates modify the agent's policy network as it interacts with a scene, allowing the agent to adapt to the scene. We propose that these updates should occur with respect to $\mathcal{L}_{\text{int}}$, which we call an *interaction loss*. Minimizing $\mathcal{L}_{\text{int}}$ should assist the agent in completing its navigation task, and it can be learned or hand-crafted. For example, a hand-crafted variation may penalize the agent for

visiting the same location twice. In order for the agent to have access to $\mathcal{L}_{\text{int}}$ during inference, we use a self-supervised loss. Our objective is then to learn a good initialization θ, such that the agent will learn to effectively navigate in an environment after a few gradient updates using $\mathcal{L}_{\text{int}}$.

For clarity, we begin by formally presenting our method in a simplified setting in which we allow for a single SGD update with respect to $\mathcal{L}_{\text{int}}$. For a navigation task τ we let $\mathcal{D}_\tau^{\text{int}}$ denote the actions, observations, and internal state representations (defined in Section 3.1.3.2) for the first k steps of the agent's trajectory. Additionally, let $\mathcal{D}_\tau^{\text{nav}}$ denote this same information for the remainder of the trajectory. Our training objective is then formally given by

$$\min_\theta \sum_{\tau \in \mathcal{T}_{\text{train}}} \mathcal{L}_{\text{nav}} \left(\theta - \alpha \nabla_\theta \mathcal{L}_{\text{int}} \left(\theta, \mathcal{D}_\tau^{\text{int}} \right), \mathcal{D}_\tau^{\text{nav}} \right), \tag{3.2}$$

which mirrors the MAML objective from Equation 3.1. However, we have replaced the small training set $\mathcal{D}_\tau^{\text{tr}}$ from MAML with an interaction phase. The intuition for our objective is as follows: at first we interact with the environment and then we adapt to it. More specifically, the agent interacts with the scene using the parameters θ. After k steps an SGD update with respect to the self-supervised loss is used to obtain the *adapted* parameters $\theta - \alpha \nabla_\theta \mathcal{L}_{\text{int}} \left(\theta, \mathcal{D}_\tau^{\text{int}} \right)$.

In domain adaptive meta-learning, two separate losses are used for adaptation from one domain to another [111; 216]. A similar objective to Equation 3.2 is employed by [216] for one-shot imitation from observing humans. Our method differs in that we are learning how to adapt in the same domain through self-supervised interaction.

As in [111], a first order Taylor expansion provides intuition for our training objective. Equation 3.2 is approximated by

$$\begin{aligned} \min_\theta \sum_{\tau \in \mathcal{T}_{\text{train}}} & \mathcal{L}_{\text{nav}} \left(\theta, \mathcal{D}_\tau^{\text{nav}} \right) \\ & - \alpha \left\langle \nabla_\theta \mathcal{L}_{\text{int}} \left(\theta, \mathcal{D}_\tau^{\text{int}} \right), \nabla_\theta \mathcal{L}_{\text{nav}} \left(\theta, \mathcal{D}_\tau^{\text{nav}} \right) \right\rangle, \end{aligned} \tag{3.3}$$

where $\langle \cdot, \cdot \rangle$ denotes an inner product. We are therefore learning to minimize the navigation loss

while *maximizing* the *similarity* between the gradients we obtain from the self-supervised interaction loss and the supervised navigation loss. If the gradients we obtain from both losses are similar, then we are able to continue "training" during inference when we do not have access to $\mathcal{L}_{\text{nav}}$. However, it may be difficult to choose $\mathcal{L}_{\text{int}}$ which allows for similar gradients. This directly motivates *learning* the self-supervised interaction loss.

3.1.3.4 Learning to Learn How to Learn

We propose to *learn* a self-supervised interaction objective that is explicitly tailored to our task. Our goal is for the agent to improve at navigation by minimizing this self-supervised loss in the current environment.

During training, we both learn this objective and learn how to learn using this objective. We are therefore "learning to learn how to learn". As input to this loss we use the agent's previous k internal state representations concatenated with the agent's policy.

Formally, we consider the case where $\mathcal{L}_{\text{int}}$ is a neural network parameterized by ϕ, which we denote $\mathcal{L}^{\phi}_{\text{int}}$. Our training objective then becomes

$$\min_{\theta,\phi} \sum_{\tau \in \mathcal{T}_{\text{train}}} \mathcal{L}_{\text{nav}} \left(\theta - \alpha \nabla_{\theta} \mathcal{L}^{\phi}_{\text{int}} \left(\theta, \mathcal{D}^{\text{int}}_{\tau} \right), \mathcal{D}^{\text{nav}}_{\tau} \right) \tag{3.4}$$

and we freeze the parameters ϕ during inference. There is no explicit objective for the learned-loss. Instead, we simply encourage that minimizing this loss allows the agent to navigate effectively. This may occur if the gradients from both losses are similar. In this sense we are training the self-supervised loss to imitate the supervised $\mathcal{L}_{\text{nav}}$ loss.

As in [216], we use one dimensional temporal convolutions for the architecture of our learned loss. We use two layers, the first with 10×1 filters and the next with 1×1. As input we concatenate the past k hidden states of the LSTM and the previous k policies. To obtain the scalar objective we take the ℓ_2 norm of the output. Though we omit the ℓ_2 norm, we illustrate our interaction loss in

Algorithm 1 SAVN-Training($\mathcal{T}_{\text{train}}, \alpha, \beta_1, \beta_2, k$)

Randomly initialize θ, ϕ.
while not converged **do**
  for mini-batch of tasks $\tau_i \in \mathcal{T}_{\text{train}}$ **do**
    $\theta_i \leftarrow \theta$
    $t \leftarrow 0$
    while termination action is not issued **do**
      Take action a sampled from $\pi_{\theta_i}(s_t)$
      $t \leftarrow t + 1$
      if t is divisible by k **then**
        $\theta_i \leftarrow \theta_i - \alpha \nabla_{\theta_i} \mathcal{L}^{\phi}_{\text{int}} \left(\theta_i, \mathcal{D}^{(t,k)}_{\tau}\right)$
      end if
    end while
  end for
  $\theta \leftarrow \theta - \beta_1 \sum_i \nabla_{\theta} \mathcal{L}_{\text{nav}}(\theta_i, \mathcal{D}_{\tau})$
  $\phi \leftarrow \phi - \beta_2 \sum_i \nabla_{\phi} \mathcal{L}_{\text{nav}}(\theta_i, \mathcal{D}_{\tau})$
end while
return θ, ϕ

Figure 3.2.

Hand Crafted Interaction Objectives. We also experiment with two variations of simple hand crafted interaction losses which can be used as an alternative to the learned loss. The first is a diversity loss $\mathcal{L}^{\text{div}}_{\text{int}}$ which encourages the agent to take varied actions. If the agent does happen to reach the same state multiple times it should definitely not repeat the action it previously took. Accordingly,

$$\mathcal{L}^{\text{div}}_{\text{int}}\left(\theta, \mathcal{D}^{\text{int}}_{\tau}\right) = \sum_{i<j\leq k} g(s_i, s_j) \log\left(\pi^{(a_i)}_{\theta}(s_j)\right), \tag{3.5}$$

where s_t is the agent's state at time t, a_t is the action the agent takes at time t, and g calculates the similarity between two states. For simplicity we let $g(s_i, s_j)$ be 1 if the pixel difference between s_i and s_j is below a certain threshold and 0 otherwise.

Additionally, we consider a prediction loss $\mathcal{L}^{\text{pred}}_{\text{int}}$ where the agent aims to predict the success of each action. The idea is to avoid taking actions that the network predicts will fail. We say that the agent's action has failed if we detect sufficient similarity in two consecutive states. This may

Algorithm 2 SAVN-Testing($\mathcal{T}_{\text{test}}, \theta, \phi, \alpha, \beta, k$)

for mini-batch of tasks $\tau_i \in \mathcal{T}_{\text{test}}$ **do**
    $\theta_i \leftarrow \theta$
    $t \leftarrow 0$
    while termination action is not issued **do**
        Take action a sampled from $\pi_{\theta_i}(s_t)$
        $t \leftarrow t + 1$
        if t is divisible by k **then**
            $\theta_i \leftarrow \theta_i - \alpha \nabla_{\theta_i} \mathcal{L}_{\text{int}}^{\phi} \left(\theta_i, \mathcal{D}_{\tau}^{(t,k)} \right)$
        end if
    end while
end for

occur when the agent bumps into an object or wall. In addition to producing a policy π_θ over actions the agent also predicts the success of each action. For state s_t we denote the predicted probability that action a succeeds as $q_\theta^{(a)}(s_t)$. Instead of sampling an action from $\pi_\theta(s_t)$ we instead use $\tilde{\pi}_\theta(s_t) = \pi_\theta(s_t) * q_\theta(s_t)$ where $*$ denotes element-wise multiplication.

For $\mathcal{L}_{\text{int}}^{\text{pred}}$ we use a standard binary cross entropy loss between our success prediction $q_\theta^{(a)}$ and observed success. Using the same g from Equation 3.5 we write our loss as

$$\mathcal{L}_{\text{int}}^{\text{pred}} \left(\theta, \mathcal{D}_{\tau}^{\text{int}} \right) = \sum_{t=0}^{k-1} \mathcal{H} \left(q_\theta^{(a_t)}(s_t), 1 - g(s_t, s_{t+1}) \right), \tag{3.6}$$

where $\mathcal{H}(\cdot, \cdot)$ denotes binary cross-entropy.

We acknowledge that in a non-synthetic environment it may be difficult to produce a reliable function g. Therefore we only use g in the hand-crafted variations of the loss.

3.1.3.5 Training and Testing

So far we have implicitly decomposed the agent's trajectory into an interaction and navigation phase. In practice, we would like the agent to keep adapting until the object is found during both training and testing. We therefore perform an SGD update with respect to the self-supervised interaction loss every k steps. We compute the interaction loss at time t by using the information from the previous

k steps of the agent's trajectory, which we denote $\mathcal{D}_\tau^{(t,k)}$. Note that $\mathcal{D}_\tau^{(t,k)}$ is analogous to $\mathcal{D}_\tau^{\text{int}}$ in Equation 3.4. In addition, the agent should be able to navigate efficiently. Hence, we compute the navigation loss $\mathcal{L}_{\text{nav}}$ using the the information from the complete trajectory of the agent, denoted by $\mathcal{D}_\tau$.

For the remainder of this work we refer to the gradient with respect to $\mathcal{L}_{\text{int}}$ as the *interaction-gradient* and the gradient with respect to $\mathcal{L}_{\text{nav}}$ as the *navigation-gradient*. These gradients are illustrated in Figure 3.2 by red and green arrows, respectively. Note that we do not update the loss parameters ϕ via the interaction-gradient.




Figure 3.3: **Qualitative examples.** We compare our method with the non-adaptive baseline. We illustrate the trajectory of the agent (white corresponds to the beginning of the trajectory and dark blue shows the end). Black arrows represent rotation. We also show the egocentric view of the agent at a few time steps. Our method may learn from its mistakes (e.g., getting stuck behind an object).

Though traditional works use testing and inference interchangeably we may regard inference more abstractly as any setting in which the task is performed without supervision. This occurs not only during testing but also within each episode of navigation during training.

Algorithms 1 and 2 detail our method for training and testing, respectively. In Algorithm 1 we learn a policy network π_θ and a loss network parameterized by ϕ with step-size hyper-parameters

α, β_1, β_2. Recall that k is a hyper-parameter which prescribes the frequency of the interaction-gradients. If we are instead considering a hand-crafted self-supervised loss then we ignore ϕ and omit line 12.

Recall that the adapted parameters, which we denote θ_i in Algorithm 1 and 2, are implicitly a function of θ, ϕ. Therefore, the differentiation in lines 11 and 12 is well defined though it requires the computation of Hessian vector-products. We never compute more than 4 interaction-gradients due to computational constraints.

At test time we may adapt in an environment with respect to the self-supervised interaction loss, but we no longer have access to $\mathcal{L}_{\text{nav}}$. Note that the shared parameter θ is not updated during testing, as detailed in Algorithm 2.

3.1.4 Experiments

Our goal in this section is to (1) evaluate our self-adaptive navigation model in comparison to non-adaptive baselines, (2) determine if the learned self-supervised objective provides any improvement over hand-crafted self-supervised losses, and (3) gain insight into how and why our method may be improving performance.

3.1.4.1 Experiment setup

We train and evaluate our models using the AI2-THOR [100] environment. AI2-THOR provides indoor 3D synthetic scenes in four room categories, kitchen, living room, bedroom and bathroom. For each room type, we use 20 scenes for training, 5 for validation and 5 for testing (a total of 120 scenes).

We choose a subset of target object classes as our navigation targets such that (1) they are not hidden in cabinets, fridges, etc., (2) they are not too large that they take a big portion of the room and are visible from most parts of the room (e.g., beds in bedrooms). We choose the following sets of objects for each type of room: 1) Living room: pillow, laptop, television, garbage can, box,

and bowl. 2) Kitchen: toaster, microwave, fridge, coffee maker, garbage can, box, and bowl. 3) Bedroom: plant, lamp, book, and alarm clock. 4) Bathroom: sink, toilet paper, soap bottle, and light switch.

We consider the actions $\mathcal{A} = \{$`MoveAhead`, `RotateLeft`, `RotateRight`, `LookDown`, `LookUp`, `Done`$\}$. Horizontal rotation occurs in increments of 45 degrees while looking up and down change the camera tilt angle by 30 degrees. `Done` corresponds to the termination action discussed in Section 3.1.3.1. The agent successfully completes a navigation task if this action is issued when an instance from the target object class is within 1 meter from the agent's camera and within the field of view. This follows from the primary recommendation of [9]. Note that if the agent ever issues the `Done` action when it has not reached a target object then we consider the task a failure.

3.1.4.2 Implementation details

We train our method and baselines until the success rate saturates on the validation set. We train one model across all scene types with an equal number of episodes per type using 12 asynchronous workers. For $\mathcal{L}_{\text{nav}}$, we use a reward of 5 for finding the object and -0.01 for taking a step. For each scene we randomly sample an object from the scene as a target along with a random initial position. For our interaction-gradient updates we use SGD and for our navigation-gradients we use Adam [98]. For step size hyper-parameters (α, β_1, β_2 in Algorithm 1) we use 10^{-4} and for k we use 6. Recall that k is the hyper-parameter which prescribes the frequency of interaction-gradients. We experimented with a schedule for k but saw no significant improvement in performance.

For evaluation we perform inference for 1000 different episodes (250 for each scene type). The scene, initial state of the agent and the target object are randomly chosen. All models are evaluated using the same set. For each training run we select the model that performs best on the validation set in terms of success.

3.1.4.3 Evaluation metrics

We evaluate our method on unseen scenes using both Success Rate and Success weighted by Path Length (SPL). SPL was recently proposed by [9] and captures information about navigation efficiency. Success is defined as $\frac{1}{N}\sum_{i=1}^{N}\mathcal{S}_i$ and SPL is defined as $\frac{1}{N}\sum_{i=1}^{N}\mathcal{S}_i\frac{L_i}{\max(P_i,L_i)}$, where N is the number of episodes, $\mathcal{S}_i$ is a binary indicator of success in episode i, P_i denotes path length and L_i is the length of the optimal trajectory to any instance of the target object class in that scene. We evaluate the performance of our model both on all trajectories and trajectories where the optimal path length is at least 5. We denote this by $L \geq 5$ (L refers to optimal trajectory length).

3.1.4.4 Baselines

We compare our models with the following baselines:

Random agent baseline. At each time step the agent randomly samples an action using a uniform distribution.

Nearest neighbor (NN) baseline. At each time step we select the most similar visual observation (in terms of Euclidean distance between ResNet features) among scenes in training set which contain an object of the class we are searching for. We then take the action that is optimal in the train scene when navigating to the same object class.

No adaptation (A3C) baseline. The architecture for the baseline is the same as ours, however there is no interaction-gradient and therefore no interaction loss. The training objective for this baseline is then $\min_\theta \sum_{\tau\in\mathcal{T}_{\text{train}}} \mathcal{L}_{\text{nav}}(\theta, \mathcal{D}_\tau)$ which is equivalent to setting $\alpha = 0$ in Equation 3.4. This baseline is trained using A3C [125].

3.1.4.5 Results

Table 3.1 summarizes the results of our approach and the baselines. We consider three variations of our method, which include SAVN (learned self-supervised loss) and the hand-crafted prediction and diversity loss alternatives.

	All		$L \geq 5$	
	SPL	Success	SPL	Success
Random	$3.64_{(0.6)}$	$8.0_{(1.3)}$	$0.1_{(0.1)}$	$0.28_{(0.1)}$
NN	6.09	7.90	1.38	1.66
No Adapt (A3C)	$14.68_{(1.8)}$	$33.04_{(3.5)}$	$11.69_{(1.9)}$	$21.44_{(3.0)}$
Scene Priors [210]	$15.47_{(1.1)}$	$35.13_{(1.3)}$	$11.37_{(1.6)}$	$22.25_{(2.7)}$
Ours - prediction	$14.36_{(1.1)}$	$38.06_{(2.9)}$	$12.61_{(1.3)}$	$26.41_{(2.4)}$
Ours - diversity	$15.12_{(1.5)}$	$39.52_{(3.0)}$	$13.38_{(1.4)}$	$27.66_{(3.5)}$
Ours - SAVN	$\mathbf{16.15_{(0.5)}}$	$\mathbf{40.86_{(1.2)}}$	$\mathbf{13.91_{(0.5)}}$	$\mathbf{28.70_{(1.5)}}$

Table 3.1: **Quantitative results.** We compare variations of our method with random, nearest neighbor and non-adaptive baselines. We consider two evaluation metrics, Success Rate and SPL. We provide results for all targets 'All' and a subset of targets whose optimal trajectory length is greater than 5. We report the average over 5 training runs with standard deviations shown in sub-scripted parentheses.

Our learned self-supervised loss outperforms all baselines by a large margin in terms of both success rate and SPL metrics. Most notably, we observe about 8% absolute improvement in success and 1.5 in SPL over the non-adaptive (A3C) baseline. The self-supervised objective not only learns to navigate more effectively but it also learns to navigate efficiently.

The models trained with hand-crafted exploration losses outperform our baselines by large margins in success, however, the SPL performance is not as impressive as with the learned loss. We hypothesize that minimizing these hand-crafted exploration losses are not as conducive to efficient navigation.

Failed actions. We now explore a behavior which sets us apart from the non-adaptive baseline. In the beginning of an episode the agent looks around or explores the free space in front of it. However, as the episode progresses, the non-adaptive agent might issue the termination action or get stuck. Our method (SAVN), however, exhibits this pattern less frequently.

To examine this behavior we compute the ratio of actions which fail. Recall that an agent's action has failed if two consecutive frames are sufficiently similar. Typically, this will occur if an agent collides with an object. As shown in Figure 3.4, our method experiences significantly fewer failed actions than the baseline as the episode progresses.

Qualitative examples. Figure 3.3 qualitatively compares our method with the non-adaptive (A3C)




Figure 3.4: **Failed actions.** Our approach learns to adapt and not to take unsuccessful actions as the navigation proceeds.

baseline. In scenario (a) our baseline gets stuck behind the box and tries to move forward multiple times, while our method adapts dynamically and finds the way towards the television. Similarly in scenario (c), the baseline tries to move towards the lamp but after bumping into the bed 5 times and rotating 9 times, it issues `Done` in a distant location from the target.

3.1.4.6 Ablation Study

In this section we perform an ablation on our methods to gain further insight into our result.

Adding modules to the non-adaptive baseline. In Table 3.2 we experiment with the addition of various modules to our non-adaptive baseline. We begin by augmenting the baseline with an additional memory module which performs self-attention on the latest $k = 6$ hidden states of the LSTM. SAVN outperforms the memory-augmented baseline as well.

Additionally, we add the prediction loss detailed in Section 3.1.3.4 to the training objective. This experiment reveals that our result is not simply a consequence of additional losses. By using our training objective with the added hand-crafted prediction loss (referred to as 'Ours - prediction'), we outperform the baseline non-adaptive model with prediction (referred to as 'A3C w/ prediction') by 3.3% for all trajectories and 4.8% for trajectories of at least length 5 in terms of success rate. As discussed in the Section 3.1.4.5, minimizing the hand-crafted objectives during the episode may not be optimal for efficient exploration. This may be why we show a boost in SPL for trajectories of at

	All		$L \geq 5$	
	SPL	Success	SPL	Success
No Adapt (A3C)	14.68	33.04	11.69	21.44
A3C w/ mem	15.54	34.30	11.21	20.50
A3C w/ prediction loss	14.95	34.80	10.94	21.60
Ours - prediction	14.36	38.06	12.61	26.41
Ours - SAVN	**16.15**	**40.86**	**13.91**	**28.70**
A3C (GT obj)	31.34	44.40	16.77	26.05
Ours - SAVN (GT obj)	**35.55**	**54.40**	**23.47**	**37.87**

Table 3.2: **Ablation results.** We compare our approach with the non-adaptive baseline augmented with memory and our hand-crafted loss. We also provide the result when we use ground truth object information (bottom two rows).

least length 5 but not overall. We run the same experiment with the diversity loss but find that the baseline model is unable to converge with this additional loss.

Ablation of the number of gradients. To showcase the efficacy of our method we modify the number of interaction-gradient steps that we perform during the adaptation phase during training and testing. As discussed in Section 3.1.3.5, we never perform more than 4 interaction-gradients due to computational constraints. As illustrated by Figure 3.5, there is an increase in success rate when more gradient updates are used, demonstrating the importance of the interaction-gradients.




Figure 3.5: **Number of Gradients Ablation.** Our success rate increases as more interaction-gradients are taken during training/testing.

Perfect object information. Issuing the termination action at the correct location plays an important role in our navigation task. We observe that SAVN still outperforms the baseline even when the

termination signal is provided by the environment (referred to as 'GT obj' in Table 3.2).

3.1.5 Conclusions

We introduce a self-adaptive visual navigation agent (SAVN) that learns during both training and inference. During training the model learns a self-supervised interaction loss that can be used when there is no supervision. Our experiments show that this approach outperforms non-adaptive baselines by a large margin. Furthermore, we show that the learned interaction loss performs better than hand-crafted losses. Additionally, we find that SAVN navigates more effectively than a memory-augmented non-adaptive baseline. We conjecture that this idea may be applied in other domains where the agents may learn from self-supervised interactions.

3.2 Learning to interact

3.2.1 Introduction

Embodied AI, the sub-specialty of artificial intelligence at the intersection of robotics, computer vision, and natural language processing continues to gain popularity amongst researchers within these communities. This has expedited progress on several fronts – open source *simulators* are getting faster, more robust, and more realistic via photorealism and sophisticated physics engines, a variety of *tasks* are being worked on such as navigation and instruction following, new *algorithms* and *models* are inching us towards more powerful and generalizable models and the recent development of multiple sim-to-real environments with paired worlds in simulation and real is enabling researchers to study the challenges of overcoming the domain gap from virtual to physical spaces. A notable outcome has been the development of near-perfect pure learning-based Point Navigation [193] agents, far outperforming classical approaches.

Most of the focus and progress in Embodied AI has revolved around the task of navigation –

including navigating to coordinates, to object instances, and to rooms. Navigating around in an environment is a critical means to an end, not an end in itself. The aspiration of the Embodied AI community remains the development of embodied agents that can perform complex tasks in the real world, tasks that involve actively manipulating objects in one's environment. The early successes and interest in Embodied AI have laid a foundation for the community to tackle the myriad of challenges that lie within the problem of object manipulation.

Object manipulation has long posed daunting challenges to roboticists. Moving manipulators within an environment requires estimating free spaces and avoiding obstacles in the scene, tasks which are rendered even harder due to the unwieldy nature of robotic arms. Generalizing to novel environments and objects is another important challenge. Finally, real-world tasks often involve manipulating multiple objects in succession in cluttered scenes, which requires fairly complex visual reasoning and planning. Besides, developing simulators for object manipulation poses a unique set of challenges. In contrast to navigation tasks that require camera translation and fairly rudimentary collision checking, object manipulation requires fine grained collision detection between the agent, its arms, and surrounding objects, and the usage of advanced physics emulators to compute the resulting displacements of the constituent entities. In particular, these computations are expensive and require significant engineering efforts to produce effective simulations at reasonably high frame rates.

We extend the AI2-THOR [101] framework by adding arms to its agents, enabling these agents to not only navigate around their environments but also actively manipulate objects within them. The newly introduced arm rig is designed to work with both forward and inverse kinematics, which allows one to control the arm using both joint actuations or by specifying the desired wrist translation. This flexibility allows Embodied AI practitioners to train policies requiring fine-grained actuator controls for all joints if they so desire, or instead use inbuilt kinematics functionalities and focus solely on the desired positioning of the end of the arm and manipulator.

As a first step towards generalizable object manipulation, we present the task of ARMPOINTNAV–



Figure 3.6: We address the problem of *visual object manipulation*, where the goal is to move an object between two locations in a scene. Operating in visually rich and complex environments, generalizing to unseen environments and objects, avoiding collisions with objects and structures in the scene, and visual planning to reach the destination are among the major challenges of this task. Here, we illustrate a sequence of actions taken a by a virtual robot within the AI2-THOR environment for picking up a vase from the shelf and stack it on a plate on the countertop.

moving in the scene towards an objects, picking it up and moving it to the desired location (Figure 3.6). ARMPOINTNAV builds upon the navigation task of PointNav [9] in that it is an atomic locomotive task, a key component of more complex downstream goals, specifies source and target locations using relative coordinates as opposed to other means such as language or images and utilizes compass as part of its sensor suite. But in contrast, it offers significant new challenges. Firstly, the task requires the motion of both the agent and the arm within the environment. Secondly, it frequently entails reaching behind occluding obstacles to pick up objects which requires careful arm manipulation to avoid collisions with occluding objects and surfaces. Thirdly, it may also require the agent to manipulate multiple objects in the scene as part of a successful episode, to remove objects, or make space to move the target object, which requires long-term planning with multiple entities. Finally, the motion of the arm frequently occludes a significant portion of the view, as one may expect, which is in sharp contrast to PointNav that only encounters static unobstructed views of the world.

The end-to-end ARMPOINTNAV model provides strong baseline results and shows an ability to not just generalize to new environments but also to novel objects within these environments – a strong foundation towards learning generalizable object manipulation models. This end-to-end model is superior to a disjoint model that learns a separate policy for each skill within an episode.

In summary, we (a) introduce a novel efficient framework (ManipulaTHOR) for low level object manipulation, (b) present a new dataset for this task with new challenges for the community, and (c) train an agent that generalizes to manipulating novel objects in unseen environments. Our framework, dataset and code will be publicly released. We hope that this new framework encourages the Embodied AI community towards solving complex but exciting challenges in visual object manipulation.

3.2.2 Related Works

Object Manipulation. A long-standing problem in robotics research is object manipulation [52; 15; 17; 172; 209; 18; 47; 108; 48]. Here, we explain some recent example works that are more relevant to our work. [59] address the problem of multi-step manipulation to interact with objects in presence of clutter and occlusion. [133] propose a planning approach to grasp objects in a cluttered scene by relying on partial point cloud observation. [208] learn a 3D scene representation to predict the dynamics of objects during manipulation. [72] propose a reinforcement learning approach for robotic manipulation where they construct new policies by composing existing skills. [49] propose a model-based planner for multi-step manipulation. [110; 199] study mobile manipulation by generating sub-goal tasks. A combination of visually complex scenes, generalization to novel objects and scenes, joint navigation and manipulation, as well as navigating while manipulating object in hand are the key factors that distinguish our work from the previous work on object manipulation.

Environments for object manipulation. While several popular Embodied AI frameworks have focused on the navigation task, recently proposed improvements and frameworks such as iGibson [200], SAPIEN [201] and TDW [56] have enabled new research into manipulation. Sapien [201] is a virtual environment designed for low-level control of a robotic agent with an arm. In contrast, our framework includes a variety of visually rich and reconfigurable scenes allowing for a better exploration of the perception problem. Meta-World [217] is developed to study multi-task learning

in the context of robotic manipulation. The Meta-World framework includes a static table-top robotic arm and a limited set of objects. In contrast, our framework enables studying the problem of joint navigation and manipulation using a variety of objects. RLBench [91] also provides a simulated environment for a table-top robotic arm. RoboTurk [117] is a crowdsourcing platform to obtain human trajectories for robotic manipulation. RoboTurk also considers table-top manipulation scenarios. [67] provide a large-scale dataset of grasping and manipulation to evaluate the generalization of the models to unstructured visual environments. Unlike our framework, their dataset is non-interactive and includes only pre-recorded manipulation trajectories. iGibson [200] involves object interaction, but it does not support low-level manipulation (the interactions primarily involved pushing objects and rotation around hinges). Recently, an extension of iGibson [164] has enabled object manipulation with contact forces.

Visual navigation. Our problem can be considered as an extension of the visual navigation work [226; 69; 121; 160; 194; 211; 22; 193] in the Embodied AI literature. There are a few key differences between our manipulation task and navigation. In manipulation, the shape of the agent changes dynamically due to the extension of the arm. Also, the manipulation of objects is performed in 3D and through clutter, while the navigation works assume 2D motion on a plane in fairly clean scenes. Finally, our proposed task requires the agent to plan its motion as well as the motion of its arm simultaneously.

3.2.3 ManipulaTHOR

The growing popularity of Embodied AI can be partly attributed to the availability of numerous free and fast 3D simulators such as AI2-THOR [101], Habitat [161] and iGibson [200]. Some of these simulators excel at their photorealism, some at their speed, some at the interactivity they afford while others at their physics simulations. While researchers have many options to choose from when it comes to researching embodied navigation, fewer choices exist to study object manipulation, particularly in visually rich environments with varied objects and scenes.

Simulating object manipulation presents unique challenges to simulator builders beyond ones posed by navigation, including the need for fine-grained physics emulations, object and manipulator properties, and obtaining acceptable frame rates.

We present ManipulaTHOR, an extension to the AI2-THOR framework that adds arms to its agents. AI2-THOR is a suitable base framework due to its powerful physics engine, Unity, variety of realistic indoor scenes, large asset library of open source manipulable objects as well as articulated receptacles such as cabinets, microwaves, boxes, and fridges. While AI2-THOR has been previously used to train agents that interact with objects, this interaction has been invoked at a high level – for instance, a cabinet is opened by choosing a point on the cabinet and invoking the “open" command. ManipulaTHOR allows agents to interact with objects at a lower level via their arm manipulators, and thus opens up a whole new direction for Embodied AI research. The sensors that are available for use are RGB image, depth frame, GPS, agent’s location, and arm configuration.

Arm Design. In ManipulaTHOR, each agent has a single arm. The physical design of the arm is deliberately simple: a three-jointed arm with equal limb-lengths, attached to the body of the agent. This design is inspired by Kinova’s line of robots [1], with smooth contours and seamless joint-transitions and it is composed entirely of swivel joints, each with a single axis of rotation. The shoulder and wrist support 360 degrees of rotation and the hand grasper comes with a 6DOF (see Figure 3.7). The robot’s arm rig has been designed to work with either forward or inverse kinematics (IK), meaning its motion can be driven joint-by-joint, or directly from the wrist, respectively.

Grasper. The Grasper is defined as a sphere at the end of the arm. Objects that intersect with the sphere can be picked up by the grasper. This abstract design follows the ‘abstracted grasping’ actuation model of [14] in lieu of more involved designs like jaw grippers or humanoid hand graspers, enabling researchers to solve problems involved with object manipulation through the environment without having to account for the complexities of grasping. Object grasping is a challenging problem with a rich history in the robotics community and we hope to add this explicit




Figure 3.7: **Arm Design and Kinematic Constraints.** The arm consists of four joints (a). The max reach of the arm is defined by a hemisphere centered around the end of the first joint, whose radius is equal to 0.6335m (b,c). The height of the arm can be adjusted along the body of the agent (d). All joint rotations are solved by inverse kinematics, so any position the wrist can move to within the hemisphere's extents will have the joints rotate to accommodate the position of the wrist joint (e,f).

functionality into ManipulaTHOR in future versions.

Arm Interface. The arm comes with the following functionalities: 1) manipulating the location and orientation of the wrist (the joints connecting the base of the arm to the wrist are resolved via IK as the wrist moves), 2) adjusting the height of the arm, 3) obtaining the arm state's metadata including joint positions, 4) picking up the objects colliding with the grasper's sphere, 5) dropping the held object and 6) changing the radius of the grasper's sphere.

Physics Engine. We use NVIDIA's PhysX engine through Unity's engine integration to enable physically realistic object manipulation. This engine allows us to realistically move objects around, move the arm in the space, and cascade forces when the arm hits an object.

Rendering Speed. Accurate collision detection and object displacement estimation are very time consuming but are important requirements for our simulator. Through extensive engineering

efforts, we are able to obtain a training speed of 300 frames per second (fps) on a machine with 8 NVIDIA T4 GPUs running 40 cores. To put this into perspective, POINTNAV using AI2-THOR on the same machine achieves a training speed of roughly 800 fps, but has very rudimentary collision checks and no arm to manipulate. At 300 fps researchers may train for 20M steps per day, a fast rate to advance research in this direction, which we hope to improve significantly with more optimizations in our code base.

3.2.4 ARMPOINTNAV

As a first step towards generalizable object manipulation, we present the task of ARMPOINTNAV– moving an object in the scene from a source location to a target location. This involves, navigating towards the object, moving the arm gripper close to the object, picking it up, navigating towards the target location, moving the arm gripper (with the object in place) close to the target location, and finally releasing the object so it lands carefully. In line with the agent navigation task of POINTNAV [9], source and target locations of the object are specified via (x, y, z) coordinates in the agent coordinate frame.




Figure 3.8: **Scene and object splits in APND.** In order to benchmark the performance on ARMPOINTNAV, in addition to providing a large pool of datapoints for training, we provide a small subset of tasks per data split. We randomly subsampled 60 tasks per object per scene for evaluation purposes.

Dataset. To study the task of ARMPOINTNAV, we present the Arm POINTNAV Dataset (APND). This consists of 30 kitchen scenes in AI2-THOR that include more than 150 object categories (69 interactable object categories) with a variety of shapes, sizes and textures. We use 12 pickupable categories as our target objects. As shown in Figure 3.8, we use 20 scenes in the training set and the remaining is evenly split into Val and Test. We train with 6 object categories and use the remaining to test our model in a Novel-Obj setting.



Figure 3.9: **Dataset Samples.** The initial location of the object can pose a variety of challenges. In (a) the tomato is occluded by the bowl, therefore the agent needs to remove the bowl to reach the tomato. In (b) the lettuce is on the shelf, which requires the agent to move the arm carefully such that it does not collide with the shelf or the vase. In (c) The goal object is inside another object and in (d) the goal object is inside a receptacle, therefore it requires interacting with another entity (opening microwave's door) before reaching for the object. The latter case is outside the scope of this paper.

Metrics. We report the following metrics:

• Success rate without disturbance **(SRwD)** – Fraction of successful episodes in which the arm (or the agent) does not collide with/move other objects in the scene.

• Success rate **(SR)** – Similar to SRwD, but less strict since it does not penalize collisions and movements of objects.

• Pick up success rate **(PuSR)** – Fraction of episodes where the agent successfully picks up the

object.

• Episode Length **(Len)** – Episode length for both success and failure episodes.

• Successful episode Length **(SuLen)** – Episode length for successful episodes.

• Pick up successful episode length **(PuLen)** – Episode length for episodes with successful pickups.

APND offers significant new challenges. The agent must learn to navigate not only itself but also its arm relative to its body. Also, as the agent navigates in the environment, it should avoid colliding with other objects – which brings new complexities given the addition of the arm and potentially carrying an object in its gripper. Further, reaching to pick up objects involves free-space estimation and obstacle avoidance – which becomes challenging when the source or target locations are behind the occluders. Moreover, it needs to choose the perfect time to attempt pickup as well as ending the episode. Finally, these occluders themselves may need to be manipulated in order to complete the task. The agent should overcome these challenges while its view is frequently obstructed by the arm and/or the object being carried. Figure 3.9 illustrates a few of the challenges involved with picking up the object from its source location.




Figure 3.10: **Statistics of the dataset.** This plot presents the distribution of the initial distance of the object from the target location in meters. We mark the step size for the agent and the arm movements, and the average width of the rooms for reference.

Figure 3.10 shows the distribution of the distances of the target location of the object from its

initial state. For comparison, we show the step size for agent navigation and arm navigation as well. Note that the initial distance of the agent from the object is not taken into account.

3.2.5 Model

ARMPOINTNAV requires agents to learn to navigate themselves along the 2D floor while also learning to navigate their arm and objects within the 3D space around them. Past works for visual object manipulation tend to use modular designs to solve this problem [133; 170; 58] – for instance, employing object detection models, instance segmentation models, point cloud estimators, etc. and then feeding these outputs into a planner. In contrast, recent developments in the Embodied AI domain [227; 165] have demonstrated the benefits of using end-to-end learning-based approaches. In this work, we investigate end-to-end learning approaches for our task. See Sec. 3.2.6 for results obtained by a single end-to-end model in comparison to a disjoint approach.

Our approach builds upon the model and learning methods used in [193] for the task of POINTNAV. ManipulaTHOR provides the agent with access to a variety of sensors including egocentric RGB and Depth sensors, GPS and Compass coordinates of the arm and target locations in the scene, ground truth instance segmentation maps as well as the kinematics of the arm. In this work, we investigate using the Depth and RGB sensors as well as the GPS and Compass coordinates, but leave other sensing modalities to future work.

Our agent at each time step uses as inputs, its egocentric frame I_t, the current relative distance of the arm (the end-effector location) to the object's location d^o_{arm} and the current relative distance of the arm to the object's goal state d^{goal}_o. These observations are encoded into visual and location embeddings respectively and then fed into a controller to produce a distribution over possible actions, i.e. its policy. The discretized action space of the agent includes: moving forward, rotating the agent (left and right), pickup up the object, issuing done action, moving the arm in the space in front of the agent (ahead, backward, right, left, up, down), rotating the arm (in terms of Euler angles) and increasing or decreasing the height of the arm. Discretization of the action space is discussed




Figure 3.11: **Architecture**. Our network uses the Depth (c=1), RGB (c=3) or RGBD (c=4) observations and the agent's arm relative location to the object to estimate the movements needed to pickup the target object and take it to the goal state while avoiding the unwanted collisions.

in details in Sec. 3.2.6. An action is sampled from this policy and fed into the ManipulaTHOR simulator which generates the next state and corresponding observations. An episode terminates when the object reaches its goal state or when the agent runs out of time (the episode reaches its maximum length).

Figure 3.11 provides an overview of the model architecture. Visual embeddings are obtained using 3 convolution layers followed by a fully-connected layer with non-linearity in between to produce a 512 dimensional vector. The relative coordinates (arm $\rightarrow$ object and arm $\rightarrow$ goal) are embedded by 2 fully connected layers with ReLU non-linearity to a feature vector of size 512, which is then concatenated with the image features. The controller consisting of a GRU [31] with a hidden size of 512 uses this resulting embedding as input to produce a policy (i.e. distribution over actions) and a value (i.e. an estimate of future rewards).

The network parameters are optimized using DD-PPO [193] with both a terminal reward and intermediate rewards used to shape the reward space. More specifically, the reward at each time step t is:

$$r_t = R_{success}.\mathbb{I}_{success} + R_{pickup}.\mathbb{I}_{pickup} + \Delta^{o}_{arm} + \Delta^{goal}_{o}, \tag{3.7}$$



Figure 3.12: **Qualitative Results.** Our qualitative results illustrate our network's ability to generalize to picking up objects in novel environments and navigating the agent with the object in hand to the desired location. For example, row (c) shows a scenario from a third-perspective in which the agent needs to navigate in the kitchen while avoiding the collision with other objects (toaster, tomato and sink in this case).

where $R_{success} = 10$, $R_{pickup} = 5$, $\mathbb{I}_{success}, \mathbb{I}_{pickup}$ are the indicators of the success of the task and success of the object pickup, respectively, and Δ^{o}_{arm} and Δ^{goal}_{o} are the differences in the distance of the arm to object (d^{o}_{arm}), and the distance of the object to the goal (d^{goal}_{o}) in comparison to the previous timestep. This method of reward shaping provides us the ability to balance the importance of the different phases of the task – pickup vs place.

3.2.6 Experiments

We now present results for our ARMPOINTNAV using the APND dataset and quantify its ability to generalize to new scenes as well as new objects within these scenes. We also provide comparisons of our end-to-end approach to a multi-stage model. Finally, we ablate the importance of the RGB and Depth sensors in the presence of the GPS and Compass coordinates.

Experimental Setup. We use the AllenAct [192] framework to implement and train our models. Our agent uses an action space with 13 discrete actions: 1) moving the agent forward by $20cm$, 2-3) rotating the agent to the right/left for 45 degrees, 4-9) changing the relative location of the wrist by $5cm$ w.r.t. agent ($\pm x, \pm y, \pm z$), and 10-11) increasing or decreasing the height of the arm by $7cm$ (refer to Figure 3.7 for illustrations of the possible arm movements), 12) abstract grasp (which can be either successful or unsuccessful), 13) issuing a *Done* action indicating the end of an episode. We use DD-PPO [193] as our optimization algorithm. We train each model for 20M frames and maximum episode length of 200.

As specified in Section 3.2.4 we use 20 scenes for training, 5 for validation and 5 for test. Unless otherwise specified, we train our networks on the training scenes with 6 objects and evaluate the learned policy on the val and test scenes using the 6 seen and 6 novel object categories. Each object category includes instances of different shape and appearance.

Quantitative results. Table 3.3 reports results for our model using 6 metrics – Episode Success w/o Disturbance (SRwD), PickUp Success (PuSR), Episode Success (SR), Ep-Len for PickUp (PuLen), Ep-Len for Success (SuLen) and Episode Length (Len). The proposed model performs reasonably well and achieves 39.4% SRwD (68.7% when allowing disturbance) for objects it has interacted with at training time. It obtains a significantly higher PuSR of 89.9% indicating that navigating towards the initial location of the object and picking it up is easier than navigating the object through the scene. Interestingly, the model also generalizes moderately well to novel objects (row 2 – Test-NovelObj). The SRwD metric degrades in the challenging zero shot setting compared to the seen object scenario. These results are promising and a stepping stone towards learning a generalizable object manipulation model. We also provide results for SeenScene-NovelObj – where the agent is tested within seen environments but provided with novel objects. It is interesting to note that the performance is similar to Test-NovelObj, once again showing the challenges of moving to new object categories. Moving and manipulating objects requires an understanding of the object geometry (to be able to avoid collisions), and therefore generalizing to unseen objects is

	(SRwD)	(PuSR)	(SR)	(PuLen)	(SuLen)	(Len)
Test-SeenObj	39.4	89.9	68.7	43.6	78.1	114.0
Test-NovelObj	32.7	84.3	62.1	48.1	82.4	122.0
SeenScenes-NovelObj	32.2	90.6	74.6	44.6	80.7	104.0

Table 3.3: **Quantitative results.** The performance of our network on different data splits. Our experiments show that our trained agent can generalize to novel scenes and objects.




Figure 3.13: **Comparison of SRwD rates based on the initial distance to goal.** The plot shows that our network's generalizability to novel scenes is superior to generalization to unseen objects.

challenging.

It is interesting to analyze the performance of this model and see how the performance of our method changes based on the closeness of the target location to the initial state. As expected, the SRwD drops as we increase the distance to the goal, since it becomes harder to navigate to the target location. However, our model is relatively robust to longer distances (Figure 3.13). But once again, we see that the SRwD is higher for seen objects than novel objects.

Our qualitative results in Figure 3.12 illustrate a few examples of our agent's behavior on Test-SeenObj. In the second row the agent must move a moderately sized object (lettuce) while in the first row it must move a smaller object (apple). The second row shows an example where the target location is on a table that has several other objects on it, necessitating careful movements of

the arm while placing the object down. The third row shows the episode in row (b) from a third camera view. Note that this view is purely for illustrative purposes and not available to the agent.

Comparison to a Disjoint Model. In this work we use a single end-to-end model for the entire task which includes navigating the arm to the object to pickup, and navigating the agent, arm and the object to the goal location. We posit that navigating the arm to pick up an object shares a lot of underlying physical understanding with moving the object within the 3D environment and it would help the performance to share weights among them. To evaluate this hypothesis, we also train a disjoint model – which consists of two separate visual encoders and controllers, one for each sub-task of picking up the object and moving towards the goal (weights are not shared). At training time, the first sub-task model starts receiving gradients at the beginning of training, but the second sub-task model only receives gradients once the training episodes proceed beyond successful pickups. The results in Table 3.4 show that having a disjoint approach improves PuSR and PuLen since the first model is only required to perform the simpler task of picking up the object. However, this model fails to learn to navigate the object to the goal since the model only receives gradients for a fraction of the training episodes (the ones that completed a pickup). Since it shares no parameters between the two phases, it cannot leverage skills and abilities learned across the two phases. While the number of parameters has doubled for the disjoint model, the training has also become less efficient. We acknowledge that the success rate might increase if the model is trained for longer[1]. This ablation justifies our design choice for combining the two subtasks of *pickup* and *move-to-target*.

No-Vision Agent. Visual information is an important aspect of ARMPOINTNAV, in spite of having access to GPS and compass sensors. To illustrate the importance of the visual information in our training, we trained a model with no visual modalities but still with other sensory information such as the arm relative locations. In Table 3.4, we show that our agent outperforms the non-visual baseline by more than 2x, improving SRwD from 10.3 to 39.4.

[1]Training for 40M frames (2x normal training) slightly increased the success rate on training set but no increase on test set

	Sensors	SRwD	PuSR	SR	PuLen	SuLen	Len
No-Vision	G	10.3	66.8	18.7	38.1	65.6	64.9
Disjoint Model	GD	0.0	**91.6**	0.0	40.8	-	5.05
RGB	GR	21.2	68.3	37.7	56.2	91.1	53.0
RGBD	GRD	37.1	86.8	62.8	45.1	82.2	123.0
Depth	GD	**39.4**	89.9	**68.7**	43.6	78.1	114.0

Table 3.4: **Ablation Studies.** We study ablations of our network using different combinations of sensors as well as architecture design. Input sensors that are used by these networks are a subset of GPS (G), Depth (D) and RGB (R) sensors.

RGB and Depth modalities. ManipulaTHOR provides a host of sensor modalities to train and evaluate agents. Our experiments thus far have only leveraged ego-centric Depth observations. In Table 3.4, we show results for agents that are trained using RGB and RGBD frames as well. For our RGB experiment, we use the same architecture as Depth setup and for the RGBD input, we concatenate image features with depth features and use the combined feature as the input to the GRU. The rest of the setup is similar to our baseline method. We observe that the depth only model outperforms the RGB model. A similar trend has been shown before for the PointNav task [161]. More complex networks and/or training paradigms might help improve metrics, and we leave this direction for future work.

3.2.7 Conclusion

We propose ManipulaTHOR a framework for visual object manipulation that builds upon the AI2-THOR environment. ManipulaTHOR provides a host of diverse and visually complex scenes with several different object categories to manipulate. We hope that this new framework encourages the Embodied AI community towards tackling exciting problems dealing with object manipulation. Using ManipulaTHOR, we study the problem of ARMPOINTNAV, where the goal is to pick up an

object and move it to a target location. Our experimental evaluations show that the state-of-the-art models that perform well on embodied tasks such as navigation are not as effective for object manipulation, indicating there is still a large room for improving models for this challenging task. Furthermore, in this paper we use GPS and visual sensors. Relaxing the usage of these sensors is an interesting task that is left for future work.

Chapter 4

Conclusion

In this thesis, we studied acquiring intelligence via interaction. We discussed two approaches for learning intelligence in the form of perception. First, in Sections 2.1, 2.2, we investigated learning perception by observing intelligent agents interact with their environment, trying to predict their movements and attention, and by doing so, we learned a rich visual representation.

In Section 2.3, we described a method for predicting physical forces applied to objects from a given video. We used the feedback from the environment to update the interaction to make up for the mistakes made along the way. Finally, we showed how this training paradigm helped with generalizing to unseen objects.

In Section 3, explored the outcome of using interaction to learn to interact. We discussed how to build a pipeline that allows us to continue the learning process during the inference time after the training is done. Later, we introduced ManipulaTHOR, a simulation framework that enables interacting with visually rich physically realistic environments.

So far, we have been considering these approaches in isolation. The question is: Can we combine them to achieve bigger goals?

4.1 Future Research Direction

The first immediate goal is to have an agent observing interaction and replicating it in the real world. Since running experiments on real robots can be costly and time-consuming, we can start by imitating the interaction in simulation.

As we perform the task, we might encounter novel unseen objects that we have never observed in the videos. Moreover, we want our agents to be able to generalize to novel environments. We can use the outcome of the interactions (or the feedback from the environment) to learn to adapt to new environments and new objects with new physical properties. For instance, if the agent has never interacted with a glass vase, it might apply a significant force and break it during the interaction. Using the feedback and adapting to new environments, the agent can update its behavior to be more delicate and avoid making the same mistake (i.e., breaking the vase).

We can further extend this adaptation to generalize to real-world experiments. We acknowledge that sim2real has been a challenging problem for the community. However, by having realistic simulated environments and adaptation techniques, we hope to build upon the previous works and progress on this challenge.

Ultimately, there might be some missing information in the observed video. Training agents that can find these missing spots and ask for more instructions can be considered another direction for further research.

Bibliography

[1] https://www.kinovarobotics.com.

[2] Pieter Abbeel and Andrew Y. Ng. Apprenticeship learning via inverse reinforcement learning. In *ICML*, 2004.

[3] Karen Adolph and Scott Robinson. *Motor Development*, volume 2, pages 113–157. John Wiley & Sons, 2015.

[4] Aishwarya Agrawal, Jiasen Lu, Stanislaw Antol, Margaret Mitchell, C. Lawrence Zitnick, Devi Parikh, and Dhruv Batra. Vqa: Visual question answering. *IJCV*, 2015.

[5] Pulkit Agrawal, João Carreira, and Jitendra Malik. Learning to see by moving. In *ICCV*, 2015.

[6] Pulkit Agrawal, Joao Carreira, and Jitendra Malik. Learning to see by moving. In *ICCV*, 2015.

[7] Pulkit Agrawal, Ashvin Nair, Pieter Abbeel, Jitendra Malik, and Sergey Levine. Learning to poke by poking: Experiential learning of intuitive physics. In *NIPS*, 2016.

[8] Shuichi Akizuki and Yoshimitsu Aoki. Tactile logging for understanding plausible tool use based on human demonstration. In *British Machine Vision Conference (BMVC)*, 2018.

[9] Peter Anderson, Angel Chang, Devendra Singh Chaplot, Alexey Dosovitskiy, Saurabh Gupta, Vladlen Koltun, Jana Kosecka, Jitendra Malik, Roozbeh Mottaghi, Manolis Savva, and Amir R. Zamir. On evaluation of embodied navigation agents. *arXiv*, 2018.

[10] Peter Anderson, Qi Wu, Damien Teney, Jake Bruce, Mark Johnson, Niko Sünderhauf, Ian Reid, Stephen Gould, and Anton van den Hengel. Vision-and-language navigation: Interpreting visually-grounded navigation instructions in real environments. In *CVPR*, 2018.

[11] Philip Bachman, R Devon Hjelm, and William Buchwalter. Learning representations by maximizing mutual information across views. In *NeurIPS*, 2019.

[12] Chris L. Baker, Rebecca Saxe, and Joshua B. Tenenbaum. Action understanding as inverse planning. *Cognition*, 2009.

[13] Albert Bandura. *Social learning theory*. Prentice-hall, 1977.

[14] Dhruv Batra, Angel X Chang, Sonia Chernova, Andrew J Davison, Jia Deng, Vladlen Koltun, Sergey Levine, Jitendra Malik, Igor Mordatch, Roozbeh Mottaghi, Manolis Savva, and Hao Su. Rearrangement: A challenge for embodied ai. *arXiv*, 2020.

[15] Antonio Bicchi and Vijay Kumar. Robotic grasping and contact: A review. In *ICRA*, 2000.

[16] Michael Blösch, Stephan Weiss, Davide Scaramuzza, and Roland Siegwart. Vision based mav navigation in unknown and unstructured environments. In *ICRA*, 2010.

[17] Jeannette Bohg, Antonio Morales, Tamim Asfour, and Danica Kragic. Data-driven grasp synthesis—a survey. *IEEE Transactions on Robotics*, 2013.

[18] Konstantinos Bousmalis, Alex Irpan, Paul Wohlhart, Yunfei Bai, Matthew Kelcey, Mrinal Kalakrishnan, Laura Downs, Julian Ibarz, Peter Pastor, Kurt Konolige, Sergey Levine, and Vincent Vanhoucke. Using simulation and domain adaptation to improve efficiency of deep robotic grasping. In *ICRA*, 2018.

[19] Samarth Brahmbhatt, Cusuh Ham, Charles C Kemp, and James Hays. Contactdb: Analyzing and predicting grasp contact via thermal imaging. In *Conference on Computer Vision and Pattern Recognition*, pages 8709–8719, 2019.

[20] Samarth Brahmbhatt and James Hays. Deepnav: Learning to navigate large cities. In *CVPR*, 2017.

[21] Berk Calli, Arjun Singh, Aaron Walsman, Siddhartha Srinivasa, Pieter Abbeel, and Aaron M Dollar. The ycb object and model set: Towards common benchmarks for manipulation research. In *International Conference on Advanced Robotics (ICAR)*, pages 510–517. IEEE, 2015.

[22] Devendra Singh Chaplot, Saurabh Gupta, Dhiraj Gandhi, Abhinav Gupta, and Ruslan Salakhutdinov. Learning to explore using active neural mapping. In *ICLR*, 2020.

[23] Devendra Singh Chaplot, Kanthashree Mysore Sathyendra, Rama Kumar Pasumarthi, Dheeraj Rajagopal, and Ruslan Salakhutdinov. Gated-attention architectures for task-oriented language grounding. In *AAAI*, 2018.

[24] Yevgen Chebotar, Ankur Handa, Viktor Makoviychuk, Miles Macklin, Jan Issac, Nathan Ratliff, and Dieter Fox. Closing the sim-to-real loop: Adapting simulation randomization with real world

experience. In *International Conference on Robotics and Automation (ICRA)*, pages 8973–8979. IEEE, 2019.

[25] Boyuan Chen, Shuran Song, Hod Lipson, and Carl Vondrick. Visual hide and seek. *arXiv*, 2019.

[26] Chenyi Chen, Ary Seff, Alain L. Kornhauser, and Jianxiong Xiao. Deepdriving: Learning affordance for direct perception in autonomous driving. In *ICCV*, 2015.

[27] Liang-Chieh Chen, George Papandreou, Iasonas Kokkinos, Kevin Murphy, and Alan L. Yuille. Deeplab: Semantic image segmentation with deep convolutional nets, atrous convolution, and fully connected crfs. *TPAMI*, 2017.

[28] Ting Chen, Simon Kornblith, Mohammad Norouzi, and Geoffrey Hinton. A simple framework for contrastive learning of visual representations. *arXiv*, 2020.

[29] Ting Chen, Simon Kornblith, Kevin Swersky, Mohammad Norouzi, and Geoffrey Hinton. Big self-supervised models are strong semi-supervised learners. *arXiv preprint arXiv:2006.10029*, 2020.

[30] Xinlei Chen, Haoqi Fan, Ross Girshick, and Kaiming He. Improved baselines with momentum contrastive learning. *arXiv*, 2020.

[31] Kyunghyun Cho, Bart Van Merriënboer, Caglar Gulcehre, Dzmitry Bahdanau, Fethi Bougares, Holger Schwenk, and Yoshua Bengio. Learning phrase representations using rnn encoder-decoder for statistical machine translation. In *EMNLP*, 2014.

[32] Ignasi Clavera, Anusha Nagabandi, Ronald S Fearing, Pieter Abbeel, Sergey Levine, and Chelsea Finn. Learning to adapt: Meta-learning for model-based control. *arXiv*, 2018.

[33] Erwin Coumans and Yunfei Bai. Pybullet, a python module for physics simulation for games, robotics and machine learning. `http://pybullet.org`, 2016–2019.

[34] Mark Cummins and Paul Newman. Probabilistic appearance based navigation and loop closing. In *ICRA*, 2007.

[35] Dima Damen, Hazel Doughty, Giovanni Maria Farinella, Sanja Fidler, Antonino Furnari, Evangelos Kazakos, Davide Moltisanti, Jonathan Munro, Toby Perrett, Will Price, and Michael Wray. Scaling egocentric vision: The epic-kitchens dataset. In *ECCV*, 2018.

[36] Filipe de Avila Belbute-Peres, Kevin Smith, Kelsey Allen, Josh Tenenbaum, and J Zico Kolter. End-to-end differentiable physics for learning and control. In *Advances in Neural Information Processing*

Systems, pages 7178–7189, 2018.

[37] Jia Deng, Wei Dong, Richard Socher, Li-Jia Li, Kai Li, and Fei-Fei Li. Imagenet: A large-scale hierarchical image database. In *CVPR*, 2009.

[38] Jia Deng, Wei Dong, Richard Socher, Li-Jia Li, Kai Li, and Li Fei-Fei. Imagenet: A large-scale hierarchical image database. In *CVPR*, 2009.

[39] Jia Deng, Wei Dong, Richard Socher, Li-Jia Li, Kai Li, and Fei-Fei Li. Imagenet: A large-scale hierarchical image database. In *CVPR*, 2009.

[40] R Devon Hjelm and Philip Bachman. Representation learning with video deep infomax. *arXiv*, 2020.

[41] Carl Doersch, Abhinav Gupta, and Alexei A. Efros. Unsupervised visual representation learning by context prediction. In *ICCV*, 2015.

[42] Carl Doersch, Abhinav Gupta, and Alexei A. Efros. Unsupervised visual representation learning by context prediction. In *ICCV*, 2015.

[43] Jeff Donahue, Philipp Krähenbühl, and Trevor Darrell. Adversarial feature learning. In *ICLR*, 2017.

[44] Andreas Doumanoglou, Rigas Kouskouridas, Sotiris Malassiotis, and Tae-Kyun Kim. Recovering 6d object pose and predicting next-best-view in the crowd. In *Conference on Computer Vision and Pattern Recognition*, pages 3583–3592, 2016.

[45] Yan Duan, John Schulman, Xi Chen, Peter L. Bartlett, Ilya Sutskever, and Pieter Abbeel. rl^2: Fast reinforcement learning via slow reinforcement learning. *arXiv*, 2016.

[46] Kiana Ehsani, Hessam Bagherinezhad, Joseph Redmon, Roozbeh Mottaghi, and Ali Farhadi. Who let the dogs out? modeling dog behavior from visual data. In *CVPR*, 2018.

[47] Kuan Fang, Yunfei Bai, Stefan Hinterstoisser, Silvio Savarese, and Mrinal Kalakrishnan. Multi-task domain adaptation for deep learning of instance grasping from simulation. In *ICRA*, 2018.

[48] Kuan Fang, Yuke Zhu, Animesh Garg, Andrey Kurenkov, Viraj Mehta, Li Fei-Fei, and Silvio Savarese. Learning task-oriented grasping for tool manipulation from simulated self-supervision. *The International Journal of Robotics Research*, 2020.

[49] Kuan Fang, Yuke Zhu, Animesh Garg, Silvio Savarese, and Li Fei-Fei. Dynamics learning with cascaded variational inference for multi-step manipulation. In *CoRL*, 2020.

[50] Alireza Fathi, Ali Farhadi, and James M. Rehg. Understanding egocentric activities. In *ICCV*, 2011.

[51] Alireza Fathi, Yin Li, and James M Rehg. Learning to recognize daily actions using gaze. In *ECCV*, 2012.

[52] Ronald Fearing. Implementing a force strategy for object re-orientation. In *ICRA*, 1986.

[53] Chelsea Finn, Pieter Abbeel, and Sergey Levine. Model-agnostic meta-learning for fast adaptation of deep networks. In *ICML*, 2017.

[54] Katerina Fragkiadaki, Pulkit Agrawal, Sergey Levine, and Jitendra Malik. Predictive visual models of physics for playing billiards. In *International Conference on Learning Representations*, 2016.

[55] Katerina Fragkiadaki, Sergey Levine, Panna Felsen, and Jitendra Malik. Recurrent network models for human dynamics. In *ICCV*, 2015.

[56] Chuang Gan, Jeremy Schwartz, Seth Alter, Martin Schrimpf, James Traer, Julian De Freitas, Jonas Kubilius, Abhishek Bhandwaldar, Nick Haber, Megumi Sano, et al. Threedworld: A platform for interactive multi-modal physical simulation. *arXiv*, 2020.

[57] Guillermo Garcia-Hernando, Shanxin Yuan, Seungryul Baek, and Tae-Kyun Kim. First-person hand action benchmark with rgb-d videos and 3d hand pose annotations. In *Conference on Computer Vision and Pattern Recognition*, pages 409–419, 2018.

[58] Caelan Reed Garrett, Tomás Lozano-Pérez, and Leslie Pack Kaelbling. Pddlstream: Integrating symbolic planners and blackbox samplers via optimistic adaptive planning. In *Proceedings of the International Conference on Automated Planning and Scheduling*, 2020.

[59] Caelan Reed Garrett, Chris Paxton, Tomás Lozano-Pérez, Leslie Pack Kaelbling, and Dieter Fox. Online replanning in belief space for partially observable task and motion problems. In *ICRA*, 2020.

[60] Spyros Gidaris, Praveer Singh, and Nikos Komodakis. Unsupervised representation learning by predicting image rotations. In *ICLR*, 2018.

[61] Ross Girshick, Jeff Donahue, Trevor Darrell, and Jitendra Malik. Rich feature hierarchies for accurate object detection and semantic segmentation. In *CVPR*, 2014.

[62] Georgia Gkioxari, Ross Girshick, Piotr Dollár, and Kaiming He. Detecting and recognizing human-object interactions. In *Conference on Computer Vision and Pattern Recognition*, pages 8359–8367, 2018.

[63] Haifeng Gong, Jack Sim, Maxim Likhachev, and Jianbo Shi. Multi-hypothesis motion planning for

visual object tracking. In *ICCV*, 2011.

[64] Daniel Gordon, Kiana Ehsani, Dieter Fox, and Ali Farhadi. Watching the world go by: Representation learning from unlabeled videos. *arXiv*, 2020.

[65] Priya Goyal, Dhruv Mahajan, Abhinav Gupta, and Ishan Misra. Scaling and benchmarking self-supervised visual representation learning. In *ICCV*, 2019.

[66] Abhishek Gupta, Russell Mendonca, Yuxuan Liu, Pieter Abbeel, and Sergey Levine. Meta-reinforcement learning of structured exploration strategies. *arXiv*, 2018.

[67] Abhinav Gupta, Adithyavairavan Murali, Dhiraj Prakashchand Gandhi, and Lerrel Pinto. Robot learning in homes: Improving generalization and reducing dataset bias. In *NeurIPS*, 2018.

[68] Saurabh Gupta, Pablo Arbeláez, Ross Girshick, and Jitendra Malik. Aligning 3d models to rgb-d images of cluttered scenes. In *Conference on Computer Vision and Pattern Recognition*, pages 4731–4740, 2015.

[69] Saurabh Gupta, James Davidson, Sergey Levine, Rahul Sukthankar, and Jitendra Malik. Cognitive mapping and planning for visual navigation. In *CVPR*, 2017.

[70] Saurabh Gupta and Jitendra Malik. Visual semantic role labeling. *arXiv preprint arXiv:1505.04474*, 2015.

[71] Michael Gutmann and Aapo Hyvärinen. Noise-contrastive estimation: A new estimation principle for unnormalized statistical models. In *AISTATS*, 2010.

[72] T. Haarnoja, Vitchyr H. Pong, Aurick Zhou, Murtaza Dalal, P. Abbeel, and S. Levine. Composable deep reinforcement learning for robotic manipulation. In *ICRA*, 2018.

[73] Raia Hadsell, Sumit Chopra, and Yann LeCun. Dimensionality reduction by learning an invariant mapping. In *CVPR*, 2006.

[74] Henning Hamer, Juergen Gall, Thibaut Weise, and Luc Van Gool. An object-dependent hand pose prior from sparse training data. In *Computer Society Conference on Computer Vision and Pattern Recognition*, pages 671–678. IEEE, 2010.

[75] Mohamed Hassan, Vasileios Choutas, Dimitrios Tzionas, and Michael J. Black. Resolving 3d human pose ambiguities with 3d scene constraints. In *ICCV*, 2019.

[76] Kaiming He, Haoqi Fan, Yuxin Wu, Saining Xie, and Ross Girshick. Momentum contrast for

unsupervised visual representation learning. In *CVPR*, 2020.

[77] Kaiming He, Georgia Gkioxari, Piotr Dollár, and Ross B. Girshick. Mask r-cnn. *IEEE Transactions on Pattern Analysis and Machine Intelligence*, 42:386–397, 2020.

[78] Kaiming He, Xiangyu Zhang, Shaoqing Ren, and Jian Sun. Deep residual learning for image recognition. In *CVPR*, 2016.

[79] Kaiming He, Xiangyu Zhang, Shaoqing Ren, and Jian Sun. Deep residual learning for image recognition. In *CVPR*, 2016.

[80] Olivier J Hénaff, Aravind Srinivas, Jeffrey De Fauw, Ali Razavi, Carl Doersch, SM Eslami, and Aaron van den Oord. Data-efficient image recognition with contrastive predictive coding. *arXiv preprint arXiv:1905.09272*, 2019.

[81] Karl Moritz Hermann, Felix Hill, Simon Green, Fumin Wang, Ryan Faulkner, Hubert Soyer, David Szepesvari, Wojciech Marian Czarnecki, Max Jaderberg, Denis Teplyashin, Marcus Wainwright, Chris Apps, Demis Hassabis, and Phil Blunsom. Grounded language learning in a simulated 3d world. *arXiv*, 2017.

[82] Geoffrey Hinton, Oriol Vinyals, and Jeff Dean. Distilling the knowledge in a neural network. *arXiv*, 2015.

[83] Minh Hoai and Fernando De la Torre. Max-margin early event detectors. In *CVPR*, 2012.

[84] Rein Houthooft, Richard Y. Chen, Phillip Isola, Bradly C. Stadie, Filip Wolski, Jonathan Ho, and Pieter Abbeel. Evolved policy gradients. *arXiv*, 2018.

[85] Andrew G. Howard, Menglong Zhu, Bo Chen, Dmitry Kalenichenko, Weijun Wang, Tobias Weyand, M. Andreetto, and Hartwig Adam. Mobilenets: Efficient convolutional neural networks for mobile vision applications. *ArXiv*, abs/1704.04861, 2017.

[86] Yuanming Hu, Jiancheng Liu, Andrew Spielberg, Joshua B Tenenbaum, William T Freeman, Jiajun Wu, Daniela Rus, and Wojciech Matusik. Chainqueen: A real-time differentiable physical simulator for soft robotics. In *International Conference on Robotics and Automation (ICRA)*, pages 6265–6271. IEEE, 2019.

[87] De-An Huang, Minghuang Ma, Wei-Chiu Ma, and Kris M Kitani. How do we use our hands? discovering a diverse set of common grasps. In *Conference on Computer Vision and Pattern Recognition*,

pages 666–675, 2015.

[88] Drew A. Hudson and Christopher D. Manning. Gqa: A new dataset for real-world visual reasoning and compositional question answering. In *CVPR*, 2019.

[89] Wonjun Hwang and Soo-Chul Lim. Inferring interaction force from visual information without using physical force sensors. *Sensors*, 17(11):2455, 2017.

[90] Catalin Ionescu, Dragos Papava, V. Olaru, and C. Sminchisescu. Human3.6m: Large scale datasets and predictive methods for 3d human sensing in natural environments. *TPAMI*, 2014.

[91] Stephen James, Zicong Ma, David Rovick Arrojo, and Andrew J Davison. Rlbench: The robot learning benchmark & learning environment. *IEEE Robotics and Automation Letters*, 2020.

[92] Dinesh Jayaraman and Kristen Grauman. Learning image representations tied to ego-motion. In *ICCV*, 2015.

[93] Dinesh Jayaraman and Kristen Grauman. Learning image representations tied to ego-motion. In *ICCV*, 2015.

[94] Hao Jiang and Kristen Grauman. Seeing invisible poses: Estimating 3d body pose from egocentric video. In *CVPR*, 2017.

[95] Gregory Kahn, Adam Villaflor, Bosen Ding, Pieter Abbeel, and Sergey Levine. Self-supervised deep reinforcement learning with generalized computation graphs for robot navigation. In *ICRA*, 2018.

[96] Wadim Kehl, Fausto Milletari, Federico Tombari, Slobodan Ilic, and Nassir Navab. Deep learning of local rgb-d patches for 3d object detection and 6d pose estimation. In *European Conference on Computer Vision*, pages 205–220. Springer, 2016.

[97] Kiyosumi Kidono, Jun Miura, and Yoshiaki Shirai. Autonomous visual navigation of a mobile robot using a human-guided experience. *Robotics and Autonomous Systems*, 2002.

[98] Diederik P. Kingma and Jimmy Ba. Adam: A method for stochastic optimization. In *ICLR*, 2015.

[99] Kris M. Kitani, Brian D. Ziebart, James Andrew Bagnell, and Martial Hebert. Activity forecasting. In *ECCV*, 2012.

[100] Eric Kolve, Roozbeh Mottaghi, Daniel Gordon, Yuke Zhu, Abhinav Gupta, and Ali Farhadi. AI2-THOR: An Interactive 3D Environment for Visual AI. *arXiv*, 2017.

[101] Eric Kolve, Roozbeh Mottaghi, Winson Han, Eli VanderBilt, Luca Weihs, Alvaro Herrasti, Daniel

Gordon, Yuke Zhu, Abhinav Gupta, and Ali Farhadi. Ai2-thor: An interactive 3d environment for visual ai. *arXiv*, 2017.

[102] Kurt Konolige, Motilal Agrawal, Robert C. Bolles, Cregg Cowan, Martin A. Fischler, and Brian P. Gerkey. Outdoor mapping and navigation using stereo vision. In *ISER*, 2006.

[103] Julian Francisco Pieter Kooij, Nicolas Schneider, Fabian Flohr, and Dariu M. Gavrila. Context-based pedestrian path prediction. In *ECCV*, 2014.

[104] Hema Swetha Koppula and Ashutosh Saxena. Anticipating human activities using object affordances for reactive robotic response. In *RSS*, 2013.

[105] Ivan Krasin, Tom Duerig, Neil Alldrin, Vittorio Ferrari, Sami Abu-El-Haija, Alina Kuznetsova, Hassan Rom, Jasper Uijlings, Stefan Popov, Andreas Veit, Serge Belongie, Victor Gomes, Abhinav Gupta, Chen Sun, Gal Chechik, David Cai, Zheyun Feng, Dhyanesh Narayanan, and Kevin Murphy. Openimages: A public dataset for large-scale multi-label and multi-class image classification. *Dataset available from https://github.com/openimages*, 2017.

[106] T. Lan, T.-C. Chen, and S. Savarese. A hierarchical representation for future action prediction. In *ECCV*, 2014.

[107] Yong Jae Lee, Joydeep Ghosh, and Kristen Grauman. Discovering important people and objects for egocentric video summarization. In *CVPR*, 2012.

[108] Sergey Levine, Peter Pastor, Alex Krizhevsky, Julian Ibarz, and Deirdre Quillen. Learning hand-eye coordination for robotic grasping with deep learning and large-scale data collection. *The International Journal of Robotics Research*, 2018.

[109] Cheng Li and Kris M. Kitani. Pixel-level hand detection in ego-centric videos. In *CVPR*, 2013.

[110] Chengshu Li, Fei Xia, Roberto Martín-Martín, and Silvio Savarese. Hrl4in: Hierarchical reinforcement learning for interactive navigation with mobile manipulators. *arXiv*, 2019.

[111] Da Li, Yongxin Yang, Yi-Zhe Song, and Timothy M. Hospedales. Learning to generalize: Meta-learning for domain generalization. In *AAAI*, 2018.

[112] Yi Li, Gu Wang, Xiangyang Ji, Yu Xiang, and Dieter Fox. Deepim: Deep iterative matching for 6d pose estimation. In *European Conference on Computer Vision (ECCV)*, pages 683–698, 2018.

[113] Zongmian Li, Jiri Sedlar, Justin Carpentier, Ivan Laptev, Nicolas Mansard, and Josef Sivic. Estimating

3d motion and forces of person-object interactions from monocular video. In *Conference on Computer Vision and Pattern Recognition*, pages 8640–8649, 2019.

[114] Tsung-Yi Lin, Priya Goyal, Ross B. Girshick, Kaiming He, and Piotr Dollár. Focal loss for dense object detection. *IEEE Transactions on Pattern Analysis and Machine Intelligence*, 42:318–327, 2020.

[115] Tao Liu, Yoshio Inoue, and Kyoko Shibata. Design of low-cost tactile force sensor for 3d force scan. In *Sensors*, pages 1513–1516. IEEE, 2008.

[116] Dhruv Mahajan, Ross Girshick, Vignesh Ramanathan, Kaiming He, Manohar Paluri, Yixuan Li, Ashwin Bharambe, and Laurens van der Maaten. Exploring the limits of weakly supervised pretraining. In *ECCV*, 2018.

[117] Ajay Mandlekar, Yuke Zhu, Animesh Garg, Jonathan Booher, Max Spero, Albert Tung, Julian Gao, John Emmons, Anchit Gupta, Emre Orbay, et al. Roboturk: A crowdsourcing platform for robotic skill learning through imitation. *arXiv*, 2018.

[118] Julieta Martinez, Michael J Black, and Javier Romero. On human motion prediction using recurrent neural networks. In *CVPR*, 2017.

[119] Larry H. Matthies and Steven A. Shafer. Error modeling in stereo navigation. *IEEE J. Robotics and Automation*, 1987.

[120] Iaroslav Melekhov, Juha Ylioinas, Juho Kannala, and Esa Rahtu. Relative camera pose estimation using convolutional neural networks. In *arXiv*, 2017.

[121] Piotr Mirowski, Razvan Pascanu, Fabio Viola, Hubert Soyer, Andrew J. Ballard, Andrea Banino, Misha Denil, Ross Goroshin, Laurent Sifre, Koray Kavukcuoglu, Dharshan Kumaran, and Raia Hadsell. Learning to navigate in complex environments. In *ICLR*, 2017.

[122] Nikhil Mishra, Mostafa Rohaninejad, Xi Chen, and Pieter Abbeel. A simple neural attentive meta-learner. In *ICLR*, 2018.

[123] Dipendra Kumar Misra, John Langford, and Yoav Artzi. Mapping instructions and visual observations to actions with reinforcement learning. In *EMNLP*, 2017.

[124] Ishan Misra and Laurens van der Maaten. Self-supervised learning of pretext-invariant representations. In *CVPR*, 2020.

[125] Volodymyr Mnih, Adrià Puigdomènech Badia, Mehdi Mirza, Alex Graves, Timothy P. Lillicrap,

Tim Harley, David Silver, and Koray Kavukcuoglu. Asynchronous methods for deep reinforcement learning. In *ICML*, 2016.

[126] Roozbeh Mottaghi, Hessam Bagherinezhad, Mohammad Rastegari, and Ali Farhadi. Newtonian image understanding: Unfolding the dynamics of objects in static images. In *CVPR*, 2016.

[127] Roozbeh Mottaghi, Hessam Bagherinezhad, Mohammad Rastegari, and Ali Farhadi. Newtonian scene understanding: Unfolding the dynamics of objects in static images. In *CVPR*, 2016.

[128] Roozbeh Mottaghi, Hannaneh Hajishirzi, and Ali Farhadi. A task-oriented approach for cost-sensitive recognition. In *CVPR*, 2016.

[129] Roozbeh Mottaghi, Hannaneh Hajishirzi, and Ali Farhadi. A task-oriented approach for cost-sensitive recognition. In *CVPR*, 2016.

[130] Roozbeh Mottaghi, Mohammad Rastegari, Abhinav Gupta, and Ali Farhadi. "what happens if..." learning to predict the effect of forces in images. In *ECCV*, 2016.

[131] Roozbeh Mottaghi, Mohammad Rastegari, Abhinav Gupta, and Ali Farhadi. "what happens if..." learning to predict the effect of forces in images. In *European Conference on Computer Vision*, pages 269–285. Springer, 2016.

[132] Arsalan Mousavian, Alexander Toshev, Marek Fiser, Jana Kosecka, and James Davidson. Visual representations for semantic target driven navigation. In *ECCV Workshop on Visual Learning and Embodied Agents in Simulation Environments*, 2018.

[133] Adithyavairavan Murali, Arsalan Mousavian, Clemens Eppner, Chris Paxton, and Dieter Fox. 6-dof grasping for target-driven object manipulation in clutter. In *ICRA*, 2020.

[134] Pushmeet Kohli Nathan Silberman, Derek Hoiem and Rob Fergus. Indoor segmentation and support inference from rgbd images. In *ECCV*, 2012.

[135] Mehdi Noroozi and Paolo Favaro. Unsupervised learning of visual representations by solving jigsaw puzzles. In *ECCV*, 2016.

[136] Mehdi Noroozi, Hamed Pirsiavash, and Paolo Favaro. Representation learning by learning to count. In *ICCV*, 2017.

[137] Aaron van den Oord, Yazhe Li, and Oriol Vinyals. Representation learning with contrastive predictive coding. *arXiv*, 2018.

[138] Andrew Owens, Phillip Isola, Josh H. McDermott, Antonio Torralba, Edward H. Adelson, and William T. Freeman. Visually indicated sounds. In *CVPR*, 2016.

[139] Hyun Soo Park, Jyh-Jing Hwang, Yedong Niu, and Jianbo Shi. Egocentric future localization. In *CVPR*, 2016.

[140] Deepak Pathak, Pulkit Agrawal, Alexei A. Efros, and Trevor Darrell. Curiosity-driven exploration by self-supervised prediction. In *ICML*, 2017.

[141] Deepak Pathak, Pulkit Agrawal, Alexei A. Efros, and Trevor Darrell. Curiosity-driven exploration by self-supervised prediction. In *ICML*, 2017.

[142] Deepak Pathak, Ross Girshick, Piotr Dollár, Trevor Darrell, and Bharath Hariharan. Learning features by watching objects move. In *CVPR*, 2017.

[143] Deepak Pathak, Philipp Krähenbühl, Jeff Donahue, Trevor Darrell, and Alexei Efros. Context encoders: Feature learning by inpainting. In *CVPR*, 2016.

[144] Deepak Pathak, Philipp Krähenbühl, Jeff Donahue, Trevor Darrell, and Alexei A. Efros. Context encoders: Feature learning by inpainting. In *CVPR*, 2016.

[145] M. Pei, Y. Jia, and S.-C. Zhu. Parsing video events with goal inference and intent prediction. In *ICCV*, 2011.

[146] Jeffrey Pennington, Richard Socher, and Christopher D. Manning. Glove: Global vectors for word representation. In *EMNLP*, 2014.

[147] Tu-Hoa Pham, Abderrahmane Kheddar, Ammar Qammaz, and Antonis A Argyros. Towards force sensing from vision: Observing hand-object interactions to infer manipulation forces. In *Conference on Computer Vision and Pattern Recognition*, pages 2810–2819, 2015.

[148] Tu-Hoa Pham, Nikolaos Kyriazis, Antonis A Argyros, and Abderrahmane Kheddar. Hand-object contact force estimation from markerless visual tracking. *Transactions on Pattern Analysis and Machine Intelligence*, 40(12):2883–2896, 2017.

[149] Silvia L. Pintea, Jan C. van Gemert, and Arnold W. M. Smeulders. Déjà vu: Motion prediction in static images. In *ECCV*, 2014.

[150] Lerrel Pinto, Dhiraj Gandhi, Yuanfeng Han, Yong-Lae Park, and Abhinav Gupta. The curious robot: Learning visual representations via physical interactions. In *ECCV*, 2016.

[151] Lerrel Pinto, Dhiraj Gandhi, Yuanfeng Han, Yong-Lae Park, and Abhinav Gupta. The curious robot: Learning visual representations via physical interactions. In *ECCV*, 2016.

[152] Hamed Pirsiavash and Deva Ramanan. Detecting activities of daily living in first-person camera views. In *CVPR*, 2012.

[153] Senthil Purushwalkam, Abhinav Gupta, Danny Kaufman, and Bryan Russell. Bounce and learn: Modeling scene dynamics with real-world bounces. In *International Conference on Learning Representations*, 2019.

[154] Marc'Aurelio Ranzato, Arthur Szlam, Joan Bruna, Michaël Mathieu, Ronan Collobert, and Sumit Chopra. Video (language) modeling: a baseline for generative models of natural videos. In *arXiv*, 2014.

[155] Shaoqing Ren, Kaiming He, Ross Girshick, and Jian Sun. Faster R-CNN: Towards real-time object detection with region proposal networks. In *NeurIPS*, 2015.

[156] Shaoqing Ren, Kaiming He, Ross B. Girshick, and J. Sun. Faster r-cnn: Towards real-time object detection with region proposal networks. *IEEE Transactions on Pattern Analysis and Machine Intelligence*, 39:1137–1149, 2015.

[157] N. Rhinehart and K. Kitani. First-person forecasting with online inverse reinforcement learning. In *ICCV*, 2017.

[158] M. S. Ryoo. Human activity prediction: Early recognition of ongoing activities from streaming videos. In *ICCV*, 2011.

[159] Caner Sahin and Tae-Kyun Kim. Category-level 6d object pose recovery in depth images. In *European Conference on Computer Vision (ECCV)*, 2018.

[160] Nikolay Savinov, Alexey Dosovitskiy, and Vladlen Koltun. Semi-parametric topological memory for navigation. In *ICLR*, 2018.

[161] Manolis Savva, Abhishek Kadian, Oleksandr Maksymets, Yili Zhao, Erik Wijmans, Bhavana Jain, Julian Straub, Jia Liu, Vladlen Koltun, Jitendra Malik, et al. Habitat: A platform for embodied ai research. In *ICCV*, 2019.

[162] Jürgen Schmidhuber, Jieyu Zhao, and Marco Wiering. Shifting inductive bias with success-story algorithm, adaptive levin search, and incremental self-improvement. *Machine Learning*, 1997.

[163] Evan Shelhamer, Jonathan Long, and Trevor Darrell. Fully convolutional networks for semantic segmentation. In *CVPR*, 2015.

[164] Bokui Shen, Fei Xia, Chengshu Li, Roberto Martín-Martín, Linxi Fan, Guanzhi Wang, Shyamal Buch, Claudia D'Arpino, Sanjana Srivastava, Lyne P Tchapmi, et al. igibson, a simulation environment for interactive tasks in large realisticscenes. *arXiv*, 2020.

[165] Mohit Shridhar, Jesse Thomason, Daniel Gordon, Yonatan Bisk, Winson Han, Roozbeh Mottaghi, Luke Zettlemoyer, and Dieter Fox. ALFRED: A Benchmark for Interpreting Grounded Instructions for Everyday Tasks. In *CVPR*, 2020.

[166] Gunnar A Sigurdsson, Abhinav Gupta, Cordelia Schmid, Ali Farhadi, and Karteek Alahari. Charades-ego: A large-scale dataset of paired third and first person videos. *arXiv*, 2018.

[167] Krishna Kumar Singh, Kayvon Fatahalian, and Alexei A Efros. Krishnacam: Using a longitudinal, single-person, egocentric dataset for scene understanding tasks. In *WACV*, 2016.

[168] Shuran Song and Jianxiong Xiao. Sliding shapes for 3d object detection in depth images. In *European conference on computer vision*, pages 634–651. Springer, 2014.

[169] Nitish Srivastava, Elman Mansimov, and Ruslan Salakhutdinov. Unsupervised learning of video representations using LSTMs. In *ICML*, 2015.

[170] Siddharth Srivastava, Eugene Fang, Lorenzo Riano, Rohan Chitnis, Stuart Russell, and Pieter Abbeel. Combined task and motion planning through an extensible planner-independent interface layer. In *ICRA*, 2014.

[171] Bradly C. Stadie, Sergey Levine, and Pieter Abbeel. Incentivizing exploration in reinforcement learning with deep predictive models. *arXiv*, 2015.

[172] Mike Stilman, Jan-Ullrich Schamburek, James Kuffner, and Tamim Asfour. Manipulation planning among movable obstacles. In *ICRA*, 2007.

[173] Ilya Sutskever, Oriol Vinyals, and Quoc V. Le. Sequence to sequence learning with neural networks. In *NIPS*, 2014.

[174] S. Thrun. Learning metric-topological maps for indoor mobile robot navigation. *Artif. Intell.*, 99(1):21–71, 1998.

[175] Sebastian Thrun and Lorien Pratt. Learning to learn: Introduction and overview. In *Learning to learn*,

pages 3–17. Springer, 1998.

[176] Yonglong Tian, Dilip Krishnan, and Phillip Isola. Contrastive multiview coding. *arXiv*, 2019.

[177] Jonathan Tremblay, Thang To, Balakumar Sundaralingam, Yu Xiang, Dieter Fox, and Stan Birchfield. Deep object pose estimation for semantic robotic grasping of household objects. In *Conference on Robot Learning*, pages 306–316, 2018.

[178] B. Ummenhofer, H. Zhou, J. Uhrig, N. Mayer, E. Ilg, A. Dosovitskiy, and T. Brox. Demon: Depth and motion network for learning monocular stereo. In *CVPR*, 2017.

[179] Subhashini Venugopalan, Marcus Rohrbach, Jeffrey Donahue, Raymond J. Mooney, Trevor Darrell, and Kate Saenko. Sequence to sequence - video to text. In *ICCV*, 2015.

[180] Carl Vondrick, Hamed Pirsiavash, and Antonio Torralba. Anticipating visual representations from unlabeled video. In *CVPR*, 2016.

[181] Carl Vondrick, Hamed Pirsiavash, and Antonio Torralba. Anticipating visual representations with unlabeled video. In *CVPR*, 2016.

[182] J. Walker, A. Gupta, and M. Hebert. Patch to the future: Unsupervised visual prediction. In *CVPR*, 2014.

[183] Jacob Walker, Abhinav Gupta, and Martial Hebert. Dense optical flow prediction from a static image. In *ICCV*, 2015.

[184] Jacob Walker, Kenneth Marino, Abhinav Gupta, and Martial Hebert. The pose knows: Video forecasting by generating pose futures. In *ICCV*, 2017.

[185] Fei Wang, Mengqing Jiang, Chen Qian, S. Yang, Cheng Li, Honggang Zhang, Xiaogang Wang, and Xiaoou Tang. Residual attention network for image classification. *2017 IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*, pages 6450–6458, 2017.

[186] He Wang, Sören Pirk, Ersin Yumer, Vladimir G Kim, Ozan Sener, Srinath Sridhar, and Leonidas J Guibas. Learning a generative model for multi-step human-object interactions from videos. In *Computer Graphics Forum*, volume 38, pages 367–378. Wiley Online Library, 2019.

[187] Sen Wang, Ronald Clark, Hongkai Wen, and Niki Trigoni. Deepvo: Towards end-to-end visual odometry with deep recurrent convolutional neural networks. In *ICRA*, 2017.

[188] Xiaolong Wang, David F. Fouhey, and Abhinav Gupta. Designing deep networks for surface normal

estimation. In *CVPR*, 2015.

[189] Xiaolong Wang and Abhinav Gupta. Unsupervised learning of visual representations using videos. In *ICCV*, 2015.

[190] Xiaolong Wang and Abhinav Gupta. Unsupervised learning of visual representations using videos. In *ICCV*, 2015.

[191] Luca Weihs, Aniruddha Kembhavi, Winson Han, Alvaro Herrasti, Eric Kolve, Dustin Schwenk, Roozbeh Mottaghi, and Ali Farhadi. Artificial agents learn flexible visual representations by playing a hiding game. *arXiv*, 2019.

[192] Luca Weihs, Jordi Salvador, Klemen Kotar, Unnat Jain, Kuo-Hao Zeng, Roozbeh Mottaghi, and Aniruddha Kembhavi. Allenact: A framework for embodied ai research. *arXiv*, 2020.

[193] Erik Wijmans, Abhishek Kadian, Ari Morcos, Stefan Lee, Irfan Essa, Devi Parikh, Manolis Savva, and Dhruv Batra. Dd-ppo: Learning near-perfect pointgoal navigators from 2.5 billion frames. In *ICLR*, 2020.

[194] Mitchell Wortsman, Kiana Ehsani, Mohammad Rastegari, Ali Farhadi, and Roozbeh Mottaghi. Learning to learn how to learn: Self-adaptive visual navigation using meta-learning. In *CVPR*, 2019.

[195] Jiajun Wu, Ilker Yildirim, Joseph J Lim, Bill Freeman, and Josh Tenenbaum. Galileo: Perceiving physical object properties by integrating a physics engine with deep learning. In *Advances in Neural Information Processing Systems*, pages 127–135, 2015.

[196] Yuxin Wu and Yuandong Tian. Training agent for first-person shooter game with actor-critic curriculum learning. In *ICLR*, 2017.

[197] Yi Wu, Yuxin Wu, Aviv Tamar, Stuart J. Russell, Georgia Gkioxari, and Yuandong Tian. Learning and planning with a semantic model. *arXiv*, 2018.

[198] Zhirong Wu, Yuanjun Xiong, Stella X Yu, and Dahua Lin. Unsupervised feature learning via non-parametric instance discrimination. In *CVPR*, 2018.

[199] Fei Xia, Chengshu Li, Roberto Martín-Martín, Or Litany, Alexander Toshev, and Silvio Savarese. Relmogen: Leveraging motion generation in reinforcement learning for mobile manipulation. *arXiv*, 2020.

[200] Fei Xia, William B Shen, Chengshu Li, Priya Kasimbeg, Micael Edmond Tchapmi, Alexander

Toshev, Roberto Martín-Martín, and Silvio Savarese. Interactive gibson benchmark: A benchmark for interactive navigation in cluttered environments. *IEEE Robotics and Automation Letters*, 2020.

[201] Fanbo Xiang, Yuzhe Qin, Kaichun Mo, Yikuan Xia, Hao Zhu, Fangchen Liu, Minghua Liu, Hanxiao Jiang, Yifu Yuan, He Wang, et al. Sapien: A simulated part-based interactive environment. In *CVPR*, 2020.

[202] Yu Xiang, Tanner Schmidt, Venkatraman Narayanan, and Dieter Fox. Posecnn: A convolutional neural network for 6d object pose estimation in cluttered scenes. In *Robotics: Science and Systems (RSS)*, 2018.

[203] Jianxiong Xiao, James Hays, Krista A. Ehinger, Aude Oliva, and Antonio Torralba. SUN database: Large-scale scene recognition from abbey to zoo. In *CVPR*, 2010.

[204] Jianxiong Xiao, James Hays, Krista A Ehinger, Aude Oliva, and Antonio Torralba. Sun database: Large-scale scene recognition from abbey to zoo. In *CVPR*, 2010.

[205] Dan Xie, Sinisa Todorovic, and Song-Chun Zhu. Inferring "dark matter" and "dark energy" from videos. In *ICCV*, 2013.

[206] Tianbing Xu, Qiang Liu, Liang Zhao, and Jian Peng. Learning to explore with meta-policy gradient. In *ICML*, 2018.

[207] Yanyu Xu, Yanbing Dong, Junru Wu, Zhengzhong Sun, Zhiru Shi, Jingyi Yu, and Shenghua Gao. Gaze prediction in dynamic 360° immersive videos. In *CVPR*, 2018.

[208] Zhenjia Xu, Zhanpeng He, Jiajun Wu, and Shuran Song. Learning 3d dynamic scene representations for robot manipulation. In *CoRL*, 2020.

[209] Ali Yahya, Adrian Li, Mrinal Kalakrishnan, Yevgen Chebotar, and Sergey Levine. Collective robot reinforcement learning with distributed asynchronous guided policy search. In *IROS*, 2017.

[210] Wei Yang, Xiaolong Wang, Ali Farhadi, Abhinav Gupta, and Roozbeh Mottaghi. Visual semantic navigation using scene priors. In *ICLR*, 2019.

[211] Wei Yang, Xiaolong Wang, Ali Farhadi, Abhinav Gupta, and Roozbeh Mottaghi. Visual semantic navigation using scene priors. In *ICLR*, 2019.

[212] Li Yao, Atousa Torabi, Kyunghyun Cho, Nicolas Ballas, Christopher J. Pal, Hugo Larochelle, and Aaron C. Courville. Describing videos by exploiting temporal structure. In *ICCV*, 2015.

[213] Ting Yao, Yiheng Zhang, Zhaofan Qiu, Yingwei Pan, and Tao Mei. Seco: Exploring sequence supervision for unsupervised representation learning. *arXiv*, 2020.

[214] Mark Yatskar, Luke Zettlemoyer, and Ali Farhadi. Situation recognition: Visual semantic role labeling for image understanding. In *IEEE Conference on Computer Vision and Pattern Recognition*, pages 5534–5542, 2016.

[215] Haonan Yu, Haichao Zhang, and Wei Xu. Interactive grounded language acquisition and generalization in a 2d world. In *ICLR*, 2018.

[216] Tianhe Yu, Chelsea Finn, Annie Xie, Sudeep Dasari, Tianhao Zhang, Pieter Abbeel, and Sergey Levine. One-shot imitation from observing humans via domain-adaptive meta-learning. In *RSS*, 2018.

[217] Tianhe Yu, Deirdre Quillen, Zhanpeng He, Ryan Julian, Karol Hausman, Chelsea Finn, and Sergey Levine. Meta-world: A benchmark and evaluation for multi-task and meta reinforcement learning. In *CoRL*, 2020.

[218] J. Yuen and A. Torralba. A data-driven approach for event prediction. In *ECCV*, 2010.

[219] Amir R. Zamir, Alexander Sax, William Shen, Leonidas J. Guibas, Jitendra Malik, and Silvio Savarese. Taskonomy: Disentangling task transfer learning. In *CVPR*, 2018.

[220] Kuo-Hao Zeng, William B. Shen, De-An Huang, Min Sun, and Juan Carlos Niebles. Visual forecasting by imitating dynamics in natural sequences. In *ICCV*, 2017.

[221] Richard Zhang, Phillip Isola, and Alexei A. Efros. Colorful image colorization. In *ECCV*, 2016.

[222] Richard Zhang, Phillip Isola, and Alexei A Efros. Colorful image colorization. In *ECCV*, 2016.

[223] Tinghui Zhou, Matthew Brown, Noah Snavely, and David G. Lowe. Unsupervised learning of depth and ego-motion from video. In *CVPR*, 2017.

[224] Xingyi Zhou, Dequan Wang, and Philipp Krähenbühl. Objects as points. *ArXiv*, abs/1904.07850, 2019.

[225] Yipin Zhou and Tamara L. Berg. Temporal perception and prediction in ego-centric video. In *ICCV*, 2015.

[226] Yuke Zhu, Daniel Gordon, Eric Kolve, Dieter Fox, Li Fei-Fei, Abhinav Gupta, Roozbeh Mottaghi, and Ali Farhadi. Visual semantic planning using deep successor representations. In *ICCV*, 2017.

[227] Yuke Zhu, Daniel Gordon, Eric Kolve, Dieter Fox, Li Fei-Fei, Abhinav Gupta, Roozbeh Mottaghi, and

Ali Farhadi. Visual semantic planning using deep successor representations. In *ICCV*, 2017.

[228] Chengxu Zhuang, Alex Lin Zhai, and Daniel Yamins. Local aggregation for unsupervised learning of visual embeddings. In *ICCV*, 2019.

[229] Silvia Zuffi, Angjoo Kanazawa, David Jacobs, and Michael J. Black. 3D menagerie: Modeling the 3D shape and pose of animals. In *CVPR*, 2017.